STATE OF MISSISSIPPI AIR POLLUTION CONTROL TITLE V PERMIT

TO OPERATE AIR EMISSIONS EQUIPMENT

THIS CERTIFIES THAT

Hunt Southland Refining Company 7539 Highway 11 North Lumberton, Mississippi Lamar County

has been granted permission to operate air emissions equipment in accordance with emission limitations, monitoring requirements and conditions set forth herein. This permit is issued in accordance with Title V of the Federal Clean Air Act (42 U.S.C.A. § 7401 - 7671) and the provisions of the Mississippi Air and Water Pollution Control Law (Section 49-17-1 et. seq., Mississippi Code of 1972), and the regulations and standards adopted and promulgated thereunder.

Permit Issued:

Effective Date: As specified herein.

MISSISSIPPI ENVIRONMENTAL QUALITY PERMIT BOARD

AUTHORIZED SIGNATURE MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Expires:[Date not to exceed 5 yrs from issuance]

Permit No.: 1440-00011

979 PER20160001

TABLE OF CONTENTS

SECTION 1.	GENERAL CONDITIONS	3
SECTION 2.	EMISSION POINTS & POLLUTION CONTROL DEVICES	12
SECTION 3.	EMISSION LIMITATIONS & STANDARDS	13
SECTION 4.	COMPLIANCE SCHEDULE	17
SECTION 5.	MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS	18
SECTION 6.	ALTERNATIVE OPERATING SCENARIOS	23
SECTION 7.	TITLE VI REQUIREMENTS	24

APPENDIX A LIST OF ABBREVIATIONS USED IN THIS PERMIT

OTHER IMPORTANT DOCUMENTS:

40 CFR 60, SUBPART DC—STANDARDS OF PERFORMANCE FOR SMALL INDUSTRIAL-COMMERCIAL-INSTITUTIONAL STEAM GENERATING UNITS

40 CFR 63, SUBPART ZZZZ—NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR RECIPROCATING INTERNAL COMBUSTION ENGINES

SECTION 1. GENERAL CONDITIONS

- 1.1 The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the Federal Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(a).)
- 1.2 It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(b).)
- 1.3 This permit and/or any part thereof may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(c).)
- 1.4 (a) This permit shall be reopened and revised under any of the following circumstances:
 - (1) Additional applicable requirements under the Federal Act become applicable to a major Title V source with a remaining permit term of 3 or more years. Such a reopening shall be completed no later than 18 months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended.
 - (2) Additional requirements (including excess emissions requirements) become applicable to an affected source under the acid rain program. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit.
 - (3) The Permit Board or EPA determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emission standards or other terms or conditions of the permit.
 - (4) The Administrator or the Permit Board determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
 - (b) Proceedings to reopen and issue this permit shall follow the same procedures as apply to initial permit issuance and shall only affect those parts of the permit for which cause to reopen exists. Such reopening shall be made as expeditiously as practicable.
 - (c) Reopenings shall not be initiated before a notice of such intent is provided to the Title V source by the DEQ at least 30 days in advance of the date that the permit is to be reopened, except that the Permit Board may provide a shorter time period in the case of an emergency.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.G)

- 1.5 The permittee shall furnish to the DEQ within a reasonable time any information the DEQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the DEQ copies of records required to be kept by the permittee or, for information to be confidential, the permittee shall furnish such records to DEQ along with a claim of confidentiality. The permittee may furnish such records directly to the Administrator along with a claim of confidentiality. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(e).)
- 1.6 This permit does not convey any property rights of any sort, or any exclusive privilege. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(d).)
- 1.7 The provisions of this permit are severable. If any provision of this permit, or the application of any provision of this permit to any circumstances, is challenged or held invalid, the validity of the remaining permit provisions and/or portions thereof or their application to other persons or sets of circumstances, shall not be affected thereby. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(5).)
- 1.8 The permittee shall pay to the DEQ an annual permit fee. The amount of fee shall be determined each year based on the provisions of regulated pollutants for fee purposes and the fee schedule specified in the Commission on Environmental Quality's order which shall be issued in accordance with the procedure outlined in Regulation 11 Miss. Admin. Code Pt. 2, Ch. 6.)
 - For purposes of fee assessment and collection, the permittee shall elect for actual or (a) allowable emissions to be used in determining the annual quantity of emissions unless the Commission determines by order that the method chosen by the applicant for calculating actual emissions fails to reasonably represent actual emissions. Actual emissions shall be calculated using emission monitoring data or direct emissions measurements for the pollutant(s); mass balance calculations such as the amounts of the pollutant(s) entering and leaving process equipment and where mass balance calculations can be supported by direct measurement of process parameters, such direct measurement data shall be supplied; published emission factors such as those relating release quantities to throughput or equipment type (e.g., air emission factors); or other approaches such as engineering calculations (e.g., estimating volatilization using published mathematical formulas) or best engineering judgments where such judgments are derived from process and/or emission data which supports the estimates of maximum actual emission. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.A(2).)
 - (b) If the Commission determines that there is not sufficient information available on a facility's emissions, the determination of the fee shall be based upon the permitted allowable emissions until such time as an adequate determination of actual emissions is made. Such determination may be made anytime within one year of the submittal of

actual emissions data by the permittee. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.A(2).) If at any time within the year the Commission determines that the information submitted by the permittee on actual emissions is insufficient or incorrect, the permittee will be notified of the deficiencies and the adjusted fee schedule. Past due fees from the adjusted fee schedule will be paid on the next scheduled quarterly payment time. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.D(2).)

- (c) The fee shall be due September 1 of each year. By July 1 of each year the permittee shall submit an inventory of emissions for the previous year on which the fee is to be assessed. The permittee may elect a quarterly payment method of four (4) equal payments; notification of the election of quarterly payments must be made to the DEQ by the first payment date of September 1. The permittee shall be liable for penalty as prescribed by State Law for failure to pay the fee or quarterly portion thereof by the date due. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.D.)
- (d) If in disagreement with the calculation or applicability of the Title V permit fee, the permittee may petition the Commission in writing for a hearing in accordance with State Law. Any disputed portion of the fee for which a hearing has been requested will not incur any penalty or interest from and after the receipt by the Commission of the hearing petition. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.C.)
- 1.9 No permit revision shall be required under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes for changes that are provided for in this permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(8).)
- 1.10 Any document required by this permit to be submitted to the DEQ shall contain a certification by a responsible official that states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.2.E.)
- 1.11 The permittee shall allow the DEQ, or an authorized representative, upon the presentation of credentials and other documents as may be required by law, to perform the following:
 - (a) enter upon the permittee's premises where a Title V source is located or emissionsrelated activity is conducted, or where records must be kept under the conditions of this permit;
 - (b) have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
 - (c) inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (d) as authorized by the Federal Act, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.C(2).)

- 1.12 Except as otherwise specified or limited herein, the permittee shall have necessary sampling ports and ease of accessibility for any new air pollution control equipment, obtained after May 8, 1970, and vented to the atmosphere. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.I(1).)
- 1.13 Except as otherwise specified or limited herein, the permittee shall provide the necessary sampling ports and ease of accessibility when deemed necessary by the Permit Board for air pollution control equipment that was in existence prior to May 8, 1970. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.I(2).)
- 1.14 Compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance where such applicable requirements are included and are specifically identified in the permit or where the permit contains a determination, or summary thereof, by the Permit Board that requirements specifically identified previously are not applicable to the source. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.F(1).)
- 1.15 Nothing in this permit shall alter or affect the following:
 - (a) the provisions of Section 303 of the Federal Act (emergency orders), including the authority of the Administrator under that section;
 - (b) the liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;
 - (c) the applicable requirements of the acid rain program, consistent with Section 408(a) of the Federal Act.
 - (d) the ability of EPA to obtain information from a source pursuant to Section 114 of the Federal Act. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.F(2).)
- 1.16 The permittee shall comply with the requirement to register a Risk Management Plan if permittee's facility is required pursuant to Section 112(r) of the Act to register such a plan. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.H.)
- 1.17 Expiration of this permit terminates the permittee's right to operate unless a timely and complete renewal application has been submitted. A timely application is one which is submitted at least six (6) months prior to expiration of the Title V permit. If the permittee submits a timely and complete application, the failure to have a Title V permit is not a violation of regulations until the Permit Board takes final action on the permit application. This protection shall cease to apply if, subsequent to the completeness determination, the permittee fails to submit by the deadline specified in writing by the DEQ any additional information identified as being needed to process the application. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.C(2)., R. 6.4.B., and R. 6.2.A(1)(c).)
- 1.18 The permittee is authorized to make changes within their facility without requiring a permit revision (ref: Section 502(b)(10) of the Act) if:

- (a) the changes are not modifications under any provision of Title I of the Act;
- (b) the changes do not exceed the emissions allowable under this permit;
- (c) the permittee provides the Administrator and the Department with written notification in advance of the proposed changes (at least seven (7) days, or such other time frame as provided in other regulations for emergencies) and the notification includes:
 - (1) a brief description of the change(s),
 - (2) the date on which the change will occur,
 - (3) any change in emissions, and
 - (4) any permit term or condition that is no longer applicable as a result of the change;
- (d) the permit shield shall not apply to any Section 502(b)(10) change. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.F(1).)
- 1.19 Should the Executive Director of the Mississippi Department of Environmental Quality declare an Air Pollution Emergency Episode, the permittee will be required to operate in accordance with the permittee's previously approved Emissions Reduction Schedule or, in the absence of an approved schedule, with the appropriate requirements specified in 11 Miss. Admin. Code Pt. 2, Ch. 3., "Regulations for the Prevention of Air Pollution Emergency Episodes" for the level of emergency declared. (Ref.: 11 Miss. Admin. Code Pt. 2, Ch. 3.)
- 1.20 Except as otherwise provided herein, a modification of the facility may require a Permit to Construct in accordance with the provisions of Regulations 11 Miss. Admin. Code Pt. 2, Ch. 2., "Permit Regulations for the Construction and/or Operation of Air Emissions Equipment", and may require modification of this permit in accordance with Regulations 11 Miss. Admin. Code Pt. 2, Ch. 6., "Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act". Modification is defined as "[a]ny physical change in or change in the method of operation of a facility which increases the actual emissions or the potential uncontrolled emissions of any air pollutant subject to regulation under the Federal Act emitted into the atmosphere by that facility or which results in the emission of any air pollutant subject to regulation under the Federal Act into the atmosphere not previously emitted. A physical change or change in the method of operation shall not include:
 - (a) routine maintenance, repair, and replacement;
 - (b) use of an alternative fuel or raw material by reason of an order under Sections 2 (a) and (b) of the Federal Energy Supply and Environmental Coordination Act of 1974 (or any superseding legislation) or by reason of a natural gas curtailment plan pursuant to the Federal Power Act;
 - (c) use of an alternative fuel by reason of an order or rule under Section 125 of the Federal Act;

- (d) use of an alternative fuel or raw material by a stationary source which:
 - (1) the source was capable of accommodating before January 6, 1975, unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR 51.166; or
 - (2) the source is approved to use under any permit issued under 40 CFR 52.21 or under regulations approved pursuant to 40 CFR 51.166;
- (e) an increase in the hours of operation or in the production rate unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Subpart I or 40 CFR 51.166; or
- (f) any change in ownership of the stationary source."
- 1.21 Any change in ownership or operational control must be approved by the Permit Board. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.D(4).)
- 1.22 This permit is a Federally approved operating permit under Title V of the Federal Clean Air Act as amended in 1990. All terms and conditions, including any designed to limit the source's potential to emit, are enforceable by the Administrator and citizens under the Federal Act as well as the Commission. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.B(1).)
- 1.23 Except as otherwise specified or limited herein, the open burning of residential, commercial, institutional, or industrial solid waste, is prohibited. This prohibition does not apply to infrequent burning of agricultural wastes in the field, silvicultural wastes for forest management purposes, land-clearing debris, debris from emergency clean-up operations, and ordnance. Open burning of land-clearing debris must not use starter or auxiliary fuels which cause excessive smoke (rubber tires, plastics, etc.); must not be performed if prohibited by local ordinances; must not cause a traffic hazard; must not take place where there is a High Fire Danger Alert declared by the Mississippi Forestry Commission or Emergency Air Pollution Episode Alert imposed by the Executive Director and must meet the following buffer zones.
 - (a) Open burning without a forced-draft air system must not occur within 500 yards of an occupied dwelling.
 - (b) Open burning utilizing a forced-draft air system on all fires to improve the combustion rate and reduce smoke may be done within 500 yards of but not within 50 yards of an occupied dwelling.
 - (c) Burning must not occur within 500 yards of commercial airport property, private air fields, or marked off-runway aircraft approach corridors unless written approval to conduct burning is secured from the proper airport authority, owner or operator. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.G.)
- 1.24 Except as otherwise specified herein, the permittee shall be subject to the following

provision with respect to emergencies.

- (a) Except as otherwise specified herein, an "emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.
- (b) An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions specified in (c) following are met.
- (c) The affirmative defense of emergency shall be demonstrated through properly signed contemporaneous operating logs, or other relevant evidence that include information as follows:
 - (1) an emergency occurred and that the permittee can identify the cause(s) of the emergency;
 - (2) the permitted facility was at the time being properly operated;
 - (3) during the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements in the permit; and
 - (4) the permittee submitted notice of the emergency to the DEQ within 2 working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.
- (d) In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (e) This provision is in addition to any emergency or upset provision contained in any applicable requirement specified elsewhere herein. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.G.)
- 1.25 Except as otherwise specified herein, the permittee shall be subject to the following provisions with respect to upsets, startups, shutdowns and maintenance.
 - (a) Upsets (as defined by 11 Miss. Admin. Code Pt. 2, R. 1.2.KK.)
 - (1) The occurrence of an upset constitutes an affirmative defense to an enforcement action brought for noncompliance with emission standards or other requirements of Applicable Rules and Regulations or any applicable permit if the permittee demonstrates through properly signed contemporaneous operating logs, or other

relevant evidence that include information as follows:

- (i) an upset occurred and that the permittee can identify the cause(s) of the upset;
- (ii) the source was at the time being properly operated;
- (iii) during the upset the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements of Applicable Rules and Regulations or any applicable permit;
- (iv) the permittee submitted notice of the upset to the DEQ within 5 working days of the time the upset began; and
- (v) the notice of the upset shall contain a description of the upset, any steps taken to mitigate emissions, and corrective actions taken.
- (2) In any enforcement proceeding, the permittee seeking to establish the occurrence of an upset has the burden of proof.
- (3) This provision is in addition to any upset provision contained in any applicable requirement.
- (b) Startups and Shutdowns (as defined by 11 Miss. Admin. Code Pt. 2, R. 1.2.HH. & R. 1.2.CC.)
 - (1) Startups and shutdowns are part of normal source operation. Emissions limitations applicable to normal operation apply during startups and shutdowns except as follows:
 - (i) when sudden, unavoidable breakdowns occur during a startup or shutdown, the event may be classified as an upset subject to the requirements above;
 - (ii) when a startup or shutdown is infrequent, the duration of excess emissions is brief in each event, and the design of the source is such that the period of excess emissions cannot be avoided without causing damage to equipment or persons; or
 - (iii) when the emissions standards applicable during a startup or shutdown are defined by other requirements of Applicable Rules and Regulations or any applicable permit.
 - (2) In any enforcement proceeding, the permittee seeking to establish the applicability of any exception during a startup or shutdown has the burden of proof.
 - (3) In the event this startup and shutdown provision conflicts with another applicable requirement, the more stringent requirement shall apply.
- (c) Maintenance.

- (1) Maintenance should be performed during planned shutdown or repair of process equipment such that excess emissions are avoided. Unavoidable maintenance that results in brief periods of excess emissions and that is necessary to prevent or minimize emergency conditions or equipment malfunctions constitutes an affirmative defense to an enforcement action brought for noncompliance with emission standards, or other regulatory requirements if the permittee can demonstrate the following:
 - (i) the permittee can identify the need for the maintenance;
 - (ii) the source was at the time being properly operated;
 - (iii) during the maintenance the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements of Applicable Rules and Regulations or any applicable permit;
 - (iv) the permittee submitted notice of the maintenance to the DEQ within 5 working days of the time the maintenance began or such other times as allowed by DEQ; and
 - (v) the notice shall contain a description of the maintenance, any steps taken to mitigate emissions, and corrective actions taken.
- (2) In any enforcement proceeding, the permittee seeking to establish the applicability of this section has the burden of proof.
- (3) In the event this maintenance provision conflicts with another applicable requirement, the more stringent requirement shall apply. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.10.)
- 1.26 The permittee shall comply with all applicable standards for demolition and renovation activities pursuant to the requirements of 40 CFR Part 61, Subpart M, as adopted by reference in Regulation 11 Miss Admin. Code Pt. 2, R. 1.8. The permittee shall not be required to obtain a modification of this permit in order to perform the referenced activities

SECTION 2. EMISSION POINTS & POLLUTION CONTROL DEVICES

Emission Point	Description			
AA-007	16.0 MMBTU/hr Petro-Chem Iso Flow #5 Asphalt Natural Gas-Fired Heater (Reference No. E-7)			
AA-013	26.0 MMBTU/hr Cleaver Brooks Natural Gas-Fired (LPG/Fuel Oil Capable) Boiler (Reference No. E-18)			
AA-014	4.0 MMBTU/hr Heatec Natural Gas-Fired Hot Oil Heater (Reference No. E-19)			
AA-015	1.0 MMBTU/hr Natural Gas-Fired Water Heater (Reference No. E-20)			
AA-020	24.6 MMBTU/hr Cleaver Brooks Natural Gas-Fired Standby Boiler (Reference No. E-22)			
AA-021	3.0 MMBTU/hr Heat-Tec Natural Gas-Fired PMA Hot Oil Heater (Reference No. E-23)			
AA-022	324 hp Diesel Emergency Generator (existing compression ignition engine constructed in 1974)			
BB-011	109,200 Gallon MC-0 Asphalt Fixed Roof Storage Tank (Reference No. 2663)			
BB-012	105,000 Gallon Storm Water Fixed Roof Storage Tank (Reference No. 2504)			
BB-101	25,200 Gallon Asphalt Fixed Roof Storage Tank (Reference No.600)			
BB-107	42,000 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 1001)			
BB-108	42,000 Gallon Asphalt Emulsions Fixed Roof Storage Tank (Reference No. 1002)			
BB-109	42,000 Gallon Asphalt Emulsions Fixed Roof Storage Tank (Reference No. 1003)			
BB-110	42,000 Gallon Asphalt Emulsions Fixed Roof Storage Tank (Reference No. 1004)			
BB-111	42,000 Gallon Asphalt Emulsions Fixed Roof Storage Tank (Reference No. 1005)			
BB-112	42,000 Gallon Asphalt Emulsions Fixed Roof Storage Tank (Reference No. 1006)			
BB-113	42,000 Gallon Asphalt Emulsions Fixed Roof Storage Tank (Reference No. 1007)			
BB-114	42,000 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 1008)			
BB-115	42,000 Gallon Asphalt Emulsions Fixed Roof Storage Tank (Reference No. 1009)			
BB-116	42,000 Gallon Asphalt Emulsions Fixed Roof Storage Tank (Reference No. 1010)			
BB-117	42,000 Gallon Asphalt Emulsions Fixed Roof Storage Tank (Reference No. 1011)			
BB-118	100,800 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 2401)			
BB-122	109,200 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 2662)			
BB-123	420,000 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 10002)			
BB-124	420,000 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 10003)			
BB-126	2,100,000 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 50001)			
BB-127	2,100,000 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 50002)			
BB-128	2,310,000 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 55001)			
BB-129	2,310,000 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 55002)			
BB-130	105,000 Gallon Slop Fixed Roof Storage Tank (Reference No. 2502)			
BB-131	420,000 Gallon Asphalt Fixed Roof Storage Tank (Reference No. 10001)			
BB-132	230,160 Gallon Diesel (Distillate) Fuel Fixed Roof Storage Tank (Reference No. 5480)			

SECTION 3. EMISSION LIMITATIONS & STANDARDS

A. Facility-Wide Emission Limitations & Standards

- 3.A.1 Except as otherwise specified or limited herein, the permittee shall not cause, permit, or allow the emission of smoke from a point source into the open air from any manufacturing, industrial, commercial or waste disposal process which exceeds forty (40) percent opacity subject to the exceptions provided in (a) & (b).
 - (a) Startup operations may produce emissions which exceed 40% opacity for up to fifteen (15) minutes per startup in any one hour and not to exceed three (3) startups per stack in any twenty-four (24) hour period.
 - (b) Emissions resulting from soot blowing operations shall be permitted provided such emissions do not exceed 60 percent opacity, and provided further that the aggregate duration of such emissions during any twenty-four (24) hour period does not exceed ten (10) minutes per billion BTU gross heating value of fuel in any one hour. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.A.)
- 3.A.2 Except as otherwise specified or limited herein, the permittee shall not cause, allow, or permit the discharge into the ambient air from any point source or emissions, any air contaminant of such opacity as to obscure an observer's view to a degree in excess of 40% opacity, equivalent to that provided in Paragraph 3.A.1. This shall not apply to vision obscuration caused by uncombined water droplets. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.B.)

Emission Point(s)	Applicable Requirement	Condition Number(s)	Pollutant/ Parameter	Limit/Standard
AA-014 AA-015 AA-021	11 Miss. Admin. Code Pt. 2, R.1.3.D(1)(a).	3.B.1	РМ	0.6 lbs/MMBTU
AA-007 AA-013 AA-020	11 Miss. Admin. Code Pt. 2, R.1.3.D(1)(b).	3.B.2	РМ	$E = 0.8808 \times I^{-0.1667}$
AA-007 AA-013 AA-014 AA-015 AA-020 AA-021	11 Miss. Admin. Code Pt. 2, R.1.4.A(1).	3.B.3	SO_2	4.8 lbs/MMBTU

B. <u>Emission Point Specific Emission Limitations & Standards</u>

Page 14 of 25 Permit No. 1440-00011

Emission Point(s)	Applicable Requirement	Condition Number(s)	Pollutant/ Parameter	Limit/Standard
Facility Wide	Construction Permit issued February 27, 2009	3.B.4	Fuel	The permittee shall not burn any Fuel Oil with sulfur content greater than 0.05% by weight except during periods of Natural Gas Curtailment by suppliers or during periods approved by EPA for purposes of test runs and operator training. During such periods, the permittee shall not burn any Fuel Oil with greater than 5.0% sulfur by weight
AA-013 AA-020	NSPS Subpart Dc 40 CFR 60.40c(a)	3.B.5	Operation	Applicability
AA-013	Title V Operating Permit issued January 3, 2012	3.B.9	Fuel	Natural Gas/LPG/Fuel Oil
AA-020	Construction Permit issued May 25, 1999	3.B.6	Fuel	Fuel other than natural gas is prohibited
	NESHAP Subpart ZZZZ 40 CFR 63.6580	3.B.7	Operation	Applicability
AA-022	NESHAP Subpart ZZZ 40 CFR 63.6603(a) and Table 2d.4, Subpart ZZZZ	3.B.8	Maintenance Requirements	Change oil and filter every 500 hours of operation or annually; inspect air cleaner every 1,000 hours of operation or annually; and inspect all hoses and belts every 500 hours of operation or annually

3.B.1 For Emission Points AA-014, AA-015, and AA-021, the maximum permissible emission of ash and/or particulate matter from fossil fuel burning installations of less than 10 million BTU per hour heat input shall not exceed 0.6 pounds per million BTU per hour heat input.

(Ref.: 11 Miss. Admin. Code Pt. 2, R.1.3.D(1)(a).)

3.B.2 For Emission Points AA-007, AA-013, and AA-020, the maximum permissible emission of ash and/or particulate matter shall not exceed an emission rate as determined by the relationship

 $E = 0.8808 \times I^{-0.1667}$

where E is the emission rate in pounds per million BTU per hour heat input and I is the heat input in millions of BTU per hour.

(Ref.: 11 Miss. Admin. Code Pt. 2, R.1.3.D(1)(b).)

3.B.3 For Emission Points AA-007, AA-013, AA-014, AA-015, AA-020, and AA-021, the discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide) per million BTU heat input.

(Ref.: 11 Miss. Admin. Code Pt. 2, R.1.4.A(1).)

3.B.4 For the entire facility, the permittee shall not burn Fuel Oil except during periods of Natural Gas Curtailment by suppliers or during periods approved by EPA for purposes of test runs and operator training. During such periods, the permittee shall not burn any Fuel Oil with greater than 5.0% sulfur by weight. Fuel Oil shall mean any liquid fossil fuel with a sulfur content greater than 0.05% by weight.

(Ref.: Construction Permit issued February 27, 2009)

3.B.5 For Emission Points AA-013 and AA-020, the permittee is subject to and shall comply with the applicable requirements of the New Source Performance Standards specified in 40 CFR Part 60, Subpart Dc (Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units) and in 40 CFR Part 60, Subpart A (General Provisions).

(Ref.: 40 CFR 60.40c(a), Subpart Dc)

3.B.6 For Emission Point AA-020, the permittee shall limit fuel usage to natural gas.

(Ref.: Construction Permit issued May 25, 1999)

3.B.7 For Emission Point AA-022, the permittee is subject to and shall comply with the applicable requirements of the National Emission Standards for Hazardous Air Pollutants specified in 40 CFR 63, Subpart ZZZZ (Stationary Reciprocating Internal Combustion Engines) and in 40 CFR Part 63, Subpart A (General Provisions).

(Ref.: 40 CFR 63.6585, Subpart ZZZZ)

- 3.B.8 For Emission Point AA-022, the permittee shall:
 - (a) Change oil and filter every 500 hours of operation or annually, whichever comes first;
 - (b) Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first; and
 - (c) Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.

(Ref.: 40 CFR 63.6603(a) and Table 2d.4, Subpart ZZZZ)

3.B.9 For Emission Point AA-013, the permittee shall not burn Fuel Oil, except during periods of Natural Gas Curtailment and periods of DOT required maintenance of the natural gas pipeline, during which the facility shall burn only liquefied petroleum gas or low sulfur distillate.

(Ref.: Title V Operating Permit issued January 3, 2012)

C. Insignificant and Trivial Activity Emission Limitations & Standards

Applicable Requirement	Condition Number(s)	Pollutant/ Parameter	Limit/Standard
------------------------	------------------------	-------------------------	----------------

Applicable Requirement	Condition Number(s)	Pollutant/ Parameter	Limit/Standard
11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(a).	3.C.1	РМ	0.6 lbs/MMBTU
11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).	3.C.2	SO ₂	4.8 lbs/MMBTU

- 3.C.1 The maximum permissible emission of ash and/or particulate matter from fossil fuel burning installations of less than 10 million BTU per hour heat input shall not exceed 0.6 pounds per million BTU per hour heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(a).)
- 3.C.2 The maximum discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide) per million BTU heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).)

There are no other requirements applicable to the insignificant activities listed in the source's Title V permit application.

SECTION 4. COMPLIANCE SCHEDULE

- 4.1 Unless otherwise specified herein, the permittee shall be in compliance with all requirements contained herein upon issuance of this permit.
- 4.2 Except as otherwise specified herein, the permittee shall submit to the Permit Board and to the Administrator of EPA Region IV a certification of compliance with permit terms and conditions, including emission limitations, standards, or work practices, by January 31 for the preceding calendar year. Each compliance certification shall include the following:
 - (a) the identification of each term or condition of the permit that is the basis of the certification;
 - (b) the compliance status;
 - (c) whether compliance was continuous or intermittent;
 - (d) the method(s) used for determining the compliance status of the source, currently and over the applicable reporting period;
 - (e) such other facts as may be specified as pertinent in specific conditions elsewhere in this permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.C(5)(a), (c), & (d).)

SECTION 5. MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS

- A. <u>General Monitoring, Recordkeeping and Reporting Requirements</u>
- 5.A.1 The permittee shall install, maintain, and operate equipment and/or institute procedures as necessary to perform the monitoring and recordkeeping specified below.
- 5.A.2 In addition to the recordkeeping specified below, the permittee shall include with all records of required monitoring information the following:
 - (a) the date, place as defined in the permit, and time of sampling or measurements;
 - (b) the date(s) analyses were performed;
 - (c) the company or entity that performed the analyses;
 - (d) the analytical techniques or methods used;
 - (e) the results of such analyses; and
 - (f) the operating conditions existing at the time of sampling or measurement. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(b)(1).)
- 5.A.3 Except where a longer duration is specified in an applicable requirement, the permittee shall retain records of all required monitoring data and support information for a period of at least five (5) years from the date of the monitoring sample, measurement, report, or application. Support information includes all calibration and maintenance records, all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by the permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(b)(2).)
- 5.A.4 Except as otherwise specified herein, the permittee shall submit reports of any required monitoring by July 31 and January 31 for the preceding six-month period. All instances of deviations from permit requirements must be clearly identified in such reports and all required reports must be certified by a responsible official consistent with 11 Miss. Admin. Code Pt. 2, R. 6.2.E. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c)(1).)
- 5.A.5 Except as otherwise specified herein, the permittee shall report all deviations from permit requirements, including those attributable to upsets, the probable cause of such deviations, and any corrective actions or preventive measures taken. Said report shall be made within five (5) days of the time the deviation began. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c)(2).)
- 5.A.6 Except as otherwise specified herein, the permittee shall perform emissions sampling and analysis in accordance with EPA Test Methods and with any continuous emission monitoring requirements, if applicable. All test methods shall be those versions or their equivalents approved by the DEQ and the EPA.
- 5.A.7 The permittee shall maintain records of any alterations, additions, or changes in

equipment or operation.

B. <u>Specific Monitoring, Recordkeeping, and Reporting Requirements</u>

Emission Point(s)	Applicable Requirement	Condition Number	Pollutant/Parameter Monitored	Monitoring/Recordkeeping/Reporting Requirement
Facility Wide	Construction Permit issued February 27, 2009	5.B.1	Fuel	Notification of estimate of Fuel Oil to be burned during test runs or operator training
AA-013 AA-020	NSPS Subpart Dc 40 CFR 60.48c(g) and (i)	5.B.2	Fuel	Record and maintain records for amount of fuel combusted
	NSPS Subpart Dc 40 CFR 60.48c(j)	5.B.3		Reporting period for reports is each six- month period
AA-013	40 CFR 60.48c(e) and (f)	5.B.4	Fuel	Maintain records of fuel supplier certifications
		5.B.5		Reporting of fuel supplier certifications
	NESHAP Subpart ZZZZ 40 CFR 63.6625(e)	5.B.6	НАР	Maintenance
	40 CFR 63.6625(f)	5.B.7		Installation
AA-022	40 CFR 63.6625(h)	5.B.8		Operation
	40 CFR 63.6605	5.B.9		Continuous Compliance
	40 CFR 63.6640(f)	5.B.10		Continuous Compliance
	40 CFR 63.6655	5.B.11		Recordkeeping

5.B.1 For the entire facility, the permittee shall notify EPA and MDEQ and provide an estimate of the amount of Fuel Oil to be burned at least thirty (30) days prior to conducting test runs or operator training during which Fuel Oil will be burned.

(Ref.: Construction Permit issued February 27, 2009)

5.B.2 For Emission Points AA-013 and AA-020, the permittee shall record and maintain records of the amount of each fuel combusted during each calendar month, as provided by 40 CFR 60.48c(g). All records required under this section shall be maintained by the owner or operator of the affected facility for a period of two years following the date of such record.

(Ref.: 40 CFR 60.48c(g) and (i), Subpart Dc)

5.B.3 For Emission Points AA-013, the reporting period for reports required by 40 CFR 60.48c is each six-month period. All reports shall be submitted to MDEQ and postmarked by the 31st of January and July for the preceding six-month period.

(Ref.: 40 CFR 60.48c(j), Subpart Dc)

5.B.4 For Emission Point AA-013, the permittee shall record and maintain records of the fuel supplier certifications for periods of firing Fuel Oil.

(Ref.: 40 CFR 60.48c(e) and (f), Subpart Dc)

- 5.B.5 For Emission Point AA-013, the permittee shall submit a report to MDEQ which includes the calendar dates covered in the reporting period and records of fuel supplier certifications. A fuel supplier certification shall include the following information:
 - (a) For distillate oil:
 - (1) The name of the oil supplier;
 - (2) A statement from the oil supplier that the oil complies with the specifications under the definition of distillate oil in 40 CFR 60.41c; and
 - (3) The sulfur content of the oil.
 - (b) For natural gas:
 - (1) The name of the supplier of the fuel;
 - (2) The potential sulfur emissions rate of the fuel in ng/J heat input;
 - (3) The method used to determine the potential sulfur emissions rate of the fuel.

In addition to records of fuel supplier certification, the report shall include a certified statement signed by the owner or operator of the facility that the records of fuel supplier certifications submitted represent all of the fuel combusted during the reporting periods.

(Ref.: 40 CFR 60.48c(e) and (f), Subpart Dc)

5.B.6 For Emission Point AA-022, the permittee shall operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.

(Ref.: 40 CFR 63.6625(e), Subpart ZZZZ)

5.B.7 For Emission Point AA-022, the permittee shall install a non-resettable hour meter if one is not already installed.

(Ref.: 40 CFR 63.6625(f), Subpart ZZZZ)

5.B.8 For Emission Point AA-022, the permittee shall minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes.

(Ref.: 40 CFR 63.6225(h), Subpart ZZZZ)

5.B.9 For Emission Point AA-022, the permittee shall be in compliance with the operating limitations at all times. The permittee shall operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions.

(Ref.: 40 CFR 63.6605, Subpart ZZZZ)

- 5.B.10 For Emission Point AA-022, the permittee shall operate the emergency stationary RICE according to the requirements below. Any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year is prohibited. If the permittee does not operate the engine according to the requirements below, the engine will not be considered an emergency engine and will need to meet all requirements for non-emergency engines.
 - (a) There is no time limit on the use of emergency stationary RICE in emergency situations.
 - (b) The permittee may operate the emergency stationary RICE for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by Federal, State or local government, the manufacturer, the vendor, or the insurance company associated with the engine. Maintenance checks and readiness testing of such units is limited to 100 hours per year. The permittee may petition the MDEQ for approval of additional hours for maintenance checks and readiness testing, but a petition is not required if the permittee maintains records indicating that Federal, State, or local standards require maintenance and testing of emergency RICE beyond 100 hours a year.
 - The permittee may operate the emergency stationary RICE up to 50 hours per year in (c) non-emergency situations, but those 50 hours are counted towards the 100 hours per year provided for maintenance and testing. The 50 hours per year for non-emergency situations cannot be used for peak shaving or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity; except that permittees may operate the emergency engine for a maximum of 15 hours per year as part of a demand response program if the regional transmission organization or equivalent balancing authority and transmission operator has determined there are emergency conditions that could lead to a potential electrical blackout, such as unusually low frequency, equipment overload, capacity or energy deficiency, or unacceptable voltage level. The engine may not be operated for more than 30 minutes prior to the time when the emergency condition is expected to occur, and the engine operation must be terminated immediately after the facility is notified that the emergency condition is no longer imminent. The 15 hours per year of demand response operation are counted as part of the 50 hours of operation per year provided for non-emergency situations. The supply of emergency power to another entity or entities pursuant to financial arrangement is not limited by this paragraph, as long as the power provided by the financial arrangement is limited to emergency power.

(Ref.: 40 CFR 63.6640(f), Subpart ZZZZ)

- 5.B.11 For Emission Point AA-022, the permittee shall keep the following records:
 - (a) A copy of each notification and report that the permittee submitted to comply with

this subpart, including all documentation supporting any Initial Notification or Notification of Compliance Status that was submitted, according to the requirement in (63.10(b)(2)(xiv)).

- (b) Records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment.
- (c) Records of performance tests and performance evaluations as required in §63.10(b)(2)(viii).
- (d) Records of all required maintenance performed on the air pollution control and monitoring equipment.
- (e) Records of actions taken during periods of malfunction to minimize emissions in accordance with \$63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.

The permittee shall keep the records required in Table 6 of this subpart to show continuous compliance with each emission or operating limitation that applies to you.

The permittee shall keep records of the maintenance conducted on the stationary RICE in order to demonstrate that you operated and maintained the stationary RICE and after-treatment control device (if any) according to your own maintenance plan.

The permittee shall keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. If the engine is used for demand response operation, the owner or operator must keep records of the notification of the emergency situation, and the time the engine was operated as part of the demand response.

(Ref.: 40 CFR 63.6655(a), (d), (e), and (f), Subpart ZZZZ)

SECTION 6. ALTERNATIVE OPERATING SCENARIOS

6.1 None permitted.

SECTION 7. TITLE VI REQUIREMENTS

The following are applicable or potentially applicable requirements originating from Title VI of the Clean Air Act – Stratospheric Ozone Protection. The full text of the referenced regulations may be found on-line at <u>http://ecfr.gpoaccess.gov</u> under Title 40, or DEQ shall provide a copy upon request from the permittee.

- 7.1 If the permittee produces, transforms, destroys, imports or exports a controlled substance or imports or exports a controlled product, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart A Production and Consumption Controls.
- 7.2 If the permittee performs service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart B Servicing of Motor Vehicle Air Conditioners.
- 7.3 The permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart E The Labeling of Products Using Ozone-Depleting Substances, for the following containers and products:
 - (a) All containers in which a class I or class II substance is stored or transported;
 - (b) All products containing a class I substance; and
 - (c) All products directly manufactured with a process that uses a class I substance, unless otherwise exempted by this subpart or, unless EPA determines for a particular product that there are no substitute products or manufacturing processes for such product that do not rely on the use of a class I substance, that reduce overall risk to human health and the environment, and that are currently or potentially available. If the EPA makes such a determination for a particular product, then the requirements of this subpart are effective for such product no later than January 1, 2015.
- 7.4 If the permittee performs any of the following activities, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart F Recycling and Emissions Reduction:
 - (a) Servicing, maintaining, or repairing appliances;
 - (b) Disposing of appliances, including small appliances and motor vehicle air conditioners; or
 - (c) Refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturers of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, persons selling class I or class II refrigerants or offering class I or class II refrigerants for sale, and persons purchasing class I or class II refrigerants.
- 7.5 The permittee shall be allowed to switch from any ozone-depleting substance to any acceptable alternative that is listed in the Significant New Alternatives Policy (SNAP)

program promulgated pursuant to 40 CFR Part 82, Subpart G – Significant New Alternatives Policy Program. The permittee shall also comply with any use conditions for the acceptable alternative substance.

- 7.6 If the permittee performs any of the following activities, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart H Halon Emissions Reduction:
 - (a) Any person testing, servicing, maintaining, repairing, or disposing of equipment that contains halons or using such equipment during technician training;
 - (b) Any person disposing of halons;
 - (c) Manufacturers of halon blends; or
 - (d) Organizations that employ technicians who service halon-containing equipment.

APPENDIX A

List of Abbreviations Used In this Permit

1137 41		
11 Miss. Adn		r Emission Regulations for the Prevention, Abatement, and Control Air Contaminants
11 Miss. Adn		rmit Regulations for the Construction and/or Operation of Air
11 Mice Adm		nissions Equipment
		egulations for the Prevention of Air Pollution Emergency Episodes nbient Air Quality Standards
		egulations for the Prevention of Significant Deterioration of Air
11 ivii35. 7 tui		ality
11 Miss. Adm		r Emissions Operating Permit Regulations for the Purposes of Title of the Federal Clean Air Act
11 Miss. Adn		cid Rain Program Permit Regulations for Purposes of Title IV of the
		deral Clean Air Act
BACT	Best Available Control Tech	
CEM	Continuous Emission Monito	
CEMS	Continuous Emission Monito	bring System
CFR	Code of Federal Regulations	
CO	Carbon Monoxide	
COM	Continuous Opacity Monitor	
COMS	Continuous Opacity Monitor	
DEQ	Mississippi Department of E	
EPA	United States Environmental	
gr/dscf	Grains Per Dry Standard Cub	pic Foot
HP	Horsepower	
HAP	Hazardous Air Pollutant	
lbs/hr	Pounds per Hour	
M or K	Thousand	
MACT	Maximum Achievable Contro	ol Technology
MM	Million	
MMBTUH	Million British Thermal Unit	is per Hour
NA	Not Applicable	
NAAQS	National Ambient Air Qualit	
NESHAP		ls For Hazardous Air Pollutants, 40 CFR 61
	Or National Emission Standards	For Hazardous Air Pollutants for Source Categories, 40 CFR 63
NMVOC	Non-Methane Volatile Organ	
NO _x	Nitrogen Oxides	ne compounds
NSPS	New Source Performance Sta	undards 40 CFR 60
O&M	Operation and Maintenance	
PM	Particulate Matter	
PM_{10}	Particulate Matter less than 1	0 um in diameter
ppm	Parts per Million	
PSD	Prevention of Significant Det	terioration 40 CFR 52
SIP	State Implementation Plan	
SO ₂	Sulfur Dioxide	
TPY	Tons per Year	
TRS	Total Reduced Sulfur	
VEE	Visible Emissions Evaluation	1
VHAP	Volatile Hazardous Air Pollu	
VOC	Volatile Organic Compound	
	: shame organic compound	