STATE OF MISSISSIPPI AIR POLLUTION CONTROL TITLE V PERMIT

TO OPERATE AIR EMISSIONS EQUIPMENT

THIS CERTIFIES THAT

Tellus Operating Group, LLC Tallahala 4-7 Number 1 Tank Battery Smith County Road 95 Sylvarena, Mississippi (Smith County)

has been granted permission to operate air emissions equipment in accordance with emission limitations, monitoring requirements and conditions set forth herein. This permit is issued in accordance with Title V of the Federal Clean Air Act (42 U.S.C.A. § 7401 - 7671) and the provisions of the Mississippi Air and Water Pollution Control Law (Section 49-17-1 et. seq., Mississippi Code of 1972), and the regulations and standards adopted and promulgated thereunder.

Permit Issued: SEP 2 7 2016

Effective Date: As specified herein.

MISSISSIPPI ENVIRONMENTAL QUALITY PERMIT BOARD

AUTHORIZED SIGNATURE MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Expires: August 31, 2021

Permit No.: 2500-00088

TABLE OF CONTENTS

SECTION 1.	GENERAL CONDITIONS	.3
SECTION 2.	EMISSION POINTS & POLLUTION CONTROL DEVICES 1	13
SECTION 3.	EMISSION LIMITATIONS & STANDARDS	14
SECTION 4.	COMPLIANCE SCHEDULE	17
SECTION 5.	MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS	8
SECTION 6.	ALTERNATIVE OPERATING SCENARIOS	21
SECTION 7.	TITLE VI REQUIREMENTS	22

APPENDIX A LIST OF ABBREVIATIONS USED IN THIS PERMIT

SECTION 1. GENERAL CONDITIONS

- 1.1 The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the Federal Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(a).)
- 1.2 It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(b).)
- 1.3 This permit and/or any part thereof may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(c).)
- 1.4 (a) This permit shall be reopened and revised under any of the following circumstances:
 - (1) Additional applicable requirements under the Federal Act become applicable to a major Title V source with a remaining permit term of 3 or more years. Such a reopening shall be completed no later than 18 months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended.
 - (2) Additional requirements (including excess emissions requirements) become applicable to an affected source under the acid rain program. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit.
 - (3) The Permit Board or EPA determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emission standards or other terms or conditions of the permit.
 - (4) The Administrator or the Permit Board determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
 - (b) Proceedings to reopen and issue this permit shall follow the same procedures as apply to initial permit issuance and shall only affect those parts of the permit for which cause to reopen exists. Such reopening shall be made as expeditiously as

practicable.

(c) Reopenings shall not be initiated before a notice of such intent is provided to the Title V source by the DEQ at least 30 days in advance of the date that the permit is to be reopened, except that the Permit Board may provide a shorter time period in the case of an emergency.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.G)

- 1.5 The permittee shall furnish to the DEQ within a reasonable time any information the DEQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the DEQ copies of records required to be kept by the permittee or, for information to be confidential, the permittee shall furnish such records to DEQ along with a claim of confidentiality. The permittee may furnish such records directly to the Administrator along with a claim of confidentiality. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(e).)
- 1.6 This permit does not convey any property rights of any sort, or any exclusive privilege. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(d).)
- 1.7 The provisions of this permit are severable. If any provision of this permit, or the application of any provision of this permit to any circumstances, is challenged or held invalid, the validity of the remaining permit provisions and/or portions thereof or their application to other persons or sets of circumstances, shall not be affected thereby. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(5).)
- 1.8 The permittee shall pay to the DEQ an annual permit fee. The amount of fee shall be determined each year based on the provisions of regulated pollutants for fee purposes and the fee schedule specified in the Commission on Environmental Quality's order which shall be issued in accordance with the procedure outlined in Regulation 11 Miss. Admin. Code Pt. 2, Ch. 6.)
 - (a) For purposes of fee assessment and collection, the permittee shall elect for actual or allowable emissions to be used in determining the annual quantity of emissions unless the Commission determines by order that the method chosen by the applicant for calculating actual emissions fails to reasonably represent actual emissions. Actual emissions shall be calculated using emission monitoring data or direct emissions measurements for the pollutant(s); mass balance calculations such as the amounts of the pollutant(s) entering and leaving process equipment and where mass balance calculations can be supported by direct measurement of process parameters, such direct measurement data shall be supplied; published emission factors such as those relating release quantities to throughput or equipment type (e.g., air emission factors); or other approaches such as engineering calculations (e.g., estimating volatilization using published mathematical formulas) or best engineering judgments where such judgments are

derived from process and/or emission data which supports the estimates of maximum actual emission. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.A(2).)

- (b) If the Commission determines that there is not sufficient information available on a facility's emissions, the determination of the fee shall be based upon the permitted allowable emissions until such time as an adequate determination of actual emissions is made. Such determination may be made anytime within one year of the submittal of actual emissions data by the permittee. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.A(2).) If at any time within the year the Commission determines that the information submitted by the permittee on actual emissions is insufficient or incorrect, the permittee will be notified of the deficiencies and the adjusted fee schedule. Past due fees from the adjusted fee schedule will be paid on the next scheduled quarterly payment time. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.D(2).)
- (c) The fee shall be due September 1 of each year. By July 1 of each year the permittee shall submit an inventory of emissions for the previous year on which the fee is to be assessed. The permittee may elect a quarterly payment method of four (4) equal payments; notification of the election of quarterly payments must be made to the DEQ by the first payment date of September 1. The permittee shall be liable for penalty as prescribed by State Law for failure to pay the fee or quarterly portion thereof by the date due. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.D.)
- (d) If in disagreement with the calculation or applicability of the Title V permit fee, the permittee may petition the Commission in writing for a hearing in accordance with State Law. Any disputed portion of the fee for which a hearing has been requested will not incur any penalty or interest from and after the receipt by the Commission of the hearing petition. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.C.)
- 1.9 No permit revision shall be required under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes for changes that are provided for in this permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(8).)
- 1.10 Any document required by this permit to be submitted to the DEQ shall contain a certification by a responsible official that states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.2.E.)
- 1.11 The permittee shall allow the DEQ, or an authorized representative, upon the presentation of credentials and other documents as may be required by law, to perform the following:

- (a) enter upon the permittee's premises where a Title V source is located or emissions-related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
- (d) as authorized by the Federal Act, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.C(2).)
- 1.12 Except as otherwise specified or limited herein, the permittee shall have necessary sampling ports and ease of accessibility for any new air pollution control equipment, obtained after May 8, 1970, and vented to the atmosphere. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.I(1).)
- 1.13 Except as otherwise specified or limited herein, the permittee shall provide the necessary sampling ports and ease of accessibility when deemed necessary by the Permit Board for air pollution control equipment that was in existence prior to May 8, 1970. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.I(2).)
- 1.14 Compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance where such applicable requirements are included and are specifically identified in the permit or where the permit contains a determination, or summary thereof, by the Permit Board that requirements specifically identified previously are not applicable to the source. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.F(1).)
- 1.15 Nothing in this permit shall alter or affect the following:
 - (a) the provisions of Section 303 of the Federal Act (emergency orders), including the authority of the Administrator under that section;
 - (b) the liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;
 - (c) the applicable requirements of the acid rain program, consistent with Section 408(a) of the Federal Act.
 - (d) the ability of EPA to obtain information from a source pursuant to Section 114 of the Federal Act. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.F(2).)

- 1.16 The permittee shall comply with the requirement to register a Risk Management Plan if permittee's facility is required pursuant to Section 112(r) of the Act to register such a plan. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.H.)
- 1.17 Expiration of this permit terminates the permittee's right to operate unless a timely and complete renewal application has been submitted. A timely application is one which is submitted at least six (6) months prior to expiration of the Title V permit. If the permittee submits a timely and complete application, the failure to have a Title V permit is not a violation of regulations until the Permit Board takes final action on the permit application. This protection shall cease to apply if, subsequent to the completeness determination, the permittee fails to submit by the deadline specified in writing by the DEQ any additional information identified as being needed to process the application. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.C(2)., R. 6.4.B., and R. 6.2.A(1)(c).)
- 1.18 The permittee is authorized to make changes within their facility without requiring a permit revision (ref: Section 502(b)(10) of the Act) if:
 - (a) the changes are not modifications under any provision of Title I of the Act;
 - (b) the changes do not exceed the emissions allowable under this permit;
 - (c) the permittee provides the Administrator and the Department with written notification in advance of the proposed changes (at least seven (7) days, or such other time frame as provided in other regulations for emergencies) and the notification includes:
 - (1) a brief description of the change(s),
 - (2) the date on which the change will occur,
 - (3) any change in emissions, and
 - (4) any permit term or condition that is no longer applicable as a result of the change;
 - (d) the permit shield shall not apply to any Section 502(b)(10) change. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.F(1).)
- 1.19 Should the Executive Director of the Mississippi Department of Environmental Quality declare an Air Pollution Emergency Episode, the permittee will be required to operate in accordance with the permittee's previously approved Emissions Reduction Schedule or, in the absence of an approved schedule, with the appropriate requirements specified in 11 Miss. Admin. Code Pt. 2, Ch. 3., "Regulations for the Prevention of Air Pollution Emergency Episodes" for the level of emergency declared. (Ref.: 11 Miss. Admin.

Code Pt. 2, Ch. 3.)

- 1.20 Except as otherwise provided herein, a modification of the facility may require a Permit to Construct in accordance with the provisions of Regulations 11 Miss. Admin. Code Pt. 2, Ch. 2., "Permit Regulations for the Construction and/or Operation of Air Emissions Equipment", and may require modification of this permit in accordance with Regulations 11 Miss. Admin. Code Pt. 2, Ch. 6., "Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act". Modification is defined as "[a]ny physical change in or change in the method of operation of a facility which increases the actual emissions or the potential uncontrolled emissions of any air pollutant subject to regulation under the Federal Act emitted into the atmosphere by that facility or which results in the emission of any air pollutant subject to regulation under the Federal Act emitted. A physical change or change in the method of operation shall not include:
 - (a) routine maintenance, repair, and replacement;
 - (b) use of an alternative fuel or raw material by reason of an order under Sections 2
 (a) and (b) of the Federal Energy Supply and Environmental Coordination Act of 1974 (or any superseding legislation) or by reason of a natural gas curtailment plan pursuant to the Federal Power Act;
 - (c) use of an alternative fuel by reason of an order or rule under Section 125 of the Federal Act;
 - (d) use of an alternative fuel or raw material by a stationary source which:
 - (1) the source was capable of accommodating before January 6, 1975, unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR 51.166; or
 - (2) the source is approved to use under any permit issued under 40 CFR 52.21 or under regulations approved pursuant to 40 CFR 51.166;
 - (e) an increase in the hours of operation or in the production rate unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Subpart I or 40 CFR 51.166; or
 - (f) any change in ownership of the stationary source."
- 1.21 Any change in ownership or operational control must be approved by the Permit Board. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.D(4).)

- 1.22 This permit is a Federally approved operating permit under Title V of the Federal Clean Air Act as amended in 1990. All terms and conditions, including any designed to limit the source's potential to emit, are enforceable by the Administrator and citizens under the Federal Act as well as the Commission. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.B(1).)
- 1.23 Except as otherwise specified or limited herein, the open burning of residential, commercial, institutional, or industrial solid waste, is prohibited. This prohibition does not apply to infrequent burning of agricultural wastes in the field, silvicultural wastes for forest management purposes, land-clearing debris, debris from emergency clean-up operations, and ordnance. Open burning of land-clearing debris must not use starter or auxiliary fuels which cause excessive smoke (rubber tires, plastics, etc.); must not be performed if prohibited by local ordinances; must not cause a traffic hazard; must not take place where there is a High Fire Danger Alert declared by the Mississippi Forestry Commission or Emergency Air Pollution Episode Alert imposed by the Executive Director and must meet the following buffer zones.
 - (a) Open burning without a forced-draft air system must not occur within 500 yards of an occupied dwelling.
 - (b) Open burning utilizing a forced-draft air system on all fires to improve the combustion rate and reduce smoke may be done within 500 yards of but not within 50 yards of an occupied dwelling.
 - (c) Burning must not occur within 500 yards of commercial airport property, private air fields, or marked off-runway aircraft approach corridors unless written approval to conduct burning is secured from the proper airport authority, owner or operator. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.G.)
- 1.24 Except as otherwise specified herein, the permittee shall be subject to the following provision with respect to emergencies.
 - (a) Except as otherwise specified herein, an "emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.
 - (b) An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions specified in (c) following are met.

- (c) The affirmative defense of emergency shall be demonstrated through properly signed contemporaneous operating logs, or other relevant evidence that include information as follows:
 - (1) an emergency occurred and that the permittee can identify the cause(s) of the emergency;
 - (2) the permitted facility was at the time being properly operated;
 - (3) during the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements in the permit; and
 - (4) the permittee submitted notice of the emergency to the DEQ within 2 working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.
- (d) In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (e) This provision is in addition to any emergency or upset provision contained in any applicable requirement specified elsewhere herein. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.G.)
- 1.25 Except as otherwise specified herein, the permittee shall be subject to the following provisions with respect to upsets, startups, shutdowns and maintenance.
 - (a) Upsets (as defined by 11 Miss. Admin. Code Pt. 2, R. 1.2.KK.)
 - (1) The occurrence of an upset constitutes an affirmative defense to an enforcement action brought for noncompliance with emission standards or other requirements of Applicable Rules and Regulations or any applicable permit if the permittee demonstrates through properly signed contemporaneous operating logs, or other relevant evidence that include information as follows:
 - (i) an upset occurred and that the permittee can identify the cause(s) of the upset;
 - (ii) the source was at the time being properly operated;
 - (iii) during the upset the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other

requirements of Applicable Rules and Regulations or any applicable permit;

- (iv) the permittee submitted notice of the upset to the DEQ within 5 working days of the time the upset began; and
- (v) the notice of the upset shall contain a description of the upset, any steps taken to mitigate emissions, and corrective actions taken.
- (2) In any enforcement proceeding, the permittee seeking to establish the occurrence of an upset has the burden of proof.
- (3) This provision is in addition to any upset provision contained in any applicable requirement.
- (b) Startups and Shutdowns (as defined by 11 Miss. Admin. Code Pt. 2, R. 1.2.HH. & R. 1.2.CC.)
 - (1) Startups and shutdowns are part of normal source operation. Emissions limitations applicable to normal operation apply during startups and shutdowns except as follows:
 - (i) when sudden, unavoidable breakdowns occur during a startup or shutdown, the event may be classified as an upset subject to the requirements above;
 - (ii) when a startup or shutdown is infrequent, the duration of excess emissions is brief in each event, and the design of the source is such that the period of excess emissions cannot be avoided without causing damage to equipment or persons; or
 - (iii) when the emissions standards applicable during a startup or shutdown are defined by other requirements of Applicable Rules and Regulations or any applicable permit.
 - (2) In any enforcement proceeding, the permittee seeking to establish the applicability of any exception during a startup or shutdown has the burden of proof.
 - (3) In the event this startup and shutdown provision conflicts with another applicable requirement, the more stringent requirement shall apply.
- (c) Maintenance.

- (1) Maintenance should be performed during planned shutdown or repair of process equipment such that excess emissions are avoided. Unavoidable maintenance that results in brief periods of excess emissions and that is necessary to prevent or minimize emergency conditions or equipment malfunctions constitutes an affirmative defense to an enforcement action brought for noncompliance with emission standards, or other regulatory requirements if the permittee can demonstrate the following:
 - (i) the permittee can identify the need for the maintenance;
 - (ii) the source was at the time being properly operated;
 - (iii) during the maintenance the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements of Applicable Rules and Regulations or any applicable permit;
 - (iv) the permittee submitted notice of the maintenance to the DEQ within 5 working days of the time the maintenance began or such other times as allowed by DEQ; and
 - (v) the notice shall contain a description of the maintenance, any steps taken to mitigate emissions, and corrective actions taken.
- (2) In any enforcement proceeding, the permittee seeking to establish the applicability of this section has the burden of proof.
- (3) In the event this maintenance provision conflicts with another applicable requirement, the more stringent requirement shall apply. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.10.)
- 1.26 The permittee shall comply with all applicable standards for demolition and renovation activities pursuant to the requirements of 40 CFR Part 61, Subpart M, as adopted by reference in Regulation 11 Miss Admin. Code Pt. 2, R. 1.8. The permittee shall not be required to obtain a modification of this permit in order to perform the referenced activities

SECTION 2. EMISSION POINTS & POLLUTION CONTROL DEVICES

Emission Point	Description
AA-001	 Tank Battery Flare, with 0.05 MMBtu/hr propane-fired pilot, controlling the following emissions sources: Gas produced from the Oil/Gas Separator, Emissions from the Vapor Recovery Unit (VRU) controlling the storage and process tanks, and Emissions from Truck Loading
AA-002	Oil/Gas Separator with produced gas routed to the Flare (AA-001)
AA-003	21,000-gallon (500-barrel) Vertical Fixed-Roof Power Oil Production Tank (a process vessel), with emissions vented to the VRU followed by the Flare (AA-001)
AA-004	16,800-gallon (400-barrel) Vertical Fixed-Roof Oily Water Storage Tank, with emissions vented to the VRU followed by the Flare (AA-001)
AA-005	16,800-gallon (400-barrel) Vertical Fixed-Roof Oil Condensate Storage Tank No. 1, with emissions vented to the VRU followed by the Flare (AA-001)
AA-006	16,800-gallon (400-barrel) Vertical Fixed-Roof Oil Condensate Storage Tank No. 2, with emissions vented to the VRU followed by the Flare (AA-001)
AA-007	Truck Loading Emissions controlled by the Flare (AA-001)
AA-008	Fugitive Emissions from Equipment Leaks (Insignificant Activity)

SECTION 3. EMISSION LIMITATIONS & STANDARDS

A. Facility-Wide Emission Limitations & Standards

- 3.A.1 Except as otherwise specified or limited herein, the permittee shall not cause, permit, or allow the emission of smoke from a point source into the open air from any manufacturing, industrial, commercial or waste disposal process which exceeds forty (40) percent opacity subject to the exceptions provided in (a) & (b).
 - (a) Startup operations may produce emissions which exceed 40% opacity for up to fifteen (15) minutes per startup in any one hour and not to exceed three (3) startups per stack in any twenty-four (24) hour period.
 - (b) Emissions resulting from soot blowing operations shall be permitted provided such emissions do not exceed 60 percent opacity, and provided further that the aggregate duration of such emissions during any twenty-four (24) hour period does not exceed ten (10) minutes per billion BTU gross heating value of fuel in any one hour. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.A.)
- 3.A.2 Except as otherwise specified or limited herein, the permittee shall not cause, allow, or permit the discharge into the ambient air from any point source or emissions, any air contaminant of such opacity as to obscure an observer's view to a degree in excess of 40% opacity, equivalent to that provided in Paragraph 3.A.1. This shall not apply to vision obscuration caused by uncombined water droplets. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.B.)

Emission Point(s)	Applicable Requirement	Condition Number(s)	Pollutant/ Parameter	Limit/Standard
AA-001	Title V Operating Permit issued September 26, 2016; 11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).	3.B.1	SO ₂	240 tpy, determined for each consecutive 12-month period (includes other emission points facility-wide that contribute to SO2 emissions)
	Title V Operating Permit issued September 26, 2016	3.B.2	Flare Pilot	Operate with a flame present at all times
AA-002 through AA-007	11 Miss. Admin. Code Pt. 2, R. 1.4.B(2).	3.B.3	H ₂ S	1 grain H ₂ S per 100 standard cubic feet (1 gr/100 scf)

B. <u>Emission Point Specific Emission Limitations & Standards</u>

Emission Point(s)	Applicable Requirement	Condition Number(s)	Pollutant/ Parameter	Limit/Standard
AA-002	Title V Operating Permit issued September 26, 2016	3.B.4	H ₂ S/VOC	Flare all produced gas from the separator
AA-003 through AA-006	Title V Operating Permit issued September 26, 2016	3.B.5	H ₂ S/VOC	Route all emissions to the VRU followed by the Flare
AA-007	Title V Operating Permit issued September 26, 2016	3.B.6	H ₂ S/VOC	Route emissions to the Flare

- 3.B.1 For Emission Point AA-001, the permittee shall limit emissions of SO₂ from the flare to no more than 240 tpy, as determined for each consecutive 12-month period. (Ref.: Title V Operating Permit issued September 26, 2016 and 11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).)
- 3.B.2 For Emission Point AA-001, the permittee shall operate the flare with a flame present at all times. In addition, the permittee shall operate and maintain the flare according to the manufacturer's operations and maintenance instructions, or the permittee shall develop and follow a written operations and maintenance plan, which is consistent with good air pollution control practices for minimizing emissions. (Ref.: Title V Operating Permit issued September 26, 2016)
- 3.B.3 For Emission Points AA-002 through AA-007, the permittee shall not cause or permit the emission of any gas stream which contains hydrogen sulfide (H₂S) in excess of one grain per 100 standard cubic feet. Gas streams containing hydrogen sulfide in excess of one grain per 100 standard cubic feet shall be incinerated at temperatures of not less than 1600°F for a period of not less than 0.5 seconds, or processed in such a manner which is equivalent to or more effective for the removal of hydrogen sulfide. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.B(2).)
- 3.B.4 For Emission Point AA-002, the permittee shall route all produced gas from the oil/gas separator to the Flare (AA-001) or pipe all gas to the disposal well. (Ref.: Title V Operating Permit issued September 26, 2016)
- 3.B.5 For Emission Points AA-003 through AA-006, the permittee shall route all emissions from the four tanks to the vapor recovery unit (VRU) which is controlled by the Flare (AA-001). (Ref.: Title V Operating Permit issued September 26, 2016)
- 3.B.6 For Emission Point AA-007, the permittee shall route all emissions from truck loading to the Flare (AA-001). (Ref.: Title V Operating Permit issued September 26, 2016)

Applicable Requirement	Condition Number(s)	Pollutant/ Parameter	Limit/Standard
11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(a).	3.C.1	РМ	0.6 lb/MMBtu
11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).	3.C.2	SO ₂	4.8 lb/MMBtu
11 Miss. Admin. Code Pt. 2, R. 1.3.F(1).	3.C.2	SO ₂	$E = 4.1(p)^{0.67}$

C. Insignificant and Trivial Activity Emission Limitations & Standards

- 3.C.1 The maximum permissible emission of ash and/or particulate matter from fossil fuel burning installations of less than 10 million BTU per hour heat input shall not exceed 0.6 pounds per million BTU per hour heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(a).)
- 3.C.2 The maximum discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide) per million BTU heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).)
- 3.C.3 Except as otherwise specified or limited herein, the permittee shall not cause, permit, or allow the emission from any manufacturing process, in any one hour from any point source, particulate matter in total quantities in excess of the amount determined by the relationship

 $E = 4.1 (p)^{0.67}$

where E is the emission rate in pounds per hour and p is the process weight input rate in tons per hour. If the process weight input rate (p) changes, the emissions rate (E) will change correspondingly. (Ref.: Ref.: 11 Miss. Admin. Code Pt. 2, R.1.3.F(1).)

SECTION 4. COMPLIANCE SCHEDULE

- 4.1 Unless otherwise specified herein, the permittee shall be in compliance with all requirements contained herein upon issuance of this permit.
- 4.2 Except as otherwise specified herein, the permittee shall submit to the Permit Board and to the Administrator of EPA Region IV a certification of compliance with permit terms and conditions, including emission limitations, standards, or work practices, by January 31 for the preceding calendar year. Each compliance certification shall include the following:
 - (a) the identification of each term or condition of the permit that is the basis of the certification;
 - (b) the compliance status;
 - (c) whether compliance was continuous or intermittent;
 - (d) the method(s) used for determining the compliance status of the source, currently and over the applicable reporting period;
 - (e) such other facts as may be specified as pertinent in specific conditions elsewhere in this permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.C(5)(a), (c), & (d).)

SECTION 5. MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS

- A. <u>General Monitoring, Recordkeeping and Reporting Requirements</u>
- 5.A.1 The permittee shall install, maintain, and operate equipment and/or institute procedures as necessary to perform the monitoring and recordkeeping specified below.
- 5.A.2 In addition to the recordkeeping specified below, the permittee shall include with all records of required monitoring information the following:
 - (a) the date, place as defined in the permit, and time of sampling or measurements;
 - (b) the date(s) analyses were performed;
 - (c) the company or entity that performed the analyses;
 - (d) the analytical techniques or methods used;
 - (e) the results of such analyses; and
 - (f) the operating conditions existing at the time of sampling or measurement. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(b)(1).)
- 5.A.3 Except where a longer duration is specified in an applicable requirement, the permittee shall retain records of all required monitoring data and support information for a period of at least five (5) years from the date of the monitoring sample, measurement, report, or application. Support information includes all calibration and maintenance records, all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by the permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(b)(2).)
- 5.A.4 Except as otherwise specified herein, the permittee shall submit reports of any required monitoring by July 31 and January 31 for the preceding six-month period. All instances of deviations from permit requirements must be clearly identified in such reports and all required reports must be certified by a responsible official consistent with 11 Miss. Admin. Code Pt. 2, R. 6.2.E. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c)(1).)
- 5.A.5 Except as otherwise specified herein, the permittee shall report all deviations from permit requirements, including those attributable to upsets, the probable cause of such deviations, and any corrective actions or preventive measures taken. Said report shall be made within five (5) days of the time the deviation began. (Ref.: 11 Miss. Admin.

Code Pt. 2, R. 6.3.A(3)(c)(2).)

- 5.A.6 Except as otherwise specified herein, the permittee shall perform emissions sampling and analysis in accordance with EPA Test Methods and with any continuous emission monitoring requirements, if applicable. All test methods shall be those versions or their equivalents approved by the DEQ and the EPA.
- 5.A.7 The permittee shall maintain records of any alterations, additions, or changes in equipment or operation.

Emission Point(s)	Applicable Requirement	Condition Number	Pollutant/Parameter Monitored	Monitoring/Recordkeeping Requirement
AA-001	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)	5.B.1	Gas Flow	Install, operate, and maintain a flow meter for measuring total gas flow to the flare
		5.B.2	H_2S	Sample H ₂ S in the flared gas monthly
		5.B.3	SO_2	Maintain records of the SO ₂ emissions for each calendar month and each consecutive 12-month period
		5.B.4	Presence of Flame	Monitor for presence of a flame

B. <u>Specific Monitoring and Recordkeeping Requirements</u>

- 5.B.1 For Emission Point AA-001, the permittee shall install, operate, and maintain a flow meter for measuring the total gas flow to the flare for each calendar month. The flow meter shall be installed in a location that will represent the total flow to the flare. The flow meter shall be operated and maintained in accordance to the manufacturer's specifications. The permittee shall record the monthly total flow to the flare and shall record any periods the flow meters was inoperable, the date and extent of all maintenance conducted on the meter, and any corrective action taken to repair any noted problems. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3))
- 5.B.2 For Emission Point AA-001, the permittee shall measure the H_2S concentration in the combined gas stream to the flare on a monthly basis. The permittee shall use a portable H_2S gas monitor meeting ASTM standards and shall ensure the monitor is calibrated in accordance to the manufacturer's specifications. For each H_2S measurement, the permittee shall record the date of monitoring, the H_2S concentration, the date the gas monitor was last calibrated, and the personnel performing the monitoring. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3))
- 5.B.3 For Emission Point AA-001, the permittee shall determine the SO₂ emissions for each calendar month and each consecutive 12-month period using the monthly gas flow to

the flare and H_2S concentration of the gas stream for the corresponding month. The permittee shall assume 100% conversion of H_2S to SO₂. The permittee shall maintain the gas flow, H_2S concentration, and resulting SO₂ emissions in electronic form and make this information available for review by DEQ personnel. (Ref: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3))

5.B.4 For Emission Point AA-001, the permittee shall install a thermocouple or equivalent device to monitor the presence of a flame. The permittee shall install, operate, and maintain the thermocouple or equivalent device in accordance to the manufacturer's specifications. An alarm or other means of notification shall be triggered any time that the monitoring device indicates no flame is present. The permittee shall record the date, time, and duration that emissions are vented to the flare while a flame is not present. The permittee shall also record the date and extent of maintenance on the monitoring device, including calibrations, as recommended by the manufacturer. (Ref: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3))

C. <u>Specific Reporting Requirements</u>

Emission Point(s)	Applicable Requirement	Condition Number	Pollutant/Parameter Monitored	Reporting Requirement
AA-001	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c)	5.C.1	SO ₂	Report monthly and 12-month rolling total SO ₂ emissions
		5.C.2	Deviations	Include date, duration, and nature of any deviation and any corrective measures taken

- 5.C.1 In accordance with Condition 5.A.4, for Emission Point AA-001, the permittee shall submit reports of the gas flow, H₂S concentration, and SO₂ emissions for each calendar month, including sample calculations. The permittee shall also demonstrate compliance with the SO₂ permit limit by calculating the 12-month rolling total SO₂ emissions in tpy for each consecutive 12-month period in the semiannual reporting period. (Ref: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c))
- 5.C.2 In accordance with Condition 5.A.4, for Emission Point AA-001, the semiannual reports shall include the date, duration, and nature of any deviation from required monitoring, operation and maintenance, or recordkeeping required herein. Any corrective measures taken to address each deviation shall also be included in the semiannual reports. (Ref: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c))

SECTION 6. ALTERNATIVE OPERATING SCENARIOS

6.1 None permitted.

SECTION 7. TITLE VI REQUIREMENTS

The following are applicable or potentially applicable requirements originating from Title VI of the Clean Air Act – Stratospheric Ozone Protection. The full text of the referenced regulations may be found on-line at <u>http://ecfr.gpoaccess.gov</u> under Title 40, or DEQ shall provide a copy upon request from the permittee.

- 7.1 If the permittee produces, transforms, destroys, imports or exports a controlled substance or imports or exports a controlled product, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart A Production and Consumption Controls.
- 7.2 If the permittee performs service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart B Servicing of Motor Vehicle Air Conditioners.
- 7.3 The permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart E – The Labeling of Products Using Ozone-Depleting Substances, for the following containers and products:
 - (a) All containers in which a class I or class II substance is stored or transported;
 - (b) All products containing a class I substance; and
 - (c) All products directly manufactured with a process that uses a class I substance, unless otherwise exempted by this subpart or, unless EPA determines for a particular product that there are no substitute products or manufacturing processes for such product that do not rely on the use of a class I substance, that reduce overall risk to human health and the environment, and that are currently or potentially available. If the EPA makes such a determination for a particular product, then the requirements of this subpart are effective for such product no later than January 1, 2015.
- 7.4 If the permittee performs any of the following activities, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart F Recycling and Emissions Reduction:
 - (a) Servicing, maintaining, or repairing appliances;
 - (b) Disposing of appliances, including small appliances and motor vehicle air conditioners; or

- (c) Refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturers of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, persons selling class I or class II refrigerants or offering class I or class II refrigerants for sale, and persons purchasing class I or class II refrigerants.
- 7.5 The permittee shall be allowed to switch from any ozone-depleting substance to any acceptable alternative that is listed in the Significant New Alternatives Policy (SNAP) program promulgated pursuant to 40 CFR Part 82, Subpart G Significant New Alternatives Policy Program. The permittee shall also comply with any use conditions for the acceptable alternative substance.
- 7.6 If the permittee performs any of the following activities, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart H Halon Emissions Reduction:
 - (a) Any person testing, servicing, maintaining, repairing, or disposing of equipment that contains halons or using such equipment during technician training;
 - (b) Any person disposing of halons;
 - (c) Manufacturers of halon blends; or
 - (d) Organizations that employ technicians who service halon-containing equipment.

APPENDIX A

List of Abbreviations Used In this Permit

Control of Air Contaminants 11 Miss. Admin. Code Pt. 2, Ch. 2. Episodes 11 Miss. Admin. Code Pt. 2, Ch. 3. Regulations for the Prevention of Air Pollution Emergency Episodes 11 Miss. Admin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards 11 Miss. Admin. Code Pt. 2, Ch. 5. Regulations for the Prevention of Significant Deterioration of Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEM Continuous Dacity Monitor COM COMS Continuous Opacity Monitoring System CFR COMS Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality PA HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour M or K Thorean Ambient Air Quality Standards National Ambient Air Quality Standards	Control of Air Contaminants 11 Miss. Admin. Code Pt. 2, Ch. 2. Permit Regulations for the Construction and/or Operation of Air Emissions Equipment 11 Miss. Admin. Code Pt. 2, Ch. 3. Regulations for the Prevention of Air Pollution Emergency Episodes 11 Miss. Admin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards 11 Miss. Admin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Bext Available Control Technology CEM Continuous Emission Monitor CEMS Continuous Emission Monitor CCMS Continuous Dacity Monitoring System CCM CCM Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour M or K Thousand MACT Maximum Achievable Control Technology MM M Million MMBTUH Million British Thermal Units per Hour NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 Or National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 o	11 Miss. Adm	nin. Code Pt. 2, Ch. 1. Air Emission Regulations for the Prevention, Abatement, and
Emissions Equipment 11 Miss. Admin. Code Pt. 2, Ch. 3. Regulations for the Prevention of Air Pollution Emergency Episodes 11 Miss. Admin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards 11 Miss. Admin. Code Pt. 2, Ch. 5. Regulations for the Prevention of Significant Deterioration of Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEMS Continuous Emission Monitoring System CO Carbon Monoxide COM Continuous Opacity Monitor COMS Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepwer HAP Harzardous Air Pollutant Ibs/hr Pounds per Hour MA K Thousand MACT Maximum Achievable Control Technology MM Million Million British Thermal Units per Hour NA Not Applicable NAAQS	Emissions Equipment 11 Miss. Admin. Code Pt. 2, Ch. 3. Regulations for the Prevention of Air Pollution Emergency Episodes 11 Miss. Admin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards 11 Miss. Admin. Code Pt. 2, Ch. 5. Regulations for the Prevention of Significant Deterioration of Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Action Code of Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEMS Continuous Emission Monitor COM Continuous Opacity Monitoring System COM Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Air Pollutant Ib/hr Pounds per Hour MacT Maximum Achievable Control Technology MMA Million MACT Maximum Achievable Control Technology MMACT Maximum Achievable Control Technology MAC		
 11 Miss. Admin. Code Pt. 2, Ch. 3. Regulations for the Prevention of Air Pollution Emergency Episodes 11 Miss. Admin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards 11 Miss. Admin. Code Pt. 2, Ch. 5. Regulations for the Prevention of Significant Deterioration of Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title V of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitoring System CFR Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitoring System COM Continuous Opacity Monitoring System COM Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gridscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour M K Thousand MMBTUH Million British Thermal Units per Hour Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO, Mitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&AM Operation and Maintenance PM articulate Matter PM₁₀ Particulate Matter PM₁₀ Particulate Matter PSD Prevention of Significant Deterioration, 40 CFR 52 	 11 Miss. Admin. Code Pt. 2, Ch. 3. Regulations for the Prevention of Air Pollution Emergency Episodes 11 Miss. Admin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards 11 Miss. Admin. Code Pt. 2, Ch. 5. Regulations for the Prevention of Significant Deterioration of Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title V of the Federal Clean Air Act 12 Miss. Stable Control Technology CEMS Continuous Emission Monitor CEMS Continuous Emission Monitor COM Continuous Dacity Monitor COM Continuous Opacity Monitor COMS Continuous Opacity Monitor COMS Continuous Opacity Monitor COMS Continuous Opacity Monitor Intervolution Agency gr/dscf Grains Per Dry Standard Cubic Foot HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour M K Thousand MACT Maximu Achievable Control Technology MMM Million British Thermal Units per Hour NA Not Applicable NAAQS National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or or National Emission Standards For Hazardous Air Pollutants, 40 cFR 61 NMVOC Non-Methane Plan Non-Methane Notalie Organic Compounds NO₄. Million British Thermal Units per Hour NA Not Applicable NMVOC Non-Methane Plan Non-Methane Plan Particulate Matter PM Particulate Matter PM Particulate Matter PM Particulate Matter PM Particulate Matter less than 10 µm in d	11 Miss. Adm	nin. Code Pt. 2, Ch. 2. Permit Regulations for the Construction and/or Operation of Air
Episodes 11 Miss. Admin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards 11 Miss. Admin. Code Pt. 2, Ch. 5. Regulations for the Prevention of Significant Deterioration of Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitoring System CER Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitor COMS Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Hazardous Air Pollutant Ibs/hr Pounds per Hour Ma Million British Thermal Units per Hour NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMV	Episodes 11 Miss. Admin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards 11 Miss. Admin. Code Pt. 2, Ch. 5. Regulations for the Prevention of Significant Deterioration of Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEM Continuous Emission Monitor CEM Continuous Emission Monitor CEM Continuous Dapacity Monitoring System COM Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EFA United States Environmental Protection Agency gridscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour NA Not Applicable NAAQS National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 Or ref NESHAP National Emission Standards For Hazardous Air Pollutant	11 Miss Adm	
 11 Miss. Admin. Code Pt. 2, Ch. 5. Regulations for the Prevention of Significant Deterioration of Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEMS Continuous Emission Monitoring System COM Continuous Opacity Monitor COM Continuous Opacity Monitor COMS Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency grd/scf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant lbs/hr Pounds per Hour M or K Thousand MACT Maximum Achievable Control Technology MM Million Million British Thermal Units per Hour NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NQA Nirrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&AM Operation and Maintenance PM 10 Particulate Matter less than 10 µm in di	 11 Miss. Admin. Code Pt. 2, Ch. 5. Regulations for the Prevention of Significant Deterioration of Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEM Continuous Emission Monitoring System CCM Continuous Dapacity Monitoring System COM Continuous Opacity Monitoring System COM Continuous Opacity Monitoring System COM Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAR Hazardous Air Pollutant Ibs/hr Pounds per Hour M or K Thousand Maximum Achievable Control Technology MMBTUH Million British Thermal Units per Hour NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NESHAP Netional Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NESHAP Netional Emission Standards, 40 CFR 60 NeW OC Non-Methane Volatile Organic Compounds NO, Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 Ock Operation and Maintenance PM Particulate Matter less than 10 µm in diameter ppm Parts per Million PSD Prevention of Significant Deterioration, 40 CFR 52 SIP Prevention of Significant Deterioration, 40 CFR 52 SIP State Implementation Pl	11 Miss. Auf	
Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEMS Continuous Emission Monitoring System CFR Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitor COMS Continuous Opacity Monitor GOMS Continuous Opacity Monitor COMS Continuous Opacity Monitor COMS Continuous Opacity Monitor COMS Continuous Opacity Monitor COM Mains Per Dry Standard Clubic Foot HP Horsepower HAP <td>Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title IV of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitoring System CFR Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitor COMS Continuous Opacity Monitoring System DEQ Mississipi Department of Environmental Quality EPA United States Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour MA Maximum Achievable Control Technology MM Million MMBTUH Million MMBTUH Million MACT Maximum Achievable Control Technology NA Not Applicable NAAQS National Emission Standards For Hazardous Air Pollutants, 40</td> <td>11 Miss. Adn</td> <td>nin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards</td>	Air Quality 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title IV of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitoring System CFR Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitor COMS Continuous Opacity Monitoring System DEQ Mississipi Department of Environmental Quality EPA United States Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour MA Maximum Achievable Control Technology MM Million MMBTUH Million MMBTUH Million MACT Maximum Achievable Control Technology NA Not Applicable NAAQS National Emission Standards For Hazardous Air Pollutants, 40	11 Miss. Adn	nin. Code Pt. 2, Ch. 4. Ambient Air Quality Standards
 11 Miss. Admin. Code Pt. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEMS Continuous Emission Monitor CEMS Continuous Emission Monitoring System CFR Code of Federal Regulations COM Continuous Opacity Monitor COMS Continuous Opacity Monitor COMS Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour M or K Thousand MACT Maximum Achievable Control Technology MM Million British Thermal Units per Hour NAAQS National Ambient Air Quality Standards NAAQS National Ambient Air Quality Standards NESHAP National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO₄ Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PSD Prevention of Significant Deterioration, 40 CFR 52 	 11 Miss. Admin. Code Pf. 2, Ch. 6. Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEMS Continuous Emission Monitoring System CFR Code of Federal Regulations COM Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gridscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant lbs/hr Pounds per Hour M K Thousand MMBTUH Million British Thermal Units per Hour NA Anot Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO_x Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&&M Operation and Maintenance PM Particulate Matter less than 10 µm in diameter Ppm Parts per Million Prevention of Significant Deterioration, 40 CFR 52 SIP State Implementation Plan SO₂ Sulfur Dioxide PY Tons pe Year Total Reduced Sulfur VEE Visible Emissions Zandards Air Pollutant 	11 Miss. Adm	nin. Code Pt. 2, Ch. 5. Regulations for the Prevention of Significant Deterioration of
Title V of the Federal Clean Air Act11 Miss. Admin. Code Pt. 2, Ch. 7.Acid Rain Program Permit Regulations for Purposes of Title IVof the Federal Clean Air ActBACTBest Available Control TechnologyCEMContinuous Emission MonitorCEMSContinuous Emission Monitoring SystemCFRCode of Federal RegulationsCOCarbon MonoxideCOMContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air PollutantIbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNO ₄ Nitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPM<	 Title V of the Federal Clean Air Act 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEMS Continuous Emission Monitor CEMS Continuous Emission Monitor CCMS Continuous Opacity Monitor COM Continuous Opacity Monitor COMS Continuous Opacity Monitor DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour MACT Maximum Achievable Control Technology MM Million MMBTUH Million British Thermal Units per Hour NA AQS National Ambient Air Quality Standards NAAQS National Ambient Air Quality Standards NAAQS National Ambient Air Quality Standards NAAQS National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO₄ Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&AM Operation and Maintenance PM Particulate Matter less than 10 µm in diameter Ppm Parts per Million Prevention of Significant Deterioration, 40 CFR 52 SIFP State Implementation Plan SO₂ Sulfur Dioxide PFY Tons per Year TKS Total Reduced Sulfur VEE Visible Emissions Evaluation VHAP Volatile Hazardous Air Pollutant 		Air Quality
11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT BACT Best Available Control Technology CEM Continuous Emission Monitoring System CFR Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitor COMS Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant lbs/hr Pounds per Hour Mor K Thousand MMBTUH Million MIIon British Thermal Units per Hour NA Not Applicable NAAQS National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO _A Nitrogen Oxides NSPS New Source Performance Standards	 11 Miss. Admin. Code Pt. 2, Ch. 7. Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEMS Continuous Emission Monitoring System CFR Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitor COMS Continuous Opacity Monitor POW HAP Hazardous Air Pollutant BACT Maximum Achievable Control Technology MM Million MMBTUH Million British Thermal Units per Hour NA ot Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for	11 Miss. Adn	
of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitoring System CFR Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitor COMS Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour M or K Thousand MACT Maximum Achievable Control Technology MM Million MMBTUH Million British Thermal Units per Hour NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO _x Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PM, Particulate Matter PM, Particulate Matter less than 10 µm in diameter ppm Parts per Million	of the Federal Clean Air Act BACT Best Available Control Technology CEM Continuous Emission Monitor CEMS Continuous Emission Monitor CFR Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant bs/hr Pounds per Hour M or K Thousand MACT Maximum Achievable Control Technology MM Million MMBTUH Million British Thermal Units per Hour NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 Nirogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O& Operation and Maintenance PM Particulate Matter PM110 Particu	11 Mica Adm	
BACTBest Available Control TechnologyCEMContinuous Emission MonitorCEMSContinuous Emission Monitoring SystemCFRCode of Federal RegulationsCOCarbon MonoxideCOMContinuous Opacity MonitorCOMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air PollutantIbs/hrPounds per HourM or KThousandMMMMillionMMBTUHMillionMillion British Thermal Units per HourNANot ApplicableNAAQSNational Emission StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate Matter Rest than 10 μ m in diameterPMParticulate MatterPMParticulate Matter Deterioration, 40 CFR 52	BACT Best Available Control Technology CEM Continuous Emission Monitoring System CEMS Continuous Emission Monitoring System CFR Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitor COMS Continuous Chastases Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant lbs/hr Pounds per Hour M or K MACT Maxium Achievable Control Technology MM Million MMBTUH Million British Thermal Units per Hour NA Not Applicable NAAQS National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40	11 Miss. Adii	
CEMContinuous Emission MonitorCEMSContinuous Emission Monitoring SystemCFRCode of Federal RegulationsCOCarbon MonoxideCOMContinuous Opacity MonitorCOMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Emission StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNO _k Nitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMParticulate Matter less	CEM Continuous Emission Monitor CEMS Continuous Emission Monitoring System CFR Code of Federal Regulations CO Carbon Monoxide COM Continuous Opacity Monitor COMS Continuous Opacity Monitoring System DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant Ibs/hr Pounds per Hour M or K Thousand MACT Maximum Achievable Control Technology MM Million MMBTUH Million British Thermal Units per Hour NA Not Applicable NAAQ National Ambient Air Quality Standards NESHAP National Emissions Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO ₄ Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&CM Operation and Maintenance PM Par	васт	
CEMSContinuous Emission Monitoring SystemCFRCode of Federal RegulationsCOCarbon MonoxideCOMContinuous Opacity MonitorCOMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNox Nox Nitrogen OxidesNitrogen OxidesNSPS New Source Performance Standards, 40 CFR 60O&MOgeration and MaintenancePM Particulate MatterPM Particulate MatterParticulate MatterPM PBD Prevention of Significant Deterioration, 40 CFR 52Particulate Matter	CEMSContinuous Emission Monitoring SystemCFRCode of Federal RegulationsCOCarbon MonoxideCOMContinuous Opacity MonitorCOMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMMBTUHMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Emission Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63CrR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMParticulate MatterPMParticulate Matter less than 10 µm in diameterPMParticulate MatterPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO_3Suffur DioxideTPYTons per YearTRSTotal Reduced SuffurVHAPVolatile Hazardous Air Pollutant		
CFRCode of Federal RegulationsCOCarbon MonoxideCOMContinuous Opacity MonitorCOMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNA4QSNational Ambient Air Quality StandardsNESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63NMVOCNMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate Matter less than 10 µm in diameterPDFPrevention of Significant Deterioration, 40 CFR 52	CFRCode of Federal RegulationsCOCarbon MonoxideCOMContinuous Opacity MonitorCOMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air PollutantIbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNO _k Nitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate MatterPM10Particulate MatterPM10Particulate MatterPM10Particulate MatterPM10State Implementation PlanSO2Suffur DioxideTPYTons per YearTRSTotal Reduced SuffurVEEVisible Emission StandardsVHAPVolatile Hazardous Air Pollutant		
COCarbon MonoxideCOMContinuous Opacity MonitorCOMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air PollutantIbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63NMVOCNMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMParticulate MatterPMParticulate Matter less than 10 μ m in diameterPpmParticulate Matter less than 10 μ m in diameterPpmParticulate MatterPSDPrevention of Significant Deterioration, 40 CFR 52	$ \begin{array}{llllllllllllllllllllllllllllllllllll$		
COMContinuous Opacity MonitorCOMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air PollutantIbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNO _x Nitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMParticulate Matter <td< td=""><td>COMContinuous Opacity MonitorCOMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNo_kNitrogen OxidePMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate Matter less than 10 µm in diameterPpmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emission EvaluationVHAPVolatile Hazardous Air Pollutant</td><td></td><td></td></td<>	COMContinuous Opacity MonitorCOMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNo _k Nitrogen OxidePMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate MatterPMParticulate Matter less than 10 µm in diameterPpmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emission EvaluationVHAPVolatile Hazardous Air Pollutant		
COMSContinuous Opacity Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMParticulate Matter less than 10 µm in diameterPMParticulate MatterPMParticulate Matter	COMSContinuous Opacitý Monitoring SystemDEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63NWVOCNMVOCNon-Methane Volatile Organic CompoundsNO _x Nitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMParticulate MatterPMParticulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPStult Implementation PlanSO ₂ Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
DEQMississippi Department of Environmental QualityEPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63NMVOCNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μ m in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency gr/dscf Grains Per Dry Standard Cubic Foot HP Horsepower HAP Hazardous Air Pollutant lbs/hr Pounds per Hour M or K Thousand MACT Maximum Achievable Control Technology MM Million MMBTUH Million British Thermal Units per Hour NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emission Standards For Hazardous Air Pollutants, 40 CFR 61 or or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO _x Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PM Particulate Matter PMD Partiset Matter less than 10 µm in diameter Ppm Parts per Million Prevention of Significant		
EPAUnited States Environmental Protection Agency $gr/dscf$ Grains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μ m in diameterPpmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	EPAUnited States Environmental Protection Agencygr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		Mississippi Department of Environmental Quality
gr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60 O&MOe&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μ m in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	gr/dscfGrains Per Dry Standard Cubic FootHPHorsepowerHAPHazardous Air PollutantIbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Ambient Air Quality StandardsNESHAPNational Emission Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63NMVOCNMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
HPHorsepowerHAPHazardous Air Pollutant lbs/hr Pounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	HPHorsepowerHAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μ m in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant	gr/dscf	
HAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61ororNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63NMVOCNMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μ m in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	HAPHazardous Air Pollutantlbs/hrPounds per HourM or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMn0Particulate MatterPMParticulate MatterPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
M or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μ m in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	M or KThousandMACTMaximum Achievable Control TechnologyMMMillionMMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant	HAP	
$\begin{array}{llllllllllllllllllllllllllllllllllll$	 MACT Maximum Achievable Control Technology MM Million MMBTUH Million British Thermal Units per Hour NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO_x Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PM Particulate Matter less than 10 µm in diameter ppm Parts per Million PSD Prevention of Significant Deterioration, 40 CFR 52 SIP State Implementation Plan SO₂ Sulfur Dioxide TPY Tons per Year TRS Total Reduced Sulfur VEE Visible Emissions Evaluation VHAP Volatile Hazardous Air Pollutant 	lbs/hr	Pounds per Hour
$\begin{array}{llllllllllllllllllllllllllllllllllll$	MM Million MMBTUH Million British Thermal Units per Hour NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NOx NOx Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PM Particulate Matter PM Particulate Matter less than 10 µm in diameter ppm Parts per Million PSD Prevention of Significant Deterioration, 40 CFR 52 SIP State Implementation Plan SO2 Sulfur Dioxide TPY Tons per Year TRS Total Reduced Sulfur VEE Visible Emissions Evaluation VHAP Volatile Hazardous Air Pollutant	M or K	Thousand
 MMBTUH Million British Thermal Units per Hour NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO_x Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PM₁₀ Particulate Matter less than 10 µm in diameter ppm Parts per Million PSD Prevention of Significant Deterioration, 40 CFR 52 	MMBTUHMillion British Thermal Units per HourNANot ApplicableNAAQSNational Ambient Air Quality StandardsNESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61orNational Emission Standards For Hazardous Air Pollutants for Source Categories, 40CFR 63CFR 63NMVOCNon-Methane Volatile Organic CompoundsNO _x Nitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM_10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant	MACT	
 NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO_x Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PM₁₀ Particulate Matter less than 10 μm in diameter ppm Parts per Million PSD Prevention of Significant Deterioration, 40 CFR 52 	 NA Not Applicable NAAQS National Ambient Air Quality Standards NESHAP National Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO_x Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PM₁₀ Particulate Matter less than 10 µm in diameter ppm Parts per Million PSD Prevention of Significant Deterioration, 40 CFR 52 SIP State Implementation Plan SO₂ Sulfur Dioxide TPY Tons per Year TRS Total Reduced Sulfur VEE Visible Emissions Evaluation VHAP Volatile Hazardous Air Pollutant 		
 NAAQS National Ambient Air Quality Standards NESHAP National Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO_x Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PM₁₀ Particulate Matter less than 10 µm in diameter ppm Parts per Million PSD Prevention of Significant Deterioration, 40 CFR 52 	 NAAQS National Ambient Air Quality Standards NESHAP National Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO_x Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PM₁₀ Particulate Matter less than 10 μm in diameter ppm Parts per Million PSD Prevention of Significant Deterioration, 40 CFR 52 SIP State Implementation Plan SO₂ Sulfur Dioxide TPY Tons per Year TRS Total Reduced Sulfur VEE Visible Emissions Evaluation VHAP Volatile Hazardous Air Pollutant 		
 NESHAP National Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63 NMVOC Non-Methane Volatile Organic Compounds NO_x Nitrogen Oxides NSPS New Source Performance Standards, 40 CFR 60 O&M Operation and Maintenance PM Particulate Matter PM₁₀ Particulate Matter less than 10 µm in diameter ppm Parts per Million PSD Prevention of Significant Deterioration, 40 CFR 52 	NESHAPNational Emissions Standards For Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM_10Particulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	or National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM_10Particulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM_10Particulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	National Emission Standards For Hazardous Air Pollutants for Source Categories, 40 CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPMParticulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant	NESHAP	
CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM_10Particulate Matter less than 10 μ m in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	CFR 63NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM.Particulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
NMVOCNon-Methane Volatile Organic Compounds NO_x Nitrogen Oxides $NSPS$ New Source Performance Standards, 40 CFR 60 $O\&M$ Operation and Maintenance PM Particulate Matter PM_{10} Particulate Matter less than 10 µm in diameter ppm Parts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	NMVOCNon-Methane Volatile Organic CompoundsNOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM.Particulate Matter less than 10 µm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
NOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	NOxNitrogen OxidesNSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM_10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant	NNNOC	
NSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	NSPSNew Source Performance Standards, 40 CFR 60O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	O&MOperation and MaintenancePMParticulate MatterPM10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
PMParticulate MatterPM10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	PMParticulate MatterPM10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
PM10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	PM10Particulate Matter less than 10 μm in diameterppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
ppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52	ppmParts per MillionPSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
PSD Prevention of Significant Deterioration, 40 CFR 52	PSDPrevention of Significant Deterioration, 40 CFR 52SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
	SIPState Implementation PlanSO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		Prevention of Significant Deterioration 40 CFR 52
	SO2Sulfur DioxideTPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
	TPYTons per YearTRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
	TRSTotal Reduced SulfurVEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
	VEEVisible Emissions EvaluationVHAPVolatile Hazardous Air Pollutant		
			Visible Emissions Evaluation
	VOC Volatile Organic Compound		
	voc volatile Organie Compound	VOC	Volatile Organic Compound