



STATE OF MISSISSIPPI

PHIL BRYANT
GOVERNOR

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

GARY C. RIKARD, EXECUTIVE DIRECTOR

April 19, 2018

Certified Mail No. 7010 1670 0000 1400 4007
Mr. Craig Litteken
Chief, Regulatory Division
U.S. Army Corps. of Engineers, Mobile District
PO Box 2288
Mobile, Alabama 36628

Dear Mr. Litteken:

Re: US Army COE, Mobile District,
Mississippi General Permits
MSGP-06-Boat Ramps
COE No. SAM-2016-01237-MJF
WQC No. 2017088

Pursuant to Section 401 of the Federal Water Pollution Control Act (33 U. S. C. 1251, 1341), the Office of Pollution Control (OPC) issues this Certification, after public notice and opportunity for public hearing, to U.S. Army Corps. of Engineers, Mobile District, an applicant for a Federal License or permit to conduct the following activity:

US Army COE, Mobile District, Mississippi General Permit MSGP-06 - BOAT RAMPS: The U.S. Army Corps of Engineers, Mobile District proposes revision and issuance of the following Mississippi General Permit (MSGP) for a period of 5 years. In an effort to eliminate unnecessary duplication of efforts among agencies and to streamline the permitting process for routine projects with only minimal impact, the Mobile District will regulate minor structures and activities in waters of the U.S., in the state of Mississippi and outer continental shelf waters off the coast of Mississippi, within the Regulatory boundaries of the Mobile District under Regional General Permits identified herein. These permits will supersede Mississippi General Permits issued April 12, 2013.

MSGP-06 - BOAT RAMPS:

This permit authorizes the construction or modification of boat ramps and marine ways.

Cubic Yards to be Dredged/Filled: This permit allows up to 250 cubic yards of material to be dredged and the placement of up to 50 cubic yards of fill below mean high tide line or the ordinary high water mark for construction of a boat ramp. The use

24300 WQC20170006

OFFICE OF POLLUTION CONTROL

POST OFFICE BOX 2261 • JACKSON, MISSISSIPPI 39225-2261 • TEL: (601) 961-5171 • FAX: (601) 354-6612 • www.deq.state.ms.us

AN EQUAL OPPORTUNITY EMPLOYER

of unsuitable material that is structurally unstable is not authorized. Only clean fill material may be used.

Location of Ramps:

- Care should be taken in the placement of boat ramps to avoid interrupting the natural movement of sediments.
- Storm water runoff from boat ramp approaches and parking areas shall not be directed down the boat ramp.
- Care should be taken to prevent erosion of side banks.

Best Management Practices: Best management practices should be used at all times during construction to minimize turbidity at both the dredged and spoil sites. Methods should include, but not limited to, the use of staked hay bales; staked filter cloth; sodding, seeding and mulching; staged construction; and the installation of turbidity screens around the immediate project site. Any effluent from the disposal area should be routed through a return swale system and filtered through a series of hay bales and silt fences so as to reduce the turbidity of the effluent. Additional best management practices as required by the Mississippi Department of Environmental Quality will apply regarding the return water from the bermed disposal area.

Coordination with SHPO: Coordination with the Mississippi Department of Archives and History is required prior to verification under MSGP-06. MDAH will be provided a copy of the application and afforded 30 days to comment. If MDAH offers no objection or the applicant voluntarily incorporates recommendations of MDAH, the project may be verified by the issuing agency. If MDAH recommends a Cultural Resources Survey or provides comments regarding the potential to affect historic resources, consultation must be completed between MDAH and the Mobile District prior to permit verification.

Disposal Area:

- All dredged material must be properly confined in a specified upland area or an approved Beneficial Use for Dredge Material project site, unless otherwise authorized by the Mobile District. For a list of Beneficial Use project sites, please contact DMR, Office of Coastal Ecology.
- Spoil disposal areas shall be immediately seeded and stabilized to prevent the movement of sediment off-site and into adjacent drainage areas.
- Disposal on sand beaches is prohibited.

Construction Limits: This permit does not authorize: (1) ancillary structures such as groins, jetties, or any solid structures roughly perpendicular to the shore or bank; (2) dredging or filling in wetlands (including bottom land hardwoods), submerged grass beds, or natural shellfish beds; and (3) boat ramps and/or marine ways where adverse impacts to submerged grass beds or natural shellfish beds would occur as a result of normal use. No dredged material shall be used to raise the elevation of any wetlands. [SAM-2016-01237-MJF, WQC2017088].

The Office of Pollution Control certifies that the above-described activity will be in compliance with the applicable provisions of Sections 301, 302, 303, 306, and 307 of the Federal Water Pollution Control Act and Section 49-17-29 of the Mississippi Code of 1972, if the applicant complies with the following conditions:

1. The permittee shall obtain appropriate wastewater permits and/or approvals for the proposed activity prior to the commencement of construction activities.
2. For projects greater than five acres of total ground disturbances including clearing, grading, excavating or other construction activities, the applicant shall obtain the necessary coverage under the State of Mississippi's Large Construction Storm Water General NPDES Permit. For projects greater than one to less than five acres of total ground disturbances including clearing, grading, excavating or other construction activities, the applicant shall follow the conditions and limitations of the State of Mississippi's Small Construction Storm Water General NPDES Permit. No construction activities shall begin until the necessary approvals and/or permits have been obtained.
3. Boat ramp parking areas with impervious surfaces (concrete, asphalt) that have a surface area equal to or greater than one acre shall provide for storm water management. The first 0.5 inch of storm water runoff from impervious parking and road surfaces shall be treated using MDEQ approved best management practices before release. The storm water plan should be submitted upon application for coverage under this general permit and shall be forwarded to MDEQ.
4. All fill material and excavation areas shall have side slopes of at least 3:1 (horizontal:vertical) and shall be immediately seeded, stabilized, and maintained.
5. All dredged material must be properly confined in a specified upland area or an approved Beneficial Use for Dredge Material project site. Spoil disposal areas shall be immediately seeded and stabilized to prevent the movement of sediment off-site and into adjacent drainage areas.
6. Best management practices shall be used at all times during construction to minimize turbidity at both the dredge and disposal sites. The disposal sites shall be constructed and maintained in a manner that minimizes the discharge of turbid waters into waters of the State. Best management practices shall include, but not limited to, the use of staked hay bales; staked filter cloth; sodding, seeding and mulching; staged construction; and

April 19, 2018

the installation of turbidity screens around the immediate project site. Any effluent from the disposal area shall be routed through a return swale system and filtered through a series of hay bales and silt fences so as to reduce the turbidity of the effluent.

7. Turbidity outside the limits of a 750-foot mixing zone shall not exceed the ambient turbidity by more than 50 Nephelometric Turbidity Units.
8. No sewage, oil, refuse, or other pollutants shall be discharged into the watercourse.

The Office of Pollution Control also certifies that there are no limitations under Section 302 nor standards under Sections 306 and 307 of the Federal Water Pollution Control Act which are applicable to the applicant's above-described activity.

This certification is valid for the project as proposed. Any deviations without proper modifications and/or approvals may result in a violation of the 401 Water Quality Certification. If we can be of further assistance, please contact us.
If we can be of further assistance, please contact us.

Sincerely,



Krystal Rudolph, P.E.
Chief, Environmental Permits Division

HMW: mhg

cc: Allison F. Monroe, U.S. Army Corps of Engineers, Mobile District
Willa Brantley, Department of Marine Resources
Paul Necaie, U.S. Fish and Wildlife Service
Bill Ainslie, Environmental Protection Agency