

**STATE OF MISSISSIPPI
AND FEDERALLY ENFORCEABLE
AIR POLLUTION CONTROL
PERMIT**

**TO OPERATE AIR EMISSIONS EQUIPMENT AT A
SYNTHETIC MINOR SOURCE**

THIS CERTIFIES THAT

Equilon Enterprises LLC, dba Shell Oil Products US, Collins Terminal
21 Kola Road
Collins, Mississippi
Covington County

has been granted permission to operate air emissions equipment in accordance with emission limitations, monitoring requirements and conditions set forth herein. This permit is issued in accordance with the Federal Clean Air Act and the provisions of the Mississippi Air and Water Pollution Control Law (Section 49-17-1 et. seq., Mississippi Code of 1972), the regulations and standards adopted and promulgated thereunder, and the State Implementation Plan for operating permits for synthetic minor sources.

MISSISSIPPI ENVIRONMENTAL QUALITY PERMIT BOARD



AUTHORIZED SIGNATURE

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Issued: December 11, 2014

Permit No.: 0640-00001

Modified: MAR 18 2019

Effective Date: As specified herein.

Expires: November 30, 2019

Section 1.

A. GENERAL CONDITIONS

1. This permit is for air pollution control purposes only.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.1.D.)
2. This permit is a Federally-approved permit to operate a synthetic minor source as described in 11 Miss. Admin. Code Pt. 2, R. 2.4.D.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.4.D.)
3. Any activities not identified in the application are not authorized by this permit.
(Ref.: Miss. Code Ann. 49-17-29 1.b)
4. The knowing submittal of a permit application with false information may serve as the basis for the Permit Board to void the permit issued pursuant thereto or subject the applicant to penalties for constructing or operating without a valid permit.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(5).)
5. The issuance of a permit does not release the permittee from liability for constructing or operating air emissions equipment in violation of any applicable statute, rule, or regulation of state or federal environmental authorities.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(7).)
6. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit unless halting or reducing activity would create an imminent and substantial endangerment threatening the public health and safety of the lives and property of the people of this state.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(15)(a).)
7. The issuance of this permit does not convey any property rights in either real or personal property, or any exclusive privileges, nor does it authorize any injury to private property or any invasion of personal rights, nor any infringement of Federal, State or local laws or regulations.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(15)(c).)
8. The permittee shall allow the Mississippi Department of Environmental Quality Office of Pollution Control and the Mississippi Environmental Quality Permit Board and/or their authorized representatives, upon the presentation of credentials:

- a. To enter upon the permittee's premises where an air emission source is located or in which any records are required to be kept under the terms and conditions of this permit, and
- b. At reasonable times to have access to and copy any records required to be kept under the terms and conditions of this permit; to inspect any monitoring equipment or monitoring method required in this permit; and to sample any air emission.

(Ref.: Miss. Code Ann. 49-17-21)

9. Except for data determined to be confidential under the Mississippi Air & Water Pollution Control Law, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the offices of the Mississippi Department of Environmental Quality Office of Pollution Control.

(Ref.: Miss. Code Ann. 49-17-39)

10. Nothing herein contained shall be construed as releasing the permittee from any liability for damage to persons or property by reason of the installation, maintenance, or operation of the air cleaning facility, or from compliance with the applicable statutes of the State, or with local laws, regulations, or ordinances.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(7).)

11. The provisions of this permit are severable. If any provision of this permit, or the application of any provision of this permit to any circumstances, is challenged or held invalid, the validity of the remaining permit provisions and/or portions thereof or their application to other persons or sets of circumstances, shall not be affected thereby.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.1.D(7).)

12. This permit does not authorize a modification as defined in Regulation 11 Miss. Admin. Code Pt. 2, Ch.2., "Permit Regulations for the Construction and/or Operation of Air Emission Equipment." A modification may require a Permit to Construct and a modification of this permit. Modification is defined as "Any physical change in or change in the method of operation of a facility which increases the actual emissions or the potential uncontrolled emissions of any air pollutant subject to regulation under the Federal Act emitted into the atmosphere by that facility or which results in the emission of any air pollutant subject to regulation under the Federal Act into the atmosphere not previously emitted. A physical change or change in the method of operation shall not include:

- a. Routine maintenance, repair, and replacement;
- b. Use of an alternative fuel or raw material by reason of an order under Sections 2(a) and (b) of the Federal Energy Supply and Environmental Coordination Act of 1974

- (or any superseding legislation) or by reason of a natural gas curtailment plan pursuant to the Federal Power Act;
- c. Use of an alternative fuel by reason of an order or rule under Section 125 of the Federal Act;
 - d. Use of an alternative fuel or raw material by a stationary source which:
 - (1) The source was capable of accommodating before January 6, 1975, unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Part 51, Subpart I, or 40 CFR 51.166; or
 - (2) The source is approved to use under any permit issued under 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Part 51, Subpart I, or 40 CFR 51.166;
 - e. An increase in the hours of operation or in the production rate unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Part 51, Subpart I or 40 CFR 51.166; or
 - f. Any change in ownership of the stationary source.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.1.C(15).)

B. GENERAL OPERATIONAL CONDITIONS

- 1. Should the Executive Director of the Mississippi Department of Environmental Quality declare an Air Pollution Emergency Episode, the permittee will be required to operate in accordance with the permittee's previously approved Emissions Reduction Schedule or, in the absence of an approved schedule, with the appropriate requirements specified in Regulation, 11 Miss. Admin. Code Pt. 2, "Regulations for the Prevention of Air Pollution Emergency Episodes" for the level of emergency declared.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.10.)

- 2. Any diversion from or bypass of collection and control facilities is prohibited, except as provided for in 11 Miss. Admin. Code Pt. 2, R. 1.10., "Air Emission Regulations for the Prevention, Abatement, and Control of Air Contaminants."

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.10.)

- 3. Solids removed in the course of control of air emissions shall be disposed of in a manner such as to prevent the solids from becoming windborne and to prevent the materials from entering State waters without the proper environmental permits.

(Ref.: Miss. Code Ann. 49-17-29 1.a(i and ii))

4. Except as otherwise specified herein, the permittee shall be subject to the following provisions with respect to upsets, startups, and shutdowns.

a. Upsets

- (1) For an upset defined in 11 Miss. Admin. Code Pt. 2, R. 1.2., the Commission may pursue an enforcement action for noncompliance with an emission standard or other requirement of an applicable rule, regulation, or permit. In determining whether to pursue enforcement action, and/or the appropriate enforcement action to take, the Commission may consider whether the source has demonstrated through properly signed contemporaneous operating logs or other relevant evidence the following:
 - (i) An upset occurred and that the source can identify the cause(s) of the upset;
 - (ii) The source was at the time being properly operated;
 - (iii) During the upset the source took all reasonable steps to minimize levels of emissions that exceeded the emission standard or other requirement of an applicable rule, regulation, or permit;
 - (iv) That within 5 working days of the time the upset began, the source submitted a written report to the Department describing the upset, the steps taken to mitigate excess emissions or any other noncompliance, and the corrective actions taken and;
 - (v) That as soon as practicable but no later than 24 hours of becoming aware of an upset that caused an immediate adverse impact to human health or the environment beyond the source boundary or caused a general nuisance to the public, the source provided notification to the Department.
- (2) In any enforcement proceeding by the Commission, the source seeking to establish the occurrence of an upset has the burden of proof.
- (3) This provision is in addition to any upset provision contained in any applicable requirement.
- (4) These upset provisions apply only to enforcement actions by the Commission and are not intended to prohibit EPA or third party enforcement actions.

b. Startups and Shutdowns (as defined by 11 Miss. Admin. Code Pt. 2, R. 1.2.)

- (1) Startups and shutdowns are part of normal source operation. Emission limitations apply during startups and shutdowns unless source specific emission limitations or work practice standards for startups and shutdowns are defined by an applicable rule, regulation, or permit.
- (2) Where the source is unable to comply with existing emission limitations established under the State Implementation Plan (SIP) and defined in this regulation, 11 Mississippi Administrative Code, Part 2, Chapter 1, the Department will consider establishing source specific emission limitations or work practice standards for startups and shutdowns. Source specific emission limitations or work practice standards established for startups and shutdowns are subject to the requirements prescribed in 11 Miss. Admin. Code Pt. 2, R. 1.10.B(2)(a) through (e).
- (3) Where an upset as defined in Rule 1.2 occurs during startup or shutdown, see the upset requirements above.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.10.)

5. Compliance Testing: Regarding compliance testing:

- a. The results of any emissions sampling and analysis shall be expressed both in units consistent with the standards set forth in any Applicable Rules and Regulations or this permit and in units of mass per time.
- b. Compliance testing will be performed at the expense of the permittee.
- c. Each emission sampling and analysis report shall include but not be limited to the following:
 - (1) Detailed description of testing procedures;
 - (2) Sample calculation(s);
 - (3) Results; and
 - (4) Comparison of results to all Applicable Rules and Regulations and to emission limitations in the permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.6.B(3), (4), and (6).)

C. PERMIT RENEWAL / MODIFICATION / TRANSFER / TERMINATION

6. For renewal of this permit, the applicant shall make application not less than one-hundred eighty (180) days prior to the expiration date of the permit substantiated with current emissions data, test results or reports or other data as deemed necessary by the

Mississippi Environmental Quality Permit Board. If the applicant submits a timely and complete application pursuant to this paragraph and the Permit Board, through no fault of the applicant, fails to act on the application on or before the expiration date of the existing permit, the applicant shall continue to operate the stationary source under the terms and conditions of the expired permit, which shall remain in effect until final action on the application is taken by the Permit Board. Permit expiration terminates the source's ability to operate unless a timely and complete renewal application has been submitted.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.8.)

7. The permittee shall furnish to the DEQ within a reasonable time any information the DEQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the DEQ copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee shall furnish such records to the DEQ along with a claim of confidentiality. The permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(15)(d).)

8. The permit and/or any part thereof may be modified, revoked, reopened, and reissued, or terminated for cause. Sufficient cause for a permit to be reopened shall exist when an air emissions stationary source becomes subject to Title V. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(15)(b).)

9. After notice and opportunity for a hearing, this permit may be modified, suspended, or revoked in whole or in part during its term for cause including, but not limited to:
 - a. Persistent violation of any terms or conditions of this permit.
 - b. Obtaining this permit by misrepresentation or failure to disclose fully all relevant facts; or
 - c. A change in federal, state, or local laws or regulations that require either a temporary or permanent reduction or elimination of previously authorized air emission.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.C.)

10. This permit may only be transferred upon approval of the Mississippi Environmental Quality Permit Board.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.16.B.)

SECTION 2

EMISSION POINT DESCRIPTION

The permittee is authorized to operate air emissions equipment, as described in the following table.

Emission Point	Facility Reference	Description
AA-001	Tank #1	1,176,000 gallon Distillate Storage Tank Fixed Roof
AA-002	Tank #2	1,671,600 gallon Gasoline, Fuel Grade Ethanol, or Distillate Storage Tank Internal Floating Roof with Vapor Mounted Resilient Seal with Rim Mounted Secondary Seal
AA-003	Tank #3	1,302,000 gallon Gasoline, Fuel Grade Ethanol, or Distillate Storage Tank Internal Floating Roof with Vapor Mounted Resilient Seal with Rim Mounted Secondary Seal
AA-004	Tank #4	9,401 gallon Gasoline Additive Storage Tank Fixed Roof
AA-005	Tank #5	6,000 gallon Gasoline Additive Storage Tank Fixed Roof
AA-006	Tank #6	2,000 gallon Gasoline Additive Storage Tank Fixed Roof
AA-007	Tank #7	5,711 gallon Separated Products Storage Tank Fixed, Vertical Roof
AA-008	-----	Truck Loading Rack with 2 Diesel and 2 Gasoline Arms Vapor Recovery Unit with Backup Combustion Unit
AA-011	Tank #9	4,000 gallon Gasoline Additive Storage Tank Fixed Roof
AA-012	Tank #8	8,000 gallon Separated Products Storage Tank Fixed Roof
AA-013	Tank #10	2,500 gallon Lubricity Additive Storage Tank Fixed Roof
AA-014	-----	Oil/Water Separator
AA-018	-----	100 gallon Gasoline Additive Storage Tank Fixed Roof
AA-019	-----	210,000 gallon Fuel Grade Ethanol Storage Tank Internal Floating Roof
AA-020	Tank #20	721,560 gallon Gasoline, Fuel Grade Ethanol, or Distillate Storage Tank Internal Floating Roof with Vapor Mounted Resilient Seal
FUG-001	-----	Fugitives from Equipment in Gasoline Service
FUG-002	-----	Fugitives from Equipment Not in Gasoline Service

SECTION 3 EMISSION LIMITATIONS AND STANDARDS

Emission Point	Applicable Requirement	Condition Number(s)	Pollutant/Parameter	Limitation/Standard
Facility-Wide	11 Miss. Admin. Code Pt. 2, R. 1.3.A.	3.1	Smoke	Opacity shall not exceed 40%
	11 Miss. Admin. Code Pt. 2, R. 1.3.B.	3.2		
	11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).	3.3	Throughput	Shall not exceed 264,105,600 gallons.
	40 CFR Part 63, Subpart BBBBBB (National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities) 40 CFR Part 63.11081(a)(1)	3.4	HAPs	General Applicability
AA-002 AA-003 AA-008 AA-020	40 CFR Part 63.11087(b), Subpart BBBBBB	3.5	HAPs	Compliance Requirement
AA-008	11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).	3.6	TOC	Shall not exceed 15 mg/L of gasoline loaded.
		3.7		Operational Requirement
	40 CFR Part 63.11089(a), (b), (c), (d), Subpart BBBBBB	3.8	HAPs	Inspection Requirement
AA-019 AA-020	40 CFR Part 60, Subpart Kb (Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) For Which Construction, Reconstruction, or Modification Commenced after July 23, 1984) 40 CFR Part 60.110b(a)	3.9	VOCs	General Applicability
	40 CFR Part 60.112b(a) Subpart Kb	3.10		Operational Requirement

- 3.1. For the entire facility, the permittee shall not cause, permit, or allow the emission of smoke from a point source into the open air from any manufacturing, industrial, commercial or waste disposal process which exceeds forty (40) percent opacity subject to the exceptions provided in (a) and (b).
- a) Startup operations may produce emissions which exceed 40% opacity for up to fifteen minutes per startup in any one hour and not to exceed three startups per stack in any twenty-four-hour period.
 - b) Emissions resulting from soot blowing operations shall be permitted provided such emissions do not exceed 60 percent opacity, and provided further that the aggregate duration of such emissions during any twenty-four-hour period does not exceed ten minutes per billion BTU gross heating value of fuel in any one hour.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.A.)
- 3.2. For the entire facility, except as otherwise specified or limited herein, the permittee shall not cause, allow, or permit the discharge into the ambient air from any point source or emissions, any air contaminant of such opacity as to obscure an observer's view to a degree in excess of 40% opacity, equivalent to that provided in Condition 3.1. This shall not apply to vision obscuration caused by uncombined water droplets.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.B.)
- 3.3. For the entire facility, the permittee shall limit facility-wide aggregate throughput (gasoline, gasoline additives, distillate, distillate additives, and ethanol) to no more than 264,105,600 gallons in any consecutive 12-month period
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).)
- 3.4. For the entire facility, the permittee is subject to and shall comply with all applicable requirements of the National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities (40 CFR Part 63, Subpart BBBB) and applicable provisions of the General Provisions (40 CFR Part 63, Subpart A) as stated in Table 3 of Subpart BBBB..
(Ref.: 40 CFR Part 63.11081(a)(1), Subpart BBBB)
- 3.5. For Emission Points AA-002, AA-003, AA-008, and AA-020, the permittee shall comply with the requirements of Subpart BBBB by January 10, 2011, except that storage vessels equipped with floating roofs and not meeting the requirements of Table 1 of Subpart BBBB must be in compliance at the first degassing and cleaning activity after January 10, 2011 or by January 10, 2018, whichever is first.
(Ref.: 40 CFR Part 63.11087(b), Subpart BBBB)

- 3.6. For Emission Point AA-008, the permittee shall limit Total Organic Compound (TOC) emissions to 15 mg/L of gasoline loaded, as determined by EPA Reference Methods 25A or 25B, 40 CFR Part 60, Appendix A, and the test methods and procedures specified in 40 CFR Part 60.503.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).)
- 3.7. For Emission Point AA-008, the permittee shall only operate the loading rack when the VRU or Backup VCU are available. The VRU and Backup VCU shall be operated and maintained according to the manufacturers' recommendations.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).)
- 3.8. For Emission Point AA-008, the permittee shall perform a monthly leak inspection of all equipment in gasoline service, as defined in 63.11100. For this inspection, detection methods incorporating sight, sound, and smell are acceptable.
- A log book shall be used and shall be signed by the permittee at the completion of each inspection. A section of the log book shall contain a list, summary description, or diagram(s) showing the location of all equipment in gasoline service at the facility.
- Each detection of a liquid or vapor leak shall be recorded in the log book. When a leak is detected, an initial attempt at repair shall be made as soon as practicable, but no later than 5 calendar days after the leak is detected. Repair or replacement of leaking equipment shall be completed within 15 calendar days after detection of each leak.
- Delay of repair of leaking equipment will be allowed if the repair is not feasible within 15 days. The owner or operator shall provide in the semiannual report specified in 63.11095(b), the reason(s) why the repair was not feasible and the date each repair was completed.
(Ref.: 40 CFR Part 63.11089(a), (b), (c), (d), Subpart BBBBBB)
- 3.9. For Emission Points AA-019 and AA-020, the permittee is subject to and shall comply with all applicable requirements of the Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) For Which Construction, Reconstruction, or Modification Commenced after July 23, 1984 (40 CFR Part 60, Subpart Kb) and General Provisions (40 CFR Part 60, Subpart A).
(Ref.: 40 CFR Part 60.110b(a), Subpart Kb)
- 3.10. For Emission Points AA-019 and AA-020, the permittee shall equip the storage vessel with an internal floating roof with the specifications of 40 CFR Part 60.112b(a)(1).
(Ref.: 40 CFR Part 60.112b(a), Subpart Kb)

SECTION 4
WORK PRACTICES

Emission Point	Applicable Requirement	Condition Number(s)	Pollutant/Parameter	Work Practice
Facility-Wide	11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).	4.1	Work Practice	Operational Requirement
AA-002 AA-003 AA-020	40 CFR Part 63.11087(a), Table 1, Subpart BBBBBB	4.2	HAPs	Operational Requirement
AA-008	40 CFR Part 63.11088(a), (b), Table 2(1)(a), (c), (d), Subpart BBBBBB	4.3	HAPs	Operational Requirement

- 4.1. For the entire facility, the permittee shall operate and maintain the equipment to assure that the emission rates will not, at any time, exceed the rates allowed by the Mississippi Air Emission Regulations.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).)
- 4.2. For Emission Points AA-002, AA-003, and AA-020, the permittee shall comply with one of the following options:
- a) Reduce emissions of total organic Hazardous Air Pollutants (HAPs) or TOC from each storage tank by 95 weight-percent with a closed vent system and control device as specified in 40 CFR Part 60.112b(a)(3), Subpart Kb.
 - b) Equip each internal floating roof gasoline storage tank according to the requirements in 40 CFR Part 60.112b(a)(1) excluding 40 CFR Part 60.112b(a)(1)(ii)(B) and 40 CFR Part 60.112b(a)(1)(iv) through (ix).
 - c) Equip and operate each internal floating roof gasoline storage tank according to the applicable requirements in 40 CFR Part 63.1063(a)(1) and (b), Subpart WW.
(Ref.: 40 CFR Part 63.11087(a), Table 1, Subpart BBBBBB)

- 4.3. For Emission Point AA-008, the permittee shall equip the loading rack with the following:
- a) A vapor collection system designed to collect the TOC vapors displaced from cargo tanks during product loading. The vapor collection system shall be designed to prevent any TOC vapors collected at one loading rack or lane from passing through another loading rack or lane to the atmosphere.
 - b) A control device designed and operated to reduce emissions of TOC to less than or equal to 80 mg/l of gasoline loaded into the gasoline cargo tanks at the loading rack.
 - c) The permittee shall limit the loading of gasoline into gasoline cargo tanks that are vapor tight using the procedures specified in 60.502(e) through (j).

As an alternative for railcar cargo tanks to the requirements specified in above, the permittee may comply with the requirements specified in 63.422(e).

(Ref.: 40 CFR Part 63.11088(a) and (b) and Table 2(1)(a), (c), (d), Subpart BBBBBB)

SECTION 5 MONITORING AND RECORDKEEPING REQUIREMENTS

Emission Point	Applicable Requirement	Condition Number(s)	Pollutant/Parameter	Monitoring/Recordkeeping Requirement
Facility-Wide	11 Miss. Admin. Code Pt. 2, R. 2.9.	5.1	Recordkeeping	Maintain records for a minimum of 5 years.
	11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).	5.2	Throughput	Record monthly aggregate throughput.
	40 CFR Part 63.11092(f)(1), Subpart BBBBBBBB 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).	5.3	HAPs	Annual Certification Test Requirement
	40 CFR Part 63.11094(b), Subpart BBBBBBBB	5.4		Gasoline cargo tank loading recordkeeping requirement
	40 CFR Part 63.11094(c), Subpart BBBBBBBB	5.5		Documentation Requirement
	40 CFR Part 63.11094(g), Subpart BBBBBBBB	5.6		Malfunction Recordkeeping Requirement
AA-008	11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).	5.7	HAPs	Compliance Testing Requirement
	11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).	5.8		Recordkeeping Requirement
	40 CFR Part 63.11094(d), (e), Subpart BBBBBBBB	5.9		Recordkeeping Requirement
	40 CFR Part 63.11088(d), 63.11092(a), Subpart BBBBBBBB	5.10		Performance Testing Requirement
	40 CFR Part 63.11092(b)(1)(iii)(B)(I), (2), Subpart BBBBBBBB	5.11		Continuous Monitoring System Requirement
	40 CFR Part 63.11092(b)(3), (4), (5), Subpart BBBBBBBB	5.12		Monitoring Alternative Operating Parameter
	40 CFR Part 63.11092(d), Subpart BBBBBBBB	5.13		Monitoring Requirement
	40 CFR Part 63.11089(a), (b), (c), (d), Subpart BBBBBBBB	5.14		Continuous Monitoring System Recordkeeping Requirement
FUG-001	40 CFR Part 60.113b(a)(1), (2), (4), Subpart Kb	5.15	HAPs	Leak Inspection Requirement
AA-019 AA-020	40 CFR Part 60.115b(a)(2), (3), Subpart Kb	5.16	VOCs	Monitoring Requirement
	40 CFR Part 60.116b(b), (c), Subpart Kb	5.17		Recordkeeping Requirement
	40 CFR Part 63.11094(f)(1), (3), Subpart BBBBBBBB	5.18		Recordkeeping Requirement

- 5.1. For the entire facility, the permittee shall demonstrate compliance with Condition 3.3 by maintaining monthly records of the facility-wide aggregate throughput (gasoline, gasoline additives, distillate, distillate additives, and ethanol). The permittee shall maintain these records on file at the facility for five (5) years and shall make them available upon request by MDEQ.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).)

- 5.2. For the entire facility, the permittee shall retain all required records, monitoring data, supporting information and reports for a period of at least five (5) years from the date of the monitoring sample, measurement, report, or application. Support information includes all calibration and maintenance records, all original strip-chart recordings or other data for continuous monitoring instrumentation, and copies of all reports required by this permit. Copies of such records shall be submitted to MDEQ as required by Applicable Rules and Regulations or this permit or upon request.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.9.)

- 5.3. For the entire facility, the permittee shall verify that each gasoline cargo tank loaded has performed the annual certification test for gasoline cargo tanks consisting of the test method described in EPA Method 27, Appendix A-8, 40 CFR Part 60.

The annual certification test shall be performed using a time period (t) for the pressure and vacuum tests of 5 minutes. The initial pressure (P_i) for the pressure test shall be 460 millimeters (mm) of water (18 inches of water), gauge. The initial vacuum (V_i) for the vacuum test shall be 150 mm of water (6 inches of water), gauge. The maximum allowable pressure and vacuum changes (Δp , Δv) for all affected gasoline cargo tanks shall be 3 inches of water, or less, in 5 minutes.

(Ref.: 40 CFR Part 63.11092(f)(1), Subpart BBBBBBB, 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).)

- 5.4. For the entire facility, the permittee shall keep records of the test results for each gasoline cargo tank loading at the facility as specified in paragraphs (a), (b), and (c):
- a) Annual certification testing performed under Condition 5.13.
 - b) The documentation file shall be kept up-to-date for each gasoline cargo tank loading at the facility. The documentation of each test shall include, as a minimum, the following information:
 - 1) Name of test: Annual Certification Test—Method 27.
 - 2) Cargo tank owner's name and address.
 - 3) Cargo tank identification number.
 - 4) Test location and date.
 - 5) Tester name and signature.
 - 6) Witnessing inspector, if any: Name, signature, and affiliation.
 - 7) Vapor tightness repair: Nature of repair work and when performed in relation to vapor tightness testing.
 - 8) Test results: Test pressure; pressure or vacuum change, mm of water; time period of test; number of leaks found with instrument; and leak definition.
 - c) If the permittee is complying with the alternative requirements in 63.11088(b), you must keep records documenting that you have verified the vapor tightness testing according to the requirements of MDEQ.

(Ref.: 40 CFR Part 63.11094(b), Subpart BBBBBB)

5.5. For the entire facility, as an alternative to keeping records at the terminal of each gasoline cargo tank test result as required in Condition 5.3, the permittee may comply with the requirements in either paragraph (a) or (b):

- a) An electronic copy of each record is instantly available at the terminal.
 - 1) The copy of each record in paragraph (a) is an exact duplicate image of the original paper record with certifying signatures.
 - 2) MDEQ is notified in writing that each terminal using this alternative is in compliance with paragraph (a)(1).
- b) If the permittee uses a terminal automation system to prevent gasoline cargo tanks that do not have valid cargo tank vapor tightness documentation from loading (e.g., via a card lock-out system), a copy of the documentation is made available (e.g., via facsimile) for inspection by MDEQ's delegated representatives during the course of a site visit, or within a mutually agreeable time frame.
 - 1) The copy of each record in paragraph (b) is an exact duplicate image of the original paper record with certifying signatures.
 - 2) MDEQ is notified in writing that the terminal using this alternative is in compliance with paragraph (b)(2).

(Ref.: 40 CFR Part 63.11094(c), Subpart BBBBBBB)

5.6. For the entire facility, the permittee shall keep the following records:

- a) Records of the occurrence and duration of each malfunction of operation (*i.e.*, process equipment) or the air pollution control and monitoring equipment.
- b) Records of actions taken during periods of malfunction to minimize emissions in accordance with 63.11085(a), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.

(Ref.: 40 CFR Part 63.11094(g) Subpart BBBBBBB)

- 5.7. For Emission Point AA-008, the permittee shall demonstrate compliance with the additized gasoline (each grade of gasoline as received from the pipeline plus additive) loading emission limitation by using the test methods and procedures of 40 CFR Part 60.503. The compliance test shall be performed after the issuance date of this permit, but no later than ninety (90) days prior to its expiration date. Each test report shall be submitted within forty-five (45) days to the test date.

The permittee shall submit a written test protocol at least thirty (30) days prior to the intended test date(s) to ensure that all test methods and procedures are acceptable to MDEQ. Also, the permittee shall notify MDEQ in writing at least ten (10) days prior to the test day so that an observer may be afforded the opportunity to witness the test.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).)

- 5.8. For Emission Point AA-008, the permittee shall demonstrate compliance with Condition 3.7 by keeping a record of each event when gasoline is loaded while the VRU or Backup VCU is not operating. The record of the deviation shall include the date, duration, and gallons loaded.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).)

- 5.9. For Emission Point AA-008, the permittee shall demonstrate compliance with Condition 3.8 by preparing and maintaining a record describing the types, identification numbers, and locations of all equipment in gasoline service. For facilities electing to implement an instrument program under 63.11089, the record shall contain a full description of the program.

The permittee shall keep a record in the log book for each leak that is detected, and the log book shall contain the following information:

- a) The equipment type and identification number.
- b) The nature of the leak (i.e., vapor or liquid) and the method of detection (i.e., sight, sound, or smell).
- c) The date the leak was detected and the date of each attempt to repair the leak.
- d) Repair methods applied in each attempt to repair the leak.
- e) “Repair delayed” and the reason for the delay if the leak is not repaired within 15 calendar days after discovery of the leak.
- f) The expected date of successful repair of the leak if the leak is not repaired within 15 days.
- g) The date of successful repair of the leak.

(Ref.: 40 CFR Part 63.11094(d) and (e), Subpart BBBBBBB)

5.10. For Emission Point AA-008, the permittee shall conduct a performance test on the vapor processing and collection systems according to either paragraph (a) or (b) below:

- a) Use the test methods and procedures in 40 CFR 60.503, except a reading of 500 ppm shall be used to determine the level of leaks to be repaired under 40 CFR Part 60.503(b).
- b) Use alternative test methods and procedures in accordance with the alternative test method requirements in 40 CFR Part 63.7(f).

If operating the gasoline loading rack in compliance with an enforceable State permit that requires the loading rack to meet an emission limit of 80 mg/L or less of gasoline loaded, the permittee may submit a statement by a responsible official certifying the compliance status of the loading rack in lieu of the aforementioned performance testing requirement.

If a performance test has been conducted on the vapor processing and collection systems with 5 years prior to January 8, 2008, and the test is representative of current or anticipates operating processes and conditions, the permittee may submit the results of such testing in lieu of the aforementioned performance testing requirement, provided the testing was conducted using the test methods and procedures in 40 CFR Part 60.503. Should the Department deem the prior test data unacceptable, the facility is still required to meet the requirement to conduct an initial performance test within 180 days of the compliance date specified in 40 CFR Part 63.11083; thus, previous test reports should be submitted as soon as possible after January 10, 2008.

The permittee shall maintain the Continuous Emission Monitoring System (CEMS) for the Vapor Recovery Unit (VRU) at no greater than 1.6% TOC by volume (as propane) in the VRU outlet stream monitored continuously by a CEMS and averaged over a six-hour rolling period. The normal operating range from previous performance tests resulted in an operating range of 0.24% to 0.81% TOC.

The permittee shall install, calibrate, certify, operate, and maintain a continuous parameter monitoring system (CPMS) for the backup VCU that is capable of measuring temperature in the firebox or in the ductwork immediately downstream from the firebox. As an alternative to the CPMS requirement listed above the permittee may meet the requirements listed in Condition 5.10 for the backup VCU.

For each performance test conducted under this condition, the permittee must determine a monitored operating parameter for the vapor processing system (backup VCU) using the CPMS. The operating parameter must be continuously monitored during the performance test. The permittee shall not be required to perform this if they elect to use the alternative requirements listed in Condition 5.10.

The permittee shall document the reasons for a change in the operating parameter value being monitored where there is a change from the value obtained from a previous performance test.

(Ref.: 40 CFR Part 63.11088(d), 63.11092(a), Subpart BBBBBBB)

- 5.11. For Emission Point AA-008, the permittee shall operate and monitor the Backup VCU in the following manner as an alternative to the CPMS required by Condition 5.10.
- a) The presence of the Backup VCU pilot flame shall be monitored using a heat-sensing device, such as an ultraviolet beam sensor or a thermocouple, installed in proximity of the pilot flame, to indicate the presence of a flame. The heat-sensing device shall send a positive parameter value to indicate that the pilot flame is on, or a negative parameter value to indicate that the pilot flame is off.
 - b) The permittee shall develop and submit to MDEQ a monitoring and inspection plan that describes the permittee's approach for meeting the following requirements:
 - 1) The Backup VCU shall be equipped to automatically prevent gasoline loading operations from beginning at any time that the pilot flame is absent.
 - 2) The permittee shall, during each day of operation of the loading rack, the proper operation of the assist-air blower and the vapor line valve. Verification shall be through visual observation, or through an automated alarm or shutdown system that monitors system operations. A manual or electronic record of the start and end of a shutdown event may be used.
 - 3) The permittee shall perform semi-annual preventative maintenance inspection of the Backup VCU, including the automated alarm or shutdown system for those units so equipped according to the recommendations of the manufacturer of the system.
 - 4) The monitoring plan developed under Paragraph (b) shall specify conditions that would be considered malfunctions of the Backup VCU during the inspections or automated monitoring performed under Paragraph 2 and 3, described specific corrective actions that will be taken to correct any malfunction, and define what the permittee would consider to be a timely repair for each potential malfunction.

- 5) The permittee shall document any system malfunction, as defined in the monitoring and inspection plan, and any activation of the automated alarm or shutdown system with a written entry into a log book or other permanent form of record. Such record shall also include a description of the corrective action taken and whether such corrective actions were taken in a timely manner, as defined in the monitoring and inspection plan, as well as an estimate of the amount of gasoline loaded during the period of the malfunction.

(Ref.: 40 CFR Part 63.11092(b)(1)(iii)(B)(1), (2), Subpart BBBBBBB)

5.12. Monitoring an alternative operating parameter or a parameter of a vapor processing system other than those listed in Conditions 5.9 or 5.10 will be allowed upon demonstrating to MDEQ's satisfaction that the alternative parameter demonstrates continuous compliance with the emission standard in Condition 3.6.

- a) Determine an operating parameter value based on the parameter data monitored during the performance test, supplemented by engineering assessments and the manufacturer's recommendations.
- b) Provide for the MDEQ's approval the rationale for the selected operating parameter value, monitoring frequency, and averaging time, including data and calculations used to develop the value and a description of why the value, monitoring frequency, and averaging time demonstrate continuous compliance with the emission standard in Condition 3.6.
- c) If the permittee chooses to comply with the performance testing alternatives in Condition 5.9, the monitored operating parameter value may be determined according to the provisions (i) and (ii) below:
 - 1) Monitor an operating parameter that has been approved by MDEQ and is specified in the operating permit. At the time that MDEQ requires a new performance test, the permittee must determine the monitored operating parameter value according to the requirements specified in this condition.
 - 2) Determine an operating parameter value based on engineering assessment and manufacturer's recommendation and submit the information specified in Paragraph (c) above for approval by MDEQ. At the time that MDEQ requires a new performance test, the permittee must determine the monitored operating parameter value according to the requirements specified in this condition.

(Ref.: 40 CFR Part 63.11092(b)(3), (4), (5), Subpart BBBBBBB)

5.13. For Emission Point AA-008, the permittee shall comply with the following requirements:

- a) The permittee shall operate the vapor processing system in a manner not to exceed or not to go below, as appropriate, the operating parameter value for the parameters described in Condition 5.9.
- b) In cases where an alternative parameter pursuant to Condition 5.10 is approved, the permittee shall operate the vapor processing system in a manner not to exceed or not to go below, as appropriate, the alternative operating parameter value.
- c) Operation of the vapor processing system in a manner exceeding or going below the operating parameter value, as appropriate, shall constitute a violation of the emission standard in Condition 4.3, except as specified in Condition 5.12(d).
- d) For the monitoring and inspection, as required under Condition 5.10, malfunctions that are discovered shall not constitute a violation of the emission standard in Condition 4.3 if corrective actions as described in the monitoring and inspection plan are followed. The owner or operator must:
 - 1) Initiate corrective action to determine the cause of the problem within 1 hour;
 - 2) Initiate corrective action to fix the problem within 24 hours;
 - 3) Complete all corrective actions needed to fix the problem as soon as practicable consistent with good air pollution control practices for minimizing emissions;
 - 4) Minimize periods of start-up, shutdown, or malfunction; and
 - 5) Take any necessary corrective actions to restore normal operation and prevent the recurrence of the cause of the problem.

(Ref.: 40 CFR Part 63.11092(d), Subpart BBBBBBB)

- 5.14. For Emission Point AA-008, the permittee shall keep an up-to-date, readily accessible record of the continuous parameter monitoring data required under Condition 5.9 unless the permittee chooses to meet the requirements of Condition 5.10. This record shall indicate the time intervals during which loadings of gasoline cargo tanks have occurred or, alternatively, shall record the operating parameter data only during such loadings. The date and time of day shall also be indicated at reasonable intervals on this record.

The permittee shall keep an up-to-date, readily accessible copy of the monitoring and inspection plan required under Condition 5.10 if the permittee chooses this compliance option.

(Ref.: 40 CFR Part 63.11094(f)(1), (3), Subpart BBBBBBB)

- 5.15. For Emission Point FUG-001, the permittee shall perform a monthly leak inspection of all equipment in gasoline service, as defined in 40 CFR 63.11100. For this inspection, detection methods incorporating sight, sound, and smell are acceptable.

A log book shall be used and shall be signed by the permittee at the completion of each inspection. A section of the log book shall contain a list, summary description, or diagram(s) showing the location of all equipment in gasoline service at the facility.

Each detection of a liquid or vapor leak shall be recorded in the log book. When a leak is detected, an initial attempt at repair shall be made as soon as practicable, but no later than 5 calendar days after the leak is detected. Repair or replacement of leaking equipment shall be completed within 15 calendar days after detection of each leak.

Delay of repair of leaking equipment will be allowed if the repair is not feasible within 15 days. The permittee shall provide in the semiannual report specified in 40 CFR Part 63.11095(b), the reason(s) why the repair was not feasible and the date each repair was completed.

(Ref.: 40 CFR Part 63.11089(a), (b), (c), (d), Subpart BBBBBBB)

- 5.16. For Emission Points AA-019 and AA-020, the internal floating roof, the primary seal, and the secondary seal shall be visually inspected prior to filling the storage vessel with VOL. Any defects in the seals or internal floating roof shall be repaired before filling the vessel.

The internal floating roof and the primary seal or secondary seal shall be visually inspected through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If a failure is detected during the inspection, the failure shall be repaired or the tank emptied and removed from service within 45 days, unless an extension is requested.

The internal floating roof, the primary seal, the secondary seal, gaskets, slotted membranes and sleeves seals shall be visually inspected each time the storage vessel is emptied and degassed. Defects shall be repaired before refilling the storage vessel. This type of inspection shall be conducted at intervals no greater than 10 years.

(Ref.: 40 CFR Part 60.113b(a)(1), (2), (4), Subpart Kb)

- 5.17. For Emission Points AA-019 and AA-020, permittee shall maintain records of each inspection. The records shall include the storage vessel identification, inspection date and observed condition of each component of the control equipment (seals, internal floating roof, and fittings). If any defects are discovered during the annual visual inspection, a report that identifies the storage vessel, the nature of the defects, and the date the repair was made, shall be furnished to MDEQ within 30 days of the inspection. (Ref.: 40 CFR Part 60.115b(a)(2), (3), Subpart Kb)

- 5.18. For Emission Points AA-019 and AA-020, the permittee shall keep readily accessible records showing the dimensions and capacity of the storage vessel.

The permittee shall maintain a record of the VOL stored, the period of storage, and the maximum true vapor pressure of the VOL during the respective storage period.

(Ref.: 40 CFR Part 60.116b(b), (c), Subpart Kb)

SECTION 6 REPORTING REQUIREMENTS

Emission Point	Applicable Requirement	Condition Number(s)	Reporting Requirement
Facility-Wide	11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).	6.1	Report permit deviations within five (5) working days.
		6.2	Submit certified semi-annual monitoring report.
		6.3	All documents submitted to MDEQ shall be certified by a Responsible Official.
		6.4	Report semi-annually aggregate throughput.
AA-002 AA-003 AA-008 AA-020 FUG-001	40 CFR Part 63.11093(a), Subpart BBBBBBB	6.5	Initial Notification Requirement
	40 CFR Part 63.11093(b), Subpart BBBBBBB	6.6	Reporting Requirement
	40 CFR Part 63.11093(c), Subpart BBBBBBB	6.7	Notification of Performance Test Requirement
	40 CFR Part 63.11087(e), 63.11088(f), 63.11089(g), 63.11095(a)(1), (2), (3), Subpart BBBBBBB	6.8	Reporting Requirement
	40 CFR Part 63.11087(e), 63.11088(f), 63.11089(g), 63.11095(b), (c), Subpart BBBBBBB	6.9	Excess Emissions Reporting Requirement
AA-008	11 Miss. Admin. Code Pt.2, R. 2.2.B(11).	6.10	Reporting Requirement
AA-019 AA-020	40 CFR Part 60.113b(a)(5), Subpart Kb	6.11	Reporting Requirement
	40 CFR Part 60.115b(a)(1), Subpart Kb	6.12	Reporting Requirement

- 6.1. Except as otherwise specified herein, the permittee shall report all deviations from permit requirements, including those attributable to upsets, the probable cause of such deviations, and any corrective actions or preventive measures taken. Said report shall be made within five (5) working days of the time the deviation began.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).)
- 6.2. Except as otherwise specified herein, the permittee shall submit a certified semi-annual synthetic minor monitoring report. The semi-annual reporting periods will be from January 1 through June 30 and from July 1 through December 31. Compliance reports shall be postmarked no later than 31st of January or the 31st of July for the preceding semi-annual reporting period. This report shall address any required monitoring specified in the permit. All instances of deviations from permit requirements must be clearly identified in the report. Where no monitoring data is required to be reported and/or there are no deviations to report, the report shall contain the appropriate negative declaration.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).)
- 6.3. Any document required by this permit to be submitted to the MDEQ shall contain a certification signed by a responsible official or duly authorized representative stating that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate and complete.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).)
- 6.4. For the entire facility, the permittee shall submit a semi-annual report to the Office of Pollution Control indicating the facility-wide aggregate throughput (gasoline, gasoline additives, distillate, distillate additives, and ethanol) for each month and each consecutive 12-month period.
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).)
- 6.5. For Emission Points AA-002, AA-003, AA-008, AA-020, and FUG-001, the permittee must submit an Initial Notification as specified in 63.9(b). If the facility is in compliance with the requirements of Subpart BBBBBB at the time the Initial Notification is due, the Notification of Compliance Status required by Condition 6.6 may be submitted in lieu of the Initial Notification.
(Ref.: 40 CFR Part 63.11093(a), Subpart BBBBBB)

- 6.6. For Emission Points AA-002, AA-003, AA-008, AA-020, and FUG-001, the permittee shall submit to MDEQ a notification of compliance status, signed by the responsible official who shall certify its accuracy, attesting to where the source has complied with the relevant standard. This notification shall contain the following information:
- a) The methods that were used to determine compliance.
 - b) The results of any performance tests, opacity or visible emission observations, continuous monitoring system (CMS) performance evaluations, and/or other monitoring procedures or methods that are conducted.
 - c) The methods that will be used for determining continuing compliance, including a description of monitoring and reporting requirements and test methods.
 - d) The type and quantity of hazardous air pollutants emitted by the source (or surrogate pollutants if specified in the relevant standard), reported in units and average times and in accordance with the test methods specified.
 - e) If the relevant standard applies to both major and area sources, an analysis demonstrating whether the affected source is a major source (using the emissions data generated for this notification).
 - f) A description of the air pollution control equipment (or method) for each emission point, including each control device (or method) for each hazardous air pollutant and the control efficiency (percent) for each control device (or method).
 - g) A statement by the permittee of the affected existing, new, or reconstructed source as to whether the source has complied with the relevant standard of other requirements.

The notification must be sent to MDEQ before the close of business of the 60th day following the completion of the relevant compliance demonstration activity. The Notification of Compliance Status must specify which of the compliance options included in Table 1 of 40 CFR Part 63, Subpart BBBBBBB is used to comply with the subpart.

(Ref.: 40 CFR Part 63.11093(b), Subpart BBBBBB)

- 6.7. For Emission Points AA-002, AA-003, AA-008, AA-020, and FUG-001, the permittee shall submit a Notification of Performance Test as specified in 40 CFR Part 60.9(e) prior to conducting the performance test required in 40 CFR Part 63.11092(a) or 63.11092(b). (Ref.: 40 CFR Part 63.11093(c), Subpart BBBBBB)

- 6.8. For Emission Points AA-002, AA-003, AA-008, AA-020, and FUG-001, the permittee shall submit the following information to MDEQ in the semi-annual compliance report beginning 6 months after January 10, 2011:
- a) For storage vessels, if the permittee is complying with options 2(a) or 2(b) in Table 1 of Subpart BBBBBB, the information specified in 40 CFR Part 60.115b(a) or 60.115b(c), depending upon the control equipment installed, or if the permittee is complying with option 2(d) in Table 1 of Subpart BBBBBB, the information specified in 40 CFR Part 63.1066.
 - b) For loading racks, each loading of a gasoline cargo tank for which vapor tightness documentation had not been previously obtained by the facility.
 - c) For equipment leak inspections, the number of equipment leaks not repaired within 15 days after detection.
- (Ref.: 40 CFR Part 63.11087(e), 63.11088(f), 63.11089(g), 63.11095(a)(1), (2), (3), Subpart BBBBBB))
- 6.9. For Emission Points AA-002, AA-003, AA-008, AA-020, and FUG-001, the permittee shall submit an excess emissions report to MDEQ at the time the semi-annual compliance report is submitted for a 6-month period during which an excess emission event has occurred. If no excess emission events have occurred during the previous 6-month period, no report is required. Excess emissions events and the information to be included in the excess emissions report, are specified in paragraphs (a) through (e) of this condition.
- a) Each instance of a non-vapor-tight gasoline cargo tank loading at the facility in which the permittee failed to take steps to assure that such cargo tank would not be reloaded at the facility before vapor tightness documentation for that cargo tank was obtained.
 - b) Each reloading of a non-vapor-tight gasoline cargo tank at the facility before vapor tightness documentation for that cargo tank is obtained by the facility in accordance with 40 CFR Part 63.11094(b).
 - c) Each exceedance or failure to maintain, as appropriate, the monitored operating parameter value determined under 40 CFR Part 63.11092(b). The report shall include the monitoring data for the days on which exceedances or failures to maintain have occurred, and a description and timing of the steps taken to repair or perform maintenance on the vapor collection and processing systems or the CMS.
 - d) Each instance in which malfunctions discovered during the monitoring and inspections required under 40 CFR Part 63.11092(b)(1)(i)(B)(2) and (b)(1)(iii)(B)(2) were not resolved according to the necessary corrective actions

described in the monitoring and inspection plan. The report shall include a description of the malfunction and the timing of the steps taken to correct the malfunction.

e) For each occurrence of an equipment leak for which no repair attempt was made within 5 days or for which repair was not completed within 15 days after detection:

- 1) The date on which the leak was detected.
- 2) The date of each attempt to repair the leak.
- 3) The reasons for the delay of repair.
- 4) The date of successful repair.

(Ref.: 40 CFR Part 63.11087(e), 63.11088(f), 63.11089(g), 63.11095(b), (c), Subpart BBBBBB)

6.10. For Emission Point AA-008, the permittee shall report any deviation in which the loading rack is operated without the control of the VRU or Backup VCU. The deviation shall be included in the certified semi-annual report.

(Ref.: 11 Miss. Admin. Code Pt.2, R. 2.2.B(11).)

6.11. For Emission Points AA-019 and AA-020, the permittee shall notify MDEQ at least 30 days prior to the filling or refilling of the storage vessel after the inspections required by 40 CFR Part 60.113b(a)(1) or (a)(4). If the inspection required by 40 CFR Part 60.113b(a)(4) is unplanned, the permittee shall notify MDEQ at least 7 days prior to the refilling of the storage vessel.

(Ref.: 40 CFR Part 60.113b(a)(5), Subpart Kb)

6.12. For Emission Points AA-019 and AA-020, the permittee shall submit a report certifying that the internal floating roof meets the equipment specifications of 40 CFR Part 60.112b(a)(1) and the testing procedures of 40 CFR Part 60.113b(a)(1) shall be furnished to MDEQ with the notifications of initial startup required by 40 CFR Part 60.7(a)(3).

(Ref.: 40 CFR Part 60.115b(a)(1), Subpart Kb)