

STATE OF MISSISSIPPI AIR POLLUTION CONTROL PERMIT

TO CONSTRUCT AIR EMISSIONS EQUIPMENT

THIS CERTIFIES THAT

Steel Dynamics Columbus
1945 Airport Road
Columbus, Mississippi
Lowndes County

has been granted permission to construct air emissions equipment to comply with the emission limitations, monitoring requirements and other conditions set forth herein. This permit is issued in accordance with the provisions of the Mississippi Air and Water Pollution Control Law (Section 49-17-1 et. seq., Mississippi Code of 1972), and the regulations and standards adopted and promulgated thereunder.

MISSISSIPPI ENVIRONMENTAL QUALITY PERMIT BOARD



AUTHORIZED SIGNATURE

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Issued: May 1, 2014

Permit No.: 1680-00064

Modified: October 27, 2014 (Ownership Change)

Part I.

A. GENERAL CONDITIONS

1. This permit is for air pollution control purposes only. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.1.D.)
2. Any activities not identified in the application are not authorized by this permit. (Ref.: Miss. Code Ann. 49-17-29 1.b)
3. The knowing submittal of a permit application with false information may serve as the basis for the Permit Board to void the permit issued pursuant thereto or subject the applicant to penalties for operating without a valid permit pursuant to State Law. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(5).)
4. It is the responsibility of the applicant/permittee to obtain all other approvals, permits, clearances, easements, agreements, etc., which may be required including, but not limited to, all required local government zoning approvals or permits. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.1.D(6).)
5. The issuance of a permit does not release the permittee from liability for constructing or operating air emissions equipment in violation of any applicable statute, rule, or regulation of state or federal environmental authorities. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(7).)
6. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit, unless halting or reducing activity would create an imminent and substantial endangerment threatening the public health and safety of the lives and property of the people of this state. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(15)(a).)
7. The permit and/or any part thereof may be modified, revoked, reopened, and reissued, or terminated for cause. Sufficient cause for a permit to be reopened shall exist when an air emissions stationary source becomes subject to Title V. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(15)(b).)
8. The permit does not convey any property rights of any sort, or any exclusive privilege. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(15)(c).)
9. The permittee shall furnish to the DEQ within a reasonable time any information the DEQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the DEQ copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee shall furnish such records to the DEQ along with a claim of confidentiality. The permittee may furnish such

records directly to the Administrator along with a claim of confidentiality. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(15)(d).)

10. Design and Construction Requirements: The stationary source shall be designed and constructed so as to operate without causing a violation of an Applicable Rules and Regulations, without interfering with the attainment and maintenance of State and National Ambient Air Quality Standards, and such that the emission of air toxics does not result in an ambient concentration sufficient to adversely affect human health and well-being or unreasonably and adversely affect plant or animal life beyond the stationary source boundaries. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.A.)
11. Solids Removal: The necessary facilities shall be constructed so that solids removed in the course of control of air emissions may be disposed of in a manner such as to prevent the solids from becoming windborne and to prevent the materials from entering State waters without the proper environmental permits. (Ref.: Miss. Code Ann. 49-17-29)
12. Diversion and Bypass of Air Pollution Controls: The air pollution control facilities shall be constructed such that diversion from or bypass of collection and control facilities is not needed except as provided for in 11 Miss. Admin. Code Pt. 2, R. 1.10., "Air Emission Regulations for the Prevention, Abatement, and Control of Air Contaminants", Section 10. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.10.)
13. Fugitive Dust Emissions from Construction Activities: The construction of the stationary source shall be performed in such a manner so as to reduce fugitive dust emissions from construction activities to a minimum. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.A(4).)
14. Right of Entry: The permittee shall allow the Mississippi Department of Environmental Quality Office of Pollution Control and the Mississippi Environmental Quality Permit Board and/or their representatives upon presentation of credentials:
 - a) To enter upon the permittee's premises where an air emission source is located or in which any records are required to be kept under the terms and conditions of this permit; and
 - b) At reasonable times to have access to and copy any records required to be kept under the terms and conditions of this permit; to inspect any monitoring equipment or monitoring method required in this permit; and to sample any air emissions. (Ref.: Miss. Code Ann. 49-17-21)
15. Permit Modification or Revocation: After notice and opportunity for a hearing, the Permit Board may modify the permit or revoke it in whole or in part for good cause shown including, but not limited to:
 - a) Persistent violation of any of the terms or conditions of this permit;

- b) Obtaining this permit by misrepresentation or failure to disclose fully all relevant facts;
or
- c) A change in federal, state, or local laws or regulations that require either a temporary or permanent reduction or elimination of previously authorized air emission.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.C.)

16. Public Record and Confidential Information: Except for data determined to be confidential under the Mississippi Air & Water Pollution Control Law, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the offices of the Mississippi Department of Environmental Quality, Office of Pollution Control. (Ref.: Miss. Code Ann. 49-17-39)
17. Permit Transfer: This permit shall not be transferred except upon approval of the Permit Board. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.16.B)
18. Severability: The provisions of this permit are severable. If any provision of the permit, or the application of any provision of the permit to any circumstances, is challenged or held invalid, the validity of the remaining permit provisions and/or portions thereof or their application to other persons or sets of circumstances, shall not be affected thereby. (Ref. 11 Miss. Admin. Code Pt. 2, R. 2.1.D(7).)
19. Permit Expiration: The permit to construct will expire if construction does not begin within eighteen (18) months from the date of issuance or if construction is suspended for eighteen (18) months or more. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.C(1).)
20. Certification of Construction: A new stationary source issued a Permit to Construct cannot begin operation until certification of construction by the permittee. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.D(3).)
21. Beginning Operation: Except as prohibited in Part I, Condition 24 of this permit, after certification of construction by the permittee, the Permit to Construct shall be deemed to satisfy the requirement for a permit to operate until the date the application for issuance or modification of the Title V Permit or the application for issuance or modification of the State Permit to Operate, whichever is applicable, is due. This provision is not applicable to a source excluded from the requirement for a permit to operate as provided by 11 Miss. Admin. Code Pt. 2, R. 2.13.G. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.D(4).)
22. Application for a Permit to Operate: Except as otherwise specified in Part I, Condition 24 of this permit, the application for issuance or modification of the State Permit to Operate or the Title V Permit, whichever is applicable, is due twelve (12) months after beginning operation or such earlier date or time as specified in the Permit to Construct. The Permit Board may specify an earlier date or time for submittal of the application. Beginning operation will be assumed to occur upon certification of construction, unless the permittee specifies differently in writing. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.D(5).)

23. **Operating Under a Permit to Construct:** Except as otherwise specified in Part I, Condition 24 of this permit, upon submittal of a timely and complete application for issuance or modification of a State Permit to Operate or a Title V Permit, whichever is applicable, the applicant may continue to operate under the terms and conditions of the Permit to Construct and in compliance with the submitted application until the Permit Board issues, modifies, or denies the Permit to Operate. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.D(6).)
24. **Application Requirements for a Permit to Operate for Moderate Modifications:** For moderate modifications that require contemporaneous enforceable emissions reductions from more than one emission point in order to “net” out of PSD/NSR, the applicable Title V Permit to Operate or State Permit to Operate must be modified prior to beginning operation of the modified facilities. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.D(7).)
25. **Compliance Testing:** Regarding compliance testing:
- a) The results of any emissions sampling and analysis shall be expressed both in units consistent with the standards set forth in any Applicable Rules and Regulations or this permit and in units of mass per time.
 - b) Compliance testing will be performed at the expense of the permittee.
 - c) Each emission sampling and analysis report shall include but not be limited to the following:
 - (1) detailed description of testing procedures;
 - (2) sample calculation(s);
 - (3) results; and
 - (4) comparison of results to all Applicable Rules and Regulations and to emission limitations in the permit.
- (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.6.B(3), (4), and (6).)

B. GENERAL NOTIFICATION REQUIREMENTS

1. Within fifteen (15) days of beginning actual construction, the permittee must notify DEQ in writing that construction has begun. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.C(2).)
2. The permittee must notify DEQ in writing when construction does not begin within eighteen (18) months of issuance or if construction is suspended for eighteen (18) months or more. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.C(3).)
3. Upon the completion of construction or installation of an approved stationary source or modification, the applicant shall notify the Permit Board that construction or installation was

performed in accordance with the approved plans and specifications on file with the Permit Board. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.D(1).)

4. The Permit Board shall be promptly notified in writing of any change in construction from the previously approved plans and specifications or permit. If the Permit Board determines the changes are substantial, it may require the submission of a new application to construct with “as built” plans and specifications. Notwithstanding any provision herein to the contrary, the acceptance of an “as built” application shall not constitute a waiver of the right to seek compliance penalties pursuant to State Law. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.5.D(2).)

Part II.
EMISSION LIMITATIONS AND MONITORING REQUIREMENTS

Beginning May 1, 2014, the permittee is authorized to construct air emissions equipment for the emission of air contaminants from Emission Point AA-003a, the 15.0 MMBTU/Hr natural gas fired Lime Injection Burner.

The air emissions equipment shall be constructed to comply with the emission limitations and monitoring requirements specified below.

EMISSION LIMITATIONS

Particulate Matter The maximum permissible emission of ash and/or particulate matter from fossil fuel burning installations equal to or greater than 10 million BTU per hour heat input but less than 10,000 million BTU per hour heat input shall not exceed an emission rate as determined by the relationship

$$E = 0.8808 * I^{-0.1667}$$

where E is the emission rate in pounds per million BTU per hour heat input and I is the heat input in millions of BTU per hour. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(b).)

Sulfur Dioxide The maximum discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide) per million BTU heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).)

Opacity 10% as determined by EPA Test Method 9, 40 CFR 60, Appendix A. (Ref.: 11 Miss. Admin. Code Pt.2, R. 2.2.B(10).)

Natural Gas The permittee shall combust natural gas only. (Ref.: 11 Miss. Admin. Code Pt.2, R. 2.2.B(10).)

MONITORING/RECORDKEEPING AND REPORTING REQUIREMENTS

In addition to 40 CFR 52.21(r)(6) as described in “other requirements”, the permittee shall monitor and keep records of the natural gas combusted by utilizing energy records, reports, and any other data necessary to determine and provide the emission rate of all NSR pollutants emitted by the modification/addition of this emission point and provide this information to the MDEQ semi-annually until such time that the Title V Operating Permit has been modified to reflect this emission point modification/addition as determined by I.A.22. (Ref.: 11 Miss. Admin. Code Pt.2, R. 2.2.B(10).)

OTHER REQUIREMENTS

In accordance with 40 CFR 52.21(r)(6), the permittee shall before beginning actual construction of the project, document and maintain a record of the following information:

- a) A description of the project;
- b) Identification of the emissions unit(s) whose emissions of a regulated NSR pollutant could be affected by the project; and
- c) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including the baseline actual emissions, the projected actual emissions, the amount of emissions excluded under paragraph (b)(41)(ii)(c) of this section and an explanation for why such amount was excluded, and any netting calculations, if applicable.

The permittee shall also monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any emissions unit identified in paragraph (r)(6)(i)(b) of this section; and calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of 5 years following resumption of regular operations after the change, or for a period of 10 years following resumption of regular operations after the change if the project increases the design capacity or potential to emit that regulated NSR pollutant at such emissions unit.

(Ref.: 40 CFR 52.52(r)(6)(i) and (iii))

Part II.
EMISSION LIMITATIONS AND MONITORING REQUIREMENTS

Beginning May 1, 2014, the permittee is authorized to construct air emissions equipment for the emission of air contaminants from Emission Point AA-003b, the 15.0 MMBTU/Hr natural gas fired Lime Injection Burner.

The air emissions equipment shall be constructed to comply with the emission limitations and monitoring requirements specified below.

EMISSION LIMITATIONS

Particulate Matter Particulate Matter The maximum permissible emission of ash and/or particulate matter from fossil fuel burning installations equal to or greater than 10 million BTU per hour heat input but less than 10,000 million BTU per hour heat input shall not exceed an emission rate as determined by the relationship

$$E = 0.8808 * I^{-0.1667}$$

where E is the emission rate in pounds per million BTU per hour heat input and I is the heat input in millions of BTU per hour. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(b).)

Sulfur Dioxide The maximum discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide) per million BTU heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).)

Opacity 10% as determined by EPA Test Method 9, 40 CFR 60, Appendix A. (Ref.: 11 Miss. Admin. Code Pt.2, R. 2.2.B(10).)

Natural Gas The permittee shall combust natural gas only. (Ref.: 11 Miss. Admin. Code Pt.2, R. 2.2.B(10).)

MONITORING AND RECORDKEEPING REQUIREMENTS

In addition to 40 CFR 52.21(r)(6) as described in “other requirements”, the permittee shall monitor and keep records of the natural gas combusted by utilizing energy records, reports, and any other data necessary to determine and provide the emission rate of all NSR pollutants emitted by the modification/addition of this emission point and provide this information to the MDEQ semi-annually until such time that the Title V Operating Permit has been modified to reflect this emission point modification/addition as determined by I.A.22. (Ref.: 11 Miss. Admin. Code Pt.2, R. 2.2.B(10).)

OTHER REQUIREMENTS

In accordance with 40 CFR 52.21(r)(6), the permittee shall before beginning actual construction of the project, document and maintain a record of the following information:

- a) A description of the project;
- b) Identification of the emissions unit(s) whose emissions of a regulated NSR pollutant could be affected by the project; and
- c) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including the baseline actual emissions, the projected actual emissions, the amount of emissions excluded under paragraph (b)(41)(ii)(c) of this section and an explanation for why such amount was excluded, and any netting calculations, if applicable.

The permittee shall also monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any emissions unit identified in paragraph (r)(6)(i)(b) of this section; and calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of 5 years following resumption of regular operations after the change, or for a period of 10 years following resumption of regular operations after the change if the project increases the design capacity or potential to emit that regulated NSR pollutant at such emissions unit.

(Ref.: 40 CFR 52.52(r)(6)(i) and (iii))

Part II.
EMISSION LIMITATIONS AND MONITORING REQUIREMENTS

Beginning May 1, 2014, the permittee is authorized to construct air emissions equipment for the emission of air contaminants from Emission Point AA-006a, the 15.0 MMBTU/Hr natural gas fired portable Ladle Heater.

The air emissions equipment shall be constructed to comply with the emission limitations and monitoring requirements specified below.

EMISSION LIMITATIONS

Particulate Matter The maximum permissible emission of ash and/or particulate matter from fossil fuel burning installations equal to or greater than 10 million BTU per hour heat input but less than 10,000 million BTU per hour heat input shall not exceed an emission rate as determined by the relationship

$$E = 0.8808 * I^{-0.1667}$$

where E is the emission rate in pounds per million BTU per hour heat input and I is the heat input in millions of BTU per hour. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(b).)

Sulfur Dioxide The maximum discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide) per million BTU heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).)

Opacity 10% as determined by EPA Test Method 9, 40 CFR 60, Appendix A. (Ref.: 11 Miss. Admin. Code Pt.2, R. 2.2.B(10).)

Natural Gas The permittee shall combust natural gas only. (Ref.: 11 Miss. Admin. Code Pt.2, R. 2.2.B(10).)

MONITORING AND RECORDKEEPING REQUIREMENTS

In addition to 40 CFR 52.21(r)(6) as described in “other requirements”, the permittee shall monitor and keep records of the natural gas combusted by utilizing energy records, reports, and any other data necessary to determine and provide the emission rate of all NSR pollutants emitted by the modification/addition of this emission point and provide this information to the MDEQ semi-annually until such time that the Title V Operating Permit has been modified to reflect this emission point modification/addition as determined by I.A.22. (Ref.: 11 Miss. Admin. Code Pt.2, R. 2.2.B(10).)

OTHER REQUIREMENTS

In accordance with 40 CFR 52.21(r)(6), the permittee shall before beginning actual construction of the project, document and maintain a record of the following information:

- a) A description of the project;
- b) Identification of the emissions unit(s) whose emissions of a regulated NSR pollutant could be affected by the project; and
- c) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including the baseline actual emissions, the projected actual emissions, the amount of emissions excluded under paragraph (b)(41)(ii)(c) of this section and an explanation for why such amount was excluded, and any netting calculations, if applicable.

The permittee shall also monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any emissions unit identified in paragraph (r)(6)(i)(b) of this section; and calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of 5 years following resumption of regular operations after the change, or for a period of 10 years following resumption of regular operations after the change if the project increases the design capacity or potential to emit that regulated NSR pollutant at such emissions unit.

(Ref.: 40 CFR 52.52(r)(6)(i) and (iii))