# STATE OF MISSISSIPPI AIR POLLUTION CONTROL TITLE V PERMIT

TO OPERATE AIR EMISSIONS EQUIPMENT

# THIS CERTIFIES THAT

Brookhaven Pellets, LLC 912 WL Behan Road Brookhaven, Mississippi Lincoln County

has been granted permission to operate air emissions equipment in accordance with emission limitations, monitoring requirements and conditions set forth herein. This permit is issued in accordance with Title V of the Federal Clean Air Act (42 U.S.C.A. § 7401 - 7671) and the provisions of the Mississippi Air and Water Pollution Control Law (Section 49-17-1 et. seq., Mississippi Code of 1972), and the regulations and standards adopted and promulgated thereunder.

# MISSISSIPPI ENVIRONMENTAL QUALITY PERMIT BOARD

Becky Simonson

AUTHORIZED SIGNATURE
MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Permit Issued: July 29, 2024

Modified Date: February 3, 2025

Effective Date: As specified herein.

Expires: June 30, 2029 Permit No.: 1620-00057

77141 PER20230001

# **TABLE OF CONTENTS**

SECTION 1.	GENERAL CONDITIONS	3
SECTION 2.	EMISSION POINTS & POLLUTION CONTROL DEVICES	14
SECTION 3.	EMISSION LIMITATIONS & STANDARDS	15
SECTION 4.	COMPLIANCE SCHEDULE	20
SECTION 5.	MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS	21
SECTION 6.	ALTERNATIVE OPERATING SCENARIOS	32
SECTION 7.	TITLE VI REQUIREMENTS	33

# APPENDIX A LIST OF ABBREVIATIONS USED IN THIS PERMIT

#### SECTION 1. GENERAL CONDITIONS

1.1 The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the Federal Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(a).)

1.2 It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(b).)

1.3 This permit and/or any part thereof may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(c).)

- 1.4 Prior to its expiration, this permit may be reopened in accordance with the provisions listed below.
  - (a) This permit shall be reopened and revised under any of the following circumstances:
    - (1) Additional applicable requirements under the Federal Act become applicable to a major Title V source with a remaining permit term of 3 or more years. Such a reopening shall be completed no later than 18 months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended.
    - (2) Additional requirements (including excess emissions requirements) become applicable to an affected source under the acid rain program. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit.
    - (3) The Permit Board or EPA determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emission standards or other terms or conditions of the permit.

- (4) The Administrator or the Permit Board determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
- (b) Proceedings to reopen and issue this permit shall follow the same procedures as apply to initial permit issuance and shall only affect those parts of the permit for which cause to reopen exists. Such reopening shall be made as expeditiously as practicable.
- (c) Reopenings shall not be initiated before a notice of such intent is provided to the Title V source by the DEQ at least 30 days in advance of the date that the permit is to be reopened, except that the Permit Board may provide a shorter time period in the case of an emergency.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.G.)

1.5 The permittee shall furnish to the DEQ within a reasonable time any information the DEQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the DEQ copies of records required to be kept by the permittee or, for information to be confidential, the permittee shall furnish such records to DEQ along with a claim of confidentiality. The permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(e).)

1.6 This permit does not convey any property rights of any sort, or any exclusive privilege.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(d).)

1.7 The provisions of this permit are severable. If any provision of this permit, or the application of any provision of this permit to any circumstances, is challenged or held invalid, the validity of the remaining permit provisions and/or portions thereof or their application to other persons or sets of circumstances, shall not be affected thereby.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(5).)

- 1.8 The permittee shall pay to the DEQ an annual permit fee. The amount of fee shall be determined each year based on the provisions of regulated pollutants for fee purposes and the fee schedule specified in the Commission on Environmental Quality's order which shall be issued in accordance with the procedure outlined in Regulation 11 Miss. Admin. Code Pt. 2, Ch. 6.
  - (a) For purposes of fee assessment and collection, the permittee shall elect for actual or allowable emissions to be used in determining the annual quantity of emissions unless the Commission determines by order that the method chosen by the applicant for calculating actual emissions fails to reasonably represent actual emissions. Actual emissions shall be calculated using emission monitoring data or direct

emissions measurements for the pollutant(s); mass balance calculations such as the amounts of the pollutant(s) entering and leaving process equipment and where mass balance calculations can be supported by direct measurement of process parameters, such direct measurement data shall be supplied; published emission factors such as those relating release quantities to throughput or equipment type (e.g., air emission factors); or other approaches such as engineering calculations (e.g., estimating volatilization using published mathematical formulas) or best engineering judgments where such judgments are derived from process and/or emission data which supports the estimates of maximum actual emission.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.A(2).)

(b) If the Commission determines that there is not sufficient information available on a facility's emissions, the determination of the fee shall be based upon the permitted allowable emissions until such time as an adequate determination of actual emissions is made. Such determination may be made anytime within one year of the submittal of actual emissions data by the permittee.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.A(2).)

(c) If at any time within the year the Commission determines that the information submitted by the permittee on actual emissions is insufficient or incorrect, the permittee will be notified of the deficiencies and the adjusted fee schedule. Past due fees from the adjusted fee schedule will be paid on the next scheduled quarterly payment time.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.D(2).)

(d) The fee shall be due September 1 of each year. By July 1 of each year, the permittee shall submit an inventory of emissions for the previous year on which the fee is to be assessed. The permittee may elect a quarterly payment method of four (4) equal payments; notification of the election of quarterly payments must be made to the DEQ by the first payment date of September 1. The permittee shall be liable for penalty as prescribed by State Law for failure to pay the fee or quarterly portion thereof by the date due.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.D.)

(e) If in disagreement with the calculation or applicability of the Title V permit fee, the permittee may petition the Commission in writing for a hearing in accordance with State Law. Any disputed portion of the fee for which a hearing has been requested will not incur any penalty or interest from and after the receipt by the Commission of the hearing petition.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.C.)

1.9 No permit revision shall be required under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes for changes that are provided for in this permit.

```
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(8).)
```

1.10 Any document required by this permit to be submitted to the DEQ shall contain a certification by a responsible official that states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

```
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.2.E.)
```

- 1.11 The permittee shall allow the DEQ, or an authorized representative, upon the presentation of credentials and other documents as may be required by law, to perform the following:
  - (a) enter upon the permittee's premises where a Title V source is located or emissionsrelated activity is conducted, or where records must be kept under the conditions of this permit;
  - (b) have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
  - (c) inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
  - (d) as authorized by the Federal Act, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements.

```
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.C(2).)
```

1.12 Except as otherwise specified or limited herein, the permittee shall have necessary sampling ports and ease of accessibility for any new air pollution control equipment, obtained after May 8, 1970, and vented to the atmosphere.

```
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.I(1).)
```

1.13 Except as otherwise specified or limited herein, the permittee shall provide the necessary sampling ports and ease of accessibility when deemed necessary by the Permit Board for air pollution control equipment that was in existence prior to May 8, 1970.

```
(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.I(2).)
```

1.14 Compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance where such applicable requirements are included and are specifically identified in the permit or where the permit contains a determination, or summary thereof, by the Permit Board that requirements specifically identified previously are not applicable to the source.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.F(1).)

- 1.15 Nothing in this permit shall alter or affect the following:
  - (a) the provisions of Section 303 of the Federal Act (emergency orders), including the authority of the Administrator under that section;
  - (b) the liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;
  - (c) the applicable requirements of the acid rain program, consistent with Section 408(a) of the Federal Act.
  - (d) the ability of EPA to obtain information from a source pursuant to Section 114 of the Federal Act.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.F(2).)

1.16 The permittee shall comply with the requirement to register a Risk Management Plan if permittee's facility is required pursuant to Section 112(r) of the Act to register such a plan.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.H.)

1.17 Expiration of this permit terminates the permittee's right to operate unless a timely and complete renewal application has been submitted. A timely application is one which is submitted at least six (6) months prior to expiration of the Title V permit. If the permittee submits a timely and complete application, the failure to have a Title V permit is not a violation of regulations until the Permit Board takes final action on the permit application. This protection shall cease to apply if, subsequent to the completeness determination, the permittee fails to submit by the deadline specified in writing by the DEQ any additional information identified as being needed to process the application.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.C(2)., R. 6.4.B., and R. 6.2.A(1)(c).)

- 1.18 The permittee is authorized to make changes within their facility without requiring a permit revision (ref: Section 502(b)(10) of the Act) if:
  - (a) the changes are not modifications under any provision of Title I of the Act;
  - (b) the changes do not exceed the emissions allowable under this permit;

- (c) the permittee provides the Administrator and the Department with written notification in advance of the proposed changes (at least seven (7) days, or such other time frame as provided in other regulations for emergencies) and the notification includes:
  - (1) a brief description of the change(s),
  - (2) the date on which the change will occur,
  - (3) any change in emissions, and
  - (4) any permit term or condition that is no longer applicable as a result of the change;
- (d) the permit shield shall not apply to any Section 502(b)(10) change.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.F(1).)

1.19 Should the Executive Director of the Mississippi Department of Environmental Quality declare an Air Pollution Emergency Episode, the permittee will be required to operate in accordance with the permittee's previously approved Emissions Reduction Schedule or, in the absence of an approved schedule, with the appropriate requirements specified in 11 Miss. Admin. Code Pt. 2, Ch. 3., "Regulations for the Prevention of Air Pollution Emergency Episodes" for the level of emergency declared.

(Ref.: 11 Miss. Admin. Code Pt. 2, Ch. 3.)

- Except as otherwise provided herein, a modification of the facility may require a Permit to Construct in accordance with the provisions of Regulations 11 Miss. Admin. Code Pt. 2, Ch. 2., "Permit Regulations for the Construction and/or Operation of Air Emissions Equipment," and may require modification of this permit in accordance with Regulations 11 Miss. Admin. Code Pt. 2, Ch. 6., "Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act." Modification is defined as [a]ny physical change in or change in the method of operation of a facility which increases the actual emissions or the potential uncontrolled emissions of any air pollutant subject to regulation under the Federal Act emitted into the atmosphere by that facility or which results in the emission of any air pollutant subject to regulation under the Federal Act into the atmosphere not previously emitted. A physical change or change in the method of operation shall not include:
  - (a) routine maintenance, repair, and replacement;
  - (b) use of an alternative fuel or raw material by reason of an order under Sections 2 (a) and (b) of the Federal Energy Supply and Environmental Coordination Act of 1974

- (or any superseding legislation) or by reason of a natural gas curtailment plan pursuant to the Federal Power Act;
- (c) use of an alternative fuel by reason of an order or rule under Section 125 of the Federal Act;
- (d) use of an alternative fuel or raw material by a stationary source which:
  - (1) the source was capable of accommodating before January 6, 1975, unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR 51, Subpart I, or 40 CFR 51.166; or
  - (2) the source is approved to use under any permit issued under 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Part 51, Subpart I, or 40 CFR 51.166;
- (e) an increase in the hours of operation or in the production rate unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Subpart I or 40 CFR 51.166; or
- (f) any change in ownership of the stationary source.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.1.C(15).)

1.21 Any change in ownership or operational control must be approved by the Permit Board.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.D(4).)

1.22 This permit is a Federally approved operating permit under Title V of the Federal Clean Air Act as amended in 1990. All terms and conditions, including any designed to limit the source's potential to emit, are enforceable by the Administrator and citizens under the Federal Act as well as the Commission.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.B(1).)

1.23 Except as otherwise specified or limited herein, the open burning of residential, commercial, institutional, or industrial solid waste, is prohibited. This prohibition does not apply to infrequent burning of agricultural wastes in the field, silvicultural wastes for forest management purposes, land-clearing debris, debris from emergency clean-up operations, and ordnance. Open burning of land-clearing debris must not use starter or auxiliary fuels which cause excessive smoke (rubber tires, plastics, etc.); must not be performed if prohibited by local ordinances; must not cause a traffic hazard; must not

take place where there is a High Fire Danger Alert declared by the Mississippi Forestry Commission or Emergency Air Pollution Episode Alert imposed by the Executive Director and must meet the following buffer zones.

- (a) Open burning without a forced-draft air system must not occur within 500 yards of an occupied dwelling.
- (b) Open burning utilizing a forced-draft air system on all fires to improve the combustion rate and reduce smoke may be done within 500 yards of but not within 50 yards of an occupied dwelling.
- (c) Burning must not occur within 500 yards of commercial airport property, private airfields, or marked off-runway aircraft approach corridors unless written approval to conduct burning is secured from the proper airport authority, owner or operator.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.G.)

- 1.24 Except as otherwise specified herein, the permittee shall be subject to the following provision with respect to emergencies:
  - (a) Except as otherwise specified herein, an "emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.
  - (b) An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions specified in (c) following are met.
  - (c) The affirmative defense of emergency shall be demonstrated through properly signed contemporaneous operating logs, or other relevant evidence that include information as follows:
    - (1) an emergency occurred and that the permittee can identify the cause(s) of the emergency;
    - (2) the permitted facility was at the time being properly operated;
    - (3) during the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements in the permit; and

- (4) the permittee submitted notice of the emergency to the DEQ within 2 working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.
- (d) In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (e) This provision is in addition to any emergency or upset provision contained in any applicable requirement specified elsewhere herein.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.G.)

- Except as otherwise specified herein, the permittee shall be subject to the following provisions with respect to upsets, startups, and shutdowns.
  - (a) Upsets (as defined in 11 Miss. Admin. Code Pt. 2, R. 1.2.)
    - (1) For an upset, the Commission may pursue an enforcement action for noncompliance with an emission standard or other requirement of an applicable rule, regulation, or permit. In determining whether to pursue enforcement action, and/or the appropriate enforcement action to take, the Commission may consider whether the source has demonstrated through properly signed contemporaneous operating logs or other relevant evidence the following:
      - (i) An upset occurred and that the source can identify the cause(s) of the upset;
      - (ii) The source was at the time being properly operated;
      - (iii) During the upset the source took all reasonable steps to minimize levels of emissions that exceeded the emission standard or other requirement of an applicable rule, regulation, or permit;
      - (iv) That within 5 working days of the time the upset began, the source submitted a written report to the Department describing the upset, the steps taken to mitigate excess emissions or any other noncompliance, and the corrective actions taken and;
      - (v) That as soon as practicable but no later than 24 hours of becoming aware of an upset that caused an immediate adverse impact to human health or the environment beyond the source boundary or caused a general nuisance to the public, the source provided notification to the Department.

- (2) In any enforcement proceeding by the Commission, the source seeking to establish the occurrence of an upset has the burden of proof.
- (3) This provision is in addition to any upset provision contained in any applicable requirement.
- (4) These upset provisions apply only to enforcement actions by the Commission and are not intended to prohibit EPA or third party enforcement actions.
- (b) Startups and Shutdowns (as defined in 11 Miss. Admin. Code Pt. 2, R. 1.2.)
  - (1) Startups and shutdowns are part of normal source operation. Emission limitations apply during startups and shutdowns unless source specific emission limitations or work practice standards for startups and shutdowns are defined by an applicable rule, regulation, or permit.
  - (2) Where the source is unable to comply with existing emission limitations established under the State Implementation Plan (SIP) and defined in this regulation, 11 Mississippi Administrative Code, Part 2, Chapter 1, the Department will consider establishing source specific emission limitations or work practice standards for startups and shutdowns. Source specific emission limitations or work practice standards established for startups and shutdowns are subject to the requirements prescribed in 11 Miss. Admin. Code Pt. 2, R. 1.10.B(2)(a) through (e).
  - (3) Where an upset as defined in Rule 1.2 occurs during startup or shutdown, see the upset requirements above.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.10.)

1.26 The permittee shall comply with all applicable standards for demolition and renovation activities pursuant to the requirements of 40 CFR Part 61, Subpart M, as adopted by reference in Regulation 11 Miss Admin. Code Pt. 2, R. 1.8. The permittee shall not be required to obtain a modification of this permit in order to perform the referenced activities.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.8.)

- 1.27 Regarding compliance testing (if applicable):
  - (a) The results of any emissions sampling and analysis shall be expressed both in units consistent with the standards set forth in any Applicable Rules and Regulations or this permit and in units of mass per time.
  - (b) Compliance testing will be performed at the expense of the permittee.

- (c) Each emission sampling and analysis report shall include (but not be limited to) the following:
  - (1) Detailed description of testing procedures;
  - (2) Sample calculation(s);
  - (3) Results; and
  - (4) Comparison of results to all Applicable Rules and Regulations and to emission limitations in the permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.6.B.(3), (4), and (6).)

# SECTION 2. EMISSION POINTS & POLLUTION CONTROL DEVICES

<b>Emission Point</b>	Description		
AA-100	Facility-Wide (Brookhaven Pellets, LLC)		
AA-001	Pre-Dried Raw Material Handling [emissions controlled by maintaining negative pressure in the dump area and routing emissions to a cartridge filter]		
AA-002a	Dry Hammermill No. 1 [emissions routed to a baghouse]		
AA-002b	Dry Hammermill No. 2 [emissions routed to a baghouse]		
AA-003a	Pelletizer / Pellet Cooler No. 1 [emissions routed to a high-efficiency cyclone]		
AA-003b	Pelletizer / Pellet Cooler No. 2 [emissions routed to a high-efficiency cyclone]		
AA-004	Pellet Storage Silo		
AA-006	Finished Pellet Truck Loading		
AA-007	Crop Dryer System [equipped with a 2.2 MMBTU / hr propane burner]		

#### SECTION 3. EMISSION LIMITATIONS & STANDARDS

- A. Facility-Wide Emission Limitations & Standards
- 3.A.1 Except as otherwise specified or limited herein, the permittee shall not cause, permit, or allow the emission of smoke from a point source into the open air from any manufacturing, industrial, commercial or waste disposal process which exceeds forty (40) percent opacity subject to the exceptions provided in (a) & (b).
  - (a) Startup operations may produce emissions which exceed 40% opacity for up to fifteen (15) minutes per startup in any one hour and not to exceed three (3) startups per stack in any twenty-four (24) hour period.
  - (b) Emissions resulting from soot blowing operations shall be permitted provided such emissions do not exceed 60 percent opacity, and provided further that the aggregate duration of such emissions during any twenty-four (24) hour period does not exceed ten (10) minutes per billion BTU gross heating value of fuel in any one hour.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.A.)

3.A.2 Except as otherwise specified or limited herein, the permittee shall not cause, allow, or permit the discharge into the ambient air from any point source or emissions, any air contaminant of such opacity as to obscure an observer's view to a degree in excess of 40% opacity, equivalent to that provided in Condition 3.A.1. This shall not apply to vision obscuration caused by uncombined water droplets.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.B.)

- 3.A.3 For the entire facility, the permittee shall not cause, permit, or allow the emission of particles or any contaminants in sufficient amounts or of such duration from any process as to be injurious to humans, animals, plants, or property, or to be a public nuisance, or create a condition of air pollution.
  - (a) The permittee shall not cause or permit the handling, transporting, or storage of any material in a manner which allows or may allow unnecessary amounts of particulate matter to become airborne.
  - (b) When dust, fumes, gases, mist, odorous matter, vapors, or any combination thereof escape from a building or equipment in such a manner and amount as to cause a nuisance to property other than that from which it originated or to violate any other provision of 11 Miss. Admin. Code Pt. 2, Ch. 1, the Commission may order such corrected in a way that all air and gases or air and gasborne material leaving the building or equipment are controlled or removed prior to discharge to the open air.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.C.)

#### B. Emission Point Specific Emission Limitations & Standards

Emission Point(s)	Applicable Requirement	Condition Number(s)	Pollutant/ Parameter	Limit/Standard
AA-100 (Facility- Wide)	11 Miss. Admin. Code Pt. 2, R. 1.3.F(1).	3.B.1	PM (filterable)	$E = 4.1 \cdot (p^{0.67})$
	11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).	3.B.2	HAPs	9.0 tpy (Individual) 24.0 tpy (Total) (Rolling 12-Month Totals)
	11 Miss. Admin. Code Pt. 2, R. 2.2.B(10). as established in the Permit to Construct issued October 27, 2020 (PSD Avoidance Limit)	3.B.3	VOCs	245.0 tpy (Rolling 12-Month Total)
AA-001	11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).	3.B.4	PM (filterable)	Operational Requirement
AA-007	11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(a).	3.B.5	PM (filterable)	0.6 lbs. / MMBTU
	11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).	3.B.6	$SO_2$	4.8 lbs. / MMBTU Heat Input

3.B.1 For Emission Point AA-100 (Facility-Wide), except as otherwise specified herein, the permittee shall not cause or allow the emission of particulate matter (PM) in total quantities in any one (1) hour from any manufacturing process (which includes any associated stacks, vents, outlets, or combinations thereof) to exceed the amount determined by the relationship:

$$E = 4.1 \cdot (p^{0.67})$$

Where "E" is the emission rate in pounds per hour and "p" is the process weight input rate in tons per hour. Conveyer discharge of coarse solid matter may be allowed if no nuisance is created beyond the property boundary where the discharge occurs.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.F(1).)

3.B.2 For Emission Point AA-100 (Facility-Wide), the permittee shall limit the emission of each individual hazardous air pollutant (HAP) to no more than 9.0 tons per year (tpy) and all HAPs in total to no more than 24.0 tpy based on a rolling 12-month total.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).)

- 3.B.3 For Emission Point AA-100 (Facility-Wide), the permittee shall limit the total emission of volatile organic compounds (VOC) from all applicable sources to no more than 245.0 tpy based on a rolling 12-month total.
  - (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(10)., as established in the Permit to Construct issued October 27, 2020 PSD Avoidance Limit)
- 3.B.4 For Emission Point AA-001, the permittee shall at all times maintain negative pressure within in the "*truck dumping system*" at all times that the system is in operation. For any period in which negative pressure system is non-operational, the permittee shall cease operation of the "*truck dumping system*" until such time that the applicable control device returns to operational status.
  - (Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(10).)
- 3.B.5 For Emission Point AA-007, the maximum permissible emission of ash and/or particulate matter (PM filterable) from any fossil fuel burning installation of less than ten (10) MMBTU per hour heat input shall not exceed 0.6 pounds per MMBTU per hour heat input.
  - (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(a).)
- 3.B.6 For Emission Point AA-007, except as otherwise specified or limited herein, the maximum discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide or SO<sub>2</sub>) per million BTU heat input.
  - (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).)

# C. Insignificant and Trivial Activity Emission Limitations & Standards

Applicable Requirement	Condition Number(s)	Pollutant/ Parameter	Limit/Standard
11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(a).	3.C.1	PM	0.6 lbs/MMBTU
11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).	3.C.2	SO <sub>2</sub>	4.8 lbs/MMBTU

3.C.1 The maximum permissible emission of ash and/or particulate matter from fossil fuel burning installations of less than 10 million BTU per hour heat input shall not exceed 0.6 pounds per million BTU per hour heat input.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(a).)

3.C.2 The maximum discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide) per million BTU heat input.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).)

# D. Work Practice Standards

THIS SECTION WAS LEFT INTENTIONALLY BLANK AS THERE ARE NO APPLICABLE WORK PRACTICE STANDARDS.

#### SECTION 4. COMPLIANCE SCHEDULE

- 4.1 Unless otherwise specified herein, the permittee shall be in compliance with all requirements contained herein upon issuance of this permit.
- 4.2 Except as otherwise specified herein, the permittee shall submit to the Permit Board and to the Administrator of EPA Region IV a certification of compliance with permit terms and conditions, including emission limitations, standards, or work practices, by January 31 for the preceding calendar year. If the permit was reissued or modified during the course of the preceding calendar year, the compliance certification shall address each version of the permit. Each compliance certification shall include the following:
  - (a) the identification of each term or condition of the permit that is the basis of the certification;
  - (b) the compliance status;
  - (c) whether compliance was continuous or intermittent;
  - (d) the method(s) used for determining the compliance status of the source, currently and over the applicable reporting period;
  - (e) such other facts as may be specified as pertinent in specific conditions elsewhere in this permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.C(5)(a), (c), & (d).)

- 4.3 The permittee shall submit progress reports consistent with an applicable schedule of compliance and 11 Miss. Admin. Code Pt. 2, R. 6.2.C(8). semiannually, or at such other frequency as is specified in an applicable requirement or by the Permit Board. Such progress reports shall contain the following:
  - (a) dates for achieving the activities, milestone(s), or compliance required in the schedule of compliance, and dates when such activities, milestone(s) or compliance were achieved; and
  - (b) an explanation of why any dates in the schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.2.C(8).)

# SECTION 5. MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS

- A. General Monitoring, Recordkeeping and Reporting Requirements
- 5.A.1 The permittee shall install, maintain, and operate equipment and/or institute procedures as necessary to perform the monitoring and recordkeeping specified below.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3).)

- 5.A.2 In addition to the recordkeeping specified below, the permittee shall include with all records of required monitoring information the following:
  - (a) the date, place as defined in the permit, and time of sampling or measurements;
  - (b) the date(s) analyses were performed;
  - (c) the company or entity that performed the analyses;
  - (d) the analytical techniques or methods used;
  - (e) the results of such analyses; and
  - (f) the operating conditions existing at the time of sampling or measurement.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(b)(1).)

5.A.3 Except where a longer duration is specified in an applicable requirement, the permittee shall retain records of all required monitoring data and support information for a period of at least five (5) years from the date of the monitoring sample, measurement, report, or application. Support information includes all calibration and maintenance records, all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by the permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(b)(2).)

5.A.4 Except as otherwise specified herein, the permittee shall submit reports of any required monitoring by July 31 and January 31 for the preceding six-month period. All instances of deviations from permit requirements must be clearly identified in such reports and all required reports must be certified by a responsible official consistent with 11 Miss. Admin. Code Pt. 2, R. 6.2.E. For applicable periodic reporting requirements in 40 CFR Parts 60, 61, and 63, the permittee shall comply with the deadlines in this condition for reporting conducted on a semiannual basis. Additionally, any required quarterly reports shall be submitted by the end of the month following each calendar quarter (i.e., April

30th, July 31st, October 31st, and January 31st), and any required annual reports shall be submitted by January 31st following each calendar year.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c)(1)., 40 CFR 60.19(c), 61.10(g), and 63.10(a)(5))

5.A.5 Except as otherwise specified herein, the permittee shall report all deviations from permit requirements, including those attributable to upsets, the probable cause of such deviations, and any corrective actions or preventive measures taken. Said report shall be made within five (5) working days of the time the deviation began.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c)(2).)

5.A.6 Except as otherwise specified herein, the permittee shall perform emissions sampling and analysis in accordance with EPA Test Methods and with any continuous emission monitoring requirements, if applicable. All test methods shall be those versions or their equivalents approved by the DEQ and the EPA.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3).)

5.A.7 The permittee shall maintain records of any alterations, additions, or changes in equipment or operation.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3).)

5.A.8 Unless otherwise specified in Section 4, upon permit issuance, the monitoring, testing, recordkeeping, and reporting requirements of Section 5 herein supersede the requirements of any preceding permit to construct and/or operate.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3).)

# B. Specific Monitoring and Recordkeeping Requirements

Emission Point(s)	Applicable Requirement	Condition Number	Pollutant/ Parameter Monitored	Monitoring/Recordkeeping Requirement
AA-100 (Facility- Wide)	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).	5.B.1	PM / PM <sub>10</sub> / PM <sub>2.5</sub>	Implement and Maintain a Dust Management Plan
		5.B.2	VOCs	Calculate the Total Emission of Applicable Pollutants (Monthly and Rolling 12-Month Total)
		5.B.3	Moisture Content	Maintain Records of Moisture Content of Raw Material
		5.B.4	Dried Wood Chip Throughput	Monitor the Total Throughput (Monthly and Rolling 12-Month Total)
		5.B.5	Wood Pellet Production	Monitor Total Production (Monthly and Rolling 12-Month Total)
AA-001	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).	5.B.6	Negative Pressure	Evaluate Pressure System on Each Truck Dump
AA-001 AA-002a AA-002b AA-003a AA-003b	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).	5.B.7	Opacity	Perform Weekly Visible Emission Observations / Evaluations
		5.B.8	PM / PM <sub>10</sub> / PM <sub>2.5</sub>	Perform Weekly Inspections of Process Units
AA-002a AA-002b	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).	5.B.9	PM / PM <sub>10</sub> / PM <sub>2.5</sub>	Evaluate Pressure Drop on Each Baghouse Daily
AA-002a AA-002b AA-003a AA-003b	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).	5.B.10	VOCs HAPs	Routine Performance Testing
		5.B.11		Establish Site-Specific Emission Factors (As Applicable)

5.B.1 For Emission Point AA-100 (Facility-Wide), the permittee shall maintain and implement a "Dust Management Plan" (DMP) that details the procedures for routinely operating, evaluating and maintaining applicable emission sources to minimize the emission of fugitive particulate matter.

Additionally, the permittee shall maintain documentation that details the results of any inspection, evaluation, survey, or corrective / maintenance actions completed in accordance with the DMP. As deemed necessary, the permittee shall revise the DMP to

address changes to applicable operations and/or to incorporate additional best management practices.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

- 5.B.2 For Emission Point AA-100 (Facility-Wide), the permittee shall calculate and record the emission of volatile organic compounds (VOCs), each hazardous air pollutant (HAP), and all HAPs in total from all applicable emission sources in tons both on a monthly and rolling 12-month total basis in accordance with the following specifications:
  - (a) The permittee shall calculate and record emissions from the Dry Hammermills (AA-002a and AA-002b) and Pelletizer / Pellet Coolers (AA-003a and AA-003b) using collected production data, collected parametric monitoring data, and the established site-specific emission factors listed below:

Process Equipment	Pollutant	lb / ODT
Hammer Mill	VOC <sub>as propane</sub>	1.086
Pellet Cooler	VOC <sub>as propane</sub>	3.925

- (b) For all sources not otherwise specified, the permittee shall either assume actual emissions are equivalent to potential emissions or utilize actual data (e.g. throughput or fuel usage) to determine compliance with the emission limitations specified in Conditions 3.B.2 and 3.B.3.
- (c) Unless otherwise specified herein, the permittee shall maintain documentation that detail any reference data utilized to validate calculated emissions (operational data, applicable emission factors, engineering judgement determinations, performance test results, etc.).

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

5.B.3 For Emission Point AA-100 (Facility-Wide), the permittee shall maintain documentation that indicates the moisture content of the pre-dried wood material used for pellet production.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

5.B.4 For Emission Point AA-100 (Facility-Wide), the permittee shall monitor and record the total throughput of all wood chips dried within the dryers in oven-dried tons (ODT) on both a monthly and rolling 12-month total basis.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

5.B.5 For Emission Point AA-100 (Facility-Wide), the permittee shall monitor and record the total production of wood pellets in ODT both on a monthly and rolling 12-month total basis.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

5.B.6 For Emission Point AA-001, the permittee shall monitor and record the negative pressure in the "truck dumping system" (in inches of water) for each truck dump. If the monitored pressure is outside the recommended range for the negative pressure system, the permittee shall conduct and record any maintenance and/or repairs conducted to return the negative pressure system to optimal operating conditions.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

5.B.7 For Emission Points AA-001, AA-002a, AA-002b, AA-003a, and AA-003b, the permittee shall perform and record a weekly visible emission observation in accordance with EPA Test Method 22 on the exhaust of each source during daylight hours and during representative operating conditions. Each observation shall be performed for a minimum of six (6) consecutive minutes.

If visible emissions are detected during an observation, the permittee shall immediately perform a visible emissions evaluations (VEE) in accordance with EPA Test Method 9. However, in lieu of performing a VEE, the permittee may assume that the visual opacity of emissions from a source exceed the applicable limitation (i.e. Condition 3.A.1 or 3.A.2) and immediately implement corrective actions.

In the event that a VEE is required but cannot be conducted, the permittee shall record a written explanations as to why it was not possible to perform the VEE and shall conduct the VEE as soon as practicable.

The permittee shall maintain all documentation and information specified by Method 22 and/or Method 9, any corrective actions taken to prevent or minimize emissions as a result of the evaluation, and the date / time when each observation / evaluation was conducted.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

5.B.8 For Emission Points AA-001, AA-002a, AA-002b, AA-003a, AA-003a (Cyclone), AA-003b, and AA-003b (Cyclone), the permittee shall perform and record an inspection of each process unit weekly to note any required maintenance.

77141 PER20230001

If a problem is noted during an inspection, the permittee shall perform the maintenance necessary on the process unit to ensure operations are as originally designed. Additionally, the permittee shall maintain on-site sufficient components as is necessary to repair a process unit (to the extent practicable).

The permittee shall maintain documentation that details the date / time of each inspection, the results of each inspection, any problem that is experienced during an inspection, any maintenance (either corrective or preventative) performed to return a process unit to operation as originally designed, and the duration in which the process unit is non-operational due to malfunction.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

5.B.9 For Emission Point AA-002a and AA-002b, the permittee shall monitor and record the differential pressure drop across each baghouse daily (in inches of water) and compare to the corresponding manufacturer's recommended pressure drop range. If a monitored pressure drop is outside the recommended range for a baghouse, the permittee shall conduct and record any maintenance and/or repairs conducted to return the baghouse to optimal operating condition.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

- 5.B.10 For Emission Points AA-002a, AA-002b, AA-003a, and AA-003b, the permittee shall conduct routine performance testing on the exhaust of each source in accordance with the following requirements:
  - (a) The permittee shall conduct performance testing for VOCs biennially (every two years) and no later than twenty-five (25) months after the previously completed performance test.
  - (b) The permittee shall evaluate the emission of methanol, acetaldehyde, formaldehyde, acrolein, propionaldehyde, and phenol once in the life of this permit and no later than 180 days after issuance of this permit.
  - (c) All performance testing shall be conducted in accordance with either applicable U.S. EPA-approved test methods found in Appendix A of 40 CFR Part 60, Appendix M of 40 CFR Part 51, Appendix A of 40 CFR Part 63, or an alternative test method approved by the MDEQ and the U.S. EPA prior to the testing event.
  - (d) The permittee shall conduct a minimum of three (3) separate test runs for a performance stack test as specified in 40 CFR 63.7(e)(3), Subpart A.
  - (e) For Emission Points AA-002a and AA-002b, the permittee shall monitor and record the hourly throughput (in oven-dried tons) of wood chips processed in a hammermill during a performance test.

(f) For Emission Points AA-003a and AA-003b, the permittee shall monitor and record the hourly throughput (in oven-dried tons) of wood pellets produced in a pelletizer / pellet cooler during a performance test.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

- 5.B.11 For Emission Points AA-002a, AA-002b, AA-003a, and AA-003b, upon completing a performance test in accordance with Condition 5.B.10, the permittee shall utilize both the test results and applicable throughput data collected during the testing event to determine site-specific factors for HAP and VOC emissions from a process unit (as applicable) in pounds of respective pollutant per oven-dried tons (ODT). The permittee shall establish these emission factors in accordance with the following specifications:
  - (a) For Emission Points AA-002a and AA-002b, all site-specific emission factors shall be based on the pounds of pollutant per ODT of wood chips processed in a hammermill.
  - (b) For Emission Points AA-003a and AA-003b, all site-specific emission factors shall be based on the pounds of pollutant per ODT of wood pellets produced in a pelletizer.

If the results from any determination exceed a site-specific emission factor(s) already established, the permittee shall submit the new emission factor(s) in accordance with Condition 5.C.4. However, if the results are lower than the approved site-specific emission factor(s), the permittee may submit the new emission factor(s) in accordance with Condition 5.C.4.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2).)

# C. Specific Reporting Requirements

Emission Point(s)	Applicable Requirement	Condition Number	Pollutant/ Parameter Monitored	Reporting Requirement
	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c)(1).	5.C.1	VOCs	
			HAPs	
			Total Throughput of Wood Chips	
			Total Wood Pellet Production	
AA-100 (Facility-			Moisture Content	Submit a Semi-Annual Monitoring
Wide)			Negative Pressure System Maintenance	Report
			Baghouse / Cyclone Maintenance	
			Dust Management Plan	
AA-002a AA-002b AA-003a AA-003b	11 Miss. Admin. Code Pt. 2, R. 2.6.B(5).	5.C.2		Submit Performance Testing Protocol
				Submit 10-Day Notification of Performance Testing Event
	11 Miss. Admin. Code Pt. 2, R. 2.6.B(6) and R. 2.2.B(11).	5.C.3	VOCs	Submit the Performance Test Results
			HAPs	and Additional Information
	11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).	5.C.4		Submit Performance Test Results to EPA
		5.C.5		Submit Site-Specific Emission Factors for Review / Approval

- 5.C.1 For Emission Point AA-100 (Facility-Wide), the permittee shall submit a semi-annual monitoring report (SMR) in accordance with 5.A.4 that contains the following information:
  - (a) The emission of each individual HAP, all HAPs in total and VOCs from all applicable sources in tons on both a monthly and rolling 12-month total basis;
  - (b) The total throughput of wood chips in oven-dried tons (ODT) on both a monthly basis and a 12-month rolling total;

- (c) The total wood pellet production in oven-dried tons (ODT) on both a monthly basis and a 12-month rolling total;
- (d) The average moisture content of the pre-dried wood material used for pellet production;
- (e) For Emission Point AA-001, a summary detailing the date(s) and corresponding duration (in hours) in which the negative pressure system operates outside the recommended pressure range and any maintenance or repairs conducted to return the negative pressure system to optimal operating condition.
- (f) For Emission Points AA-002a and AA-002b, a summary detailing the date(s) and corresponding duration (in hours) in which a baghouse operates outside the recommended differential pressure drop range and any maintenance or repairs conducted to return the baghouse to optimal operating condition.
- (g) For Emission Points AA-002a, AA-002b, AA-003a and AA-003b, a summary of any maintenance / repairs conducted during the reporting period and any periods of time (including date and duration) in which a cyclone was non-operational;
- (h) A summary of any revision(s) made to the "Dust Management Plan" during the reporting period.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c)(1).)

5.C.2 For Emission Points AA-002a, AA-002b, AA-003a, and AA-003b, the permittee shall submit a written performance test protocol for the testing required by Condition 5.B.10 that details the procedures and test methods to be implemented during the actual testing event no later than thirty (30) days prior to the intended testing date.

The permittee shall notify the MDEQ in writing at least ten (10) days prior to the intended testing date so that a representative from the MDEQ may be afforded the opportunity to observe the stack testing.

If deemed necessary by the MDEQ, a conference may be required prior to the intended testing date to discuss the proposed test methods and procedures outlined in the performance testing protocol.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.6.B(5).)

5.C.3 For Emission Points AA-002a, AA-002b, AA-003a, and AA-003b, the permittee shall submit a report for the testing required by Condition 5.B.10 no later than sixty (60) days after the testing event. The report shall include the information specified in Condition 1.27(c) and the following information (as applicable):

- (a) The hourly processed wood chip throughput or hourly wood pellet production throughput for each test run (as applicable);
- (b) The feedstock ratio of softwood and hardwood used during a performance test (as applicable);
- (c) A comparison of current results [noting the average pollutant emission rate and the average applicable throughput] with any prior results from the previous five (5) years; and
- (d) The moisture content of wood chips processed during stack testing.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.6.B(6) and R. 2.2.B(11).)

- 5.C.4 For Emission Points AA-002a, AA-002b, AA-003a, and AA-003b, the permittee shall submit the results of a performance test required to demonstrate compliance with Condition 5.B.10 to the EPA no later than sixty (60) days after completion of the performance test in accordance with the following requirements:
  - (a) Submit the results of a performance test via the Compliance and Emissions Data Reporting Interface (CEDRI), which can be accessed through the EPA's CDX (<a href="https://cdx.epa.gov/">https://cdx.epa.gov/</a>). The data must be submitted in a file format generated using the EPA's Electronic Reporting Tool (ERT) as listed on the following website: (<a href="https://www.epa.gov/electronic-reporting-air-emissions/electronic-reporting-tool-ert">https://www.epa.gov/electronic-reporting-air-emissions/electronic-reporting-tool-ert</a>).

Alternatively, the permittee may submit an electronic file consistent with the extensible markup language (XML) schema listed on the EPA's ERT website. When submitting to CEDRI, choose the "State or Other Regulation – State or Other Regulation" subpart report named "Performance Test Report (Submittal via CEDRI optional for Federal reporting)".

(b) If the permittee claims some of the information submitted to EPA under paragraph (a) is "Confidential Business Information" (CBI), the permittee must submit a complete file (including information claimed to be CBI) to the EPA in accordance with 40 CFR 63.9(k), Subpart A.

Clearly mark the part or all of the information that you claim to be CBI. Information not marked as CBI may be authorized for public release without prior notice. Information marked as CBI will not be disclosed except in accordance with procedures set forth in 40 CFR Part 2 (Public Information). The permittee must submit the same file submitted to the CBI office with the CBI omitted to the EPA via the EPA's CDX as described in 40 CFR 63.9(k), Subpart A.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).)

5.C.5 For Emission Points AA-002a, AA-002b, AA-003a, and AA-003b, if an approved site-specific emission factor(s) must be modified as a result of the performance testing required by Condition 5.B.10, the permittee shall submit a written request with supporting data to the MDEQ for review and approval no later than ninety (90) days after completing the performance test.

Any modification of a site-specific emission factor shall become effective on the month corresponding with the MDEQ's approval. The MDEQ retains the right to modify a site-specific emission factor(s) based on additional performance testing.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B(11).)

# SECTION 6. ALTERNATIVE OPERATING SCENARIOS

6.1 None permitted.

# SECTION 7. TITLE VI REQUIREMENTS

The following are applicable or potentially applicable requirements originating from Title VI of the Clean Air Act – Stratospheric Ozone Protection. The full text of the referenced regulations may be found on-line at <a href="http://www.ecfr.gov/">http://www.ecfr.gov/</a> under Title 40, or DEQ shall provide a copy upon request from the permittee.

- 7.1 If the permittee produces, transforms, destroys, imports or exports a controlled substance or imports or exports a controlled product, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart A Production and Consumption Controls.
- 7.2 If the permittee performs service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart B Servicing of Motor Vehicle Air Conditioners.
- 7.3 The permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart E The Labeling of Products Using Ozone-Depleting Substances, for the following containers and products:
  - (a) All containers in which a class I or class II substance is stored or transported;
  - (b) All products containing a class I substance; and
  - (c) All products directly manufactured with a process that uses a class I substance, unless otherwise exempted by this subpart or, unless EPA determines for a particular product that there are no substitute products or manufacturing processes for such product that do not rely on the use of a class I substance, that reduce overall risk to human health and the environment, and that are currently or potentially available. If the EPA makes such a determination for a particular product, then the requirements of this subpart are effective for such product no later than January 1, 2015.
- 7.4 If the permittee performs any of the following activities, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart F Recycling and Emissions Reduction:
  - (a) Servicing, maintaining, or repairing appliances containing class I, class II or non-exempt substitute refrigerants;
  - (b) Disposing of appliances, including small appliances and motor vehicle air conditioners; or
  - (c) Refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturers of recycling and recovery

equipment, approved recycling and recovery equipment testing organizations, as well as persons selling, offering for sale, and/or purchasing class I, class II, or non-exempt substitute refrigerants.

- 7.5 The permittee shall be allowed to switch from any ozone-depleting substance to any acceptable alternative that is listed in the Significant New Alternatives Policy (SNAP) program promulgated pursuant to 40 CFR Part 82, Subpart G Significant New Alternatives Policy Program. The permittee shall also comply with any use conditions for the acceptable alternative substance.
- 7.6 If the permittee performs any of the following activities, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart H Halon Emissions Reduction:
  - (a) Any person testing, servicing, maintaining, repairing, or disposing of equipment that contains halons or using such equipment during technician training;
  - (b) Any person disposing of halons;
  - (c) Manufacturers of halon blends; or
  - (d) Organizations that employ technicians who service halon-containing equipment.

# APPENDIX A

# **List of Abbreviations Used In this Permit**

BACT Best Available Control Technology CEM Continuous Emission Monitor

CEM Continuous Emission Monitor
CEMS Continuous Emission Monitoring System

CFR Code of Federal Regulations

CO Carbon Monoxide

COM Continuous Opacity Monitor

COMS Continuous Opacity Monitoring System

DEQ Mississippi Department of Environmental Quality EPA United States Environmental Protection Agency

gr/dscf Grains Per Dry Standard Cubic Foot

HP Horsepower

HAP Hazardous Air Pollutant lb/hr Pounds per Hour

M or K Thousand

MACT Maximum Achievable Control Technology

MM Million

MMBTUH Million British Thermal Units per Hour

NA Not Applicable

NAAQS National Ambient Air Quality Standards

NESHAP National Emissions Standards for Hazardous Air

Pollutants, 40 CFR 61, or National Emission Standards for

Hazardous Air Pollutants for Source Categories, 40 CFR 63

NMVOC Non-Methane Volatile Organic Compounds

NO<sub>x</sub> Nitrogen Oxides

NSPS New Source Performance Standards, 40 CFR 60

O&M Operation and Maintenance

PM Particulate Matter

PM $_{10}$  Particulate Matter less than 10 μm in diameter PM $_{2.5}$  Particulate Matter less than 2.5 μm in diameter

ppm Parts per Million

PSD Prevention of Significant Deterioration

SIP State Implementation Plan

SO<sub>2</sub> Sulfur Dioxide

SSM Startup, Shutdown, and Malfunction

TPY Tons per Year
TRS Total Reduced Sulfur

VEE Visible Emissions Evaluation VHAP Volatile Hazardous Air Pollutant

VOHAP Volatile Organic Hazardous Air Pollutant

VOC Volatile Organic Compound